

Package: devtools (via r-universe)

January 17, 2025

Title Tools to Make Developing R Packages Easier

Version 2.4.5.9000

Description Collection of package development tools.

License MIT + file LICENSE

URL <https://devtools.r-lib.org/>, <https://github.com/r-lib/devtools>

BugReports <https://github.com/r-lib/devtools/issues>

Depends R (>= 3.6), usethis (>= 2.1.6)

Imports cli (>= 3.3.0), desc (>= 1.4.1), ellipsis (>= 0.3.2), fs (>= 1.5.2), lifecycle (>= 1.0.1), memoise (>= 2.0.1), miniUI (>= 0.1.1.1), pkgbuild (>= 1.3.1), pkgdown (>= 2.0.6), pkgload (>= 1.3.0), profvis (>= 0.3.7), rcmdcheck (>= 1.4.0), remotes (>= 2.4.2), rlang (>= 1.0.4), roxygen2 (>= 7.2.1), rversions (>= 2.1.1), sessioninfo (>= 1.2.2), stats, testthat (>= 3.2.0), tools, urlchecker (>= 1.0.1), utils, withr (>= 2.5.0)

Suggests BiocManager (>= 1.30.18), callr (>= 3.7.1), covr (>= 3.5.1), curl (>= 4.3.2), digest (>= 0.6.29), DT (>= 0.23), foghorn (>= 1.4.2), gh (>= 1.3.0), gmailr (>= 1.0.1), httr (>= 1.4.3), knitr (>= 1.39), lintr (>= 3.0.0), MASS, mockery (>= 0.4.3), pingr (>= 2.0.1), rhub (>= 1.1.1), rmarkdown (>= 2.14), rstudioapi (>= 0.13), spelling (>= 2.2)

VignetteBuilder knitr

Remotes r-lib/testthat

Config/Needs/website tidyverse/tidytemplate

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Config/pak/sysreqs libfontconfig1-dev libfreetype6-dev libfribidi-dev
 git make libharfbuzz-dev libgit2-dev libicu-dev libjpeg-dev
 libpng-dev libtiff-dev libxml2-dev libssl-dev libx11-dev
 zlib1g-dev

Repository <https://ar-puuk.r-universe.dev>

RemoteUrl <https://github.com/r-lib/devtools>

RemoteRef HEAD

RemoteSha 6ec478bbb26645c6fda6d1c518b27e7f478fc91e

Contents

bash	3
build	3
build_manual	5
build_rmd	6
build_site	6
build_vignettes	7
check	8
check_mac_release	11
check_man	12
check_rhub	12
check_win	13
clean_vignettes	15
create	15
dev_sitrep	16
document	17
install	17
install_deps	19
lint	21
load_all	21
missing_s3	23
release	24
reload	25
run_examples	25
save_all	26
show_news	27
source_gist	27
source_url	28
spell_check	29
test	29
uninstall	30
wd	31

Index

32

bash	<i>Open bash shell in package directory.</i>
------	--

Description

Open bash shell in package directory.

Usage

```
bash(pkg = ".")
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
-----	---

build	<i>Build package</i>
-------	----------------------

Description

Building converts a package source directory into a single bundled file. If `binary = FALSE` this creates a `tar.gz` package that can be installed on any platform, provided they have a full development environment (although packages without source code can typically be installed out of the box). If `binary = TRUE`, the package will have a platform specific extension (e.g. `.zip` for windows), and will only be installable on the current platform, but no development environment is needed.

Usage

```
build(  
  pkg = ".",  
  path = NULL,  
  binary = FALSE,  
  vignettes = TRUE,  
  manual = FALSE,  
  args = NULL,  
  quiet = FALSE,  
  ...  
)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
path	Path in which to produce package. If NULL, defaults to the parent directory of the package.
binary	Produce a binary (<code>--binary</code>) or source (<code>--no-manual --no-resave-data</code>) version of the package.
vignettes, manual	For source packages: if FALSE, don't build PDF vignettes (<code>--no-build-vignettes</code>) or manual (<code>--no-manual</code>).
args	An optional character vector of additional command line arguments to be passed to R CMD build if <code>binary = FALSE</code> , or R CMD install if <code>binary = TRUE</code> .
quiet	if TRUE suppresses output from this function.
...	Additional arguments passed to pkgbuild::build .

Details**Configuration:**

DESCRIPTION *entries*:

- `Config/build/clean-inst-doc` can be set to FALSE to avoid cleaning up `inst/doc` when building a source package. Set it to TRUE to force a cleanup. See the `clean_doc` argument.
- `Config/build/copy-method` can be used to avoid copying large directories in R CMD build. It works by copying (or linking) the files of the package to a temporary directory, leaving out the (possibly large) files that are not part of the package. Possible values:
 - none: pkgbuild does not copy the package tree. This is the default.
 - copy: the package files are copied to a temporary directory before R CMD build.
 - link: the package files are symbolic linked to a temporary directory before R CMD build. Windows does not have symbolic links, so on Windows this is equivalent to copy.
 You can also use the `pkg.build_copy_method` option or the `PKG_BUILD_COPY_METHOD` environment variable to set the copy method. The option is consulted first, then the DESCRIPTION entry, then the environment variable.
- `Config/build/extra-sources` can be used to define extra source files for pkgbuild to decide whether a package DLL needs to be recompiled in `needs_compile()`. The syntax is a comma separated list of file names, or globs. (See [utils::glob2rx\(\)](#).) E.g. `src/rust/src/*.rs` or `configure*`.
- `Config/build/bootstrap` can be set to TRUE to run `Rscript bootstrap.R` in the source directory prior to running subsequent build steps.

Options:

- `pkg.build_copy_method`: use this option to avoid copying large directories when building a package. See possible values above, at the `Config/build/copy-method` DESCRIPTION entry.
- `pkg.build_stop_for_warnings`: if it is set to TRUE, then pkgbuild will stop for R CMD build errors. It takes precedence over the `PKG_BUILD_STOP_FOR_WARNINGS` environment variable.

Environment variables:

- `PKG_BUILD_COLOR_DIAGNOSTICS`: set it to `false` to opt out of colored compiler diagnostics. Set it to `true` to force colored compiler diagnostics.
- `PKG_BUILD_COPY_METHOD`: use this environment variable to avoid copying large directories when building a package. See possible values above, at the `Config/build/copy-method DESCRIPTION` entry.

will stop for R CMD build errors. The `pkg.build_stop_for_warnings` option takes precedence over this environment variable.

Value

a string giving the location (including file name) of the built package

Note

The default `manual = FALSE` is not suitable for a CRAN submission, which may require `manual = TRUE`. Even better, use [submit_cran\(\)](#) or [release\(\)](#).

build_manual	<i>Create package pdf manual</i>
--------------	----------------------------------

Description

Create package pdf manual

Usage

```
build_manual(pkg = ".", path = NULL)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
path	path in which to produce package manual. If <code>NULL</code> , defaults to the parent directory of the package.

See Also

[Rd2pdf\(\)](#)

build_rmd	<i>Build a Rmarkdown files package</i>
-----------	--

Description

build_rmd() is a wrapper around `rmarkdown::render()` that first installs a temporary copy of the package, and then renders each .Rmd in a clean R session. build_readme() locates your README.Rmd and builds it into a README.md

Usage

```
build_rmd(files, path = ".", output_options = list(), ..., quiet = TRUE)
```

```
build_readme(path = ".", quiet = TRUE, ...)
```

Arguments

files	The Rmarkdown files to be rendered.
path	path to the package to build the readme.
output_options	List of output options that can override the options specified in metadata (e.g. could be used to force self_contained or mathjax = "local"). Note that this is only valid when the output format is read from metadata (i.e. not a custom format object passed to output_format).
...	additional arguments passed to <code>rmarkdown::render()</code>
quiet	If TRUE, suppress output.

build_site	<i>Execute pkgdown build_site in a package</i>
------------	---

Description

build_site() is a shortcut for `pkgdown::build_site()`, it generates the static HTML documentation.

Usage

```
build_site(path = ".", quiet = TRUE, ...)
```

Arguments

path	path to the package to build the static HTML.
quiet	If TRUE, suppress output.
...	additional arguments passed to <code>pkgdown::build_site()</code>

build_vignettes	<i>Build package vignettes.</i>
-----------------	---------------------------------

Description

Builds package vignettes using the same algorithm that R CMD build does. This means including non-Sweave vignettes, using makefiles (if present), and copying over extra files. The files are copied in the 'doc' directory and an vignette index is created in 'Meta/vignette.rds', as they would be in a built package. 'doc' and 'Meta' are added to .Rbuildignore, so will not be included in the built package. These files can be checked into version control, so they can be viewed with browseVignettes() and vignette() if the package has been loaded with load_all() without needing to re-build them locally.

Usage

```
build_vignettes(
  pkg = ".",
  dependencies = "VignetteBuilder",
  clean = TRUE,
  upgrade = "never",
  quiet = FALSE,
  install = TRUE,
  keep_md = TRUE
)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
dependencies	Which dependencies do you want to check? Can be a character vector (selecting from "Depends", "Imports", "LinkingTo", "Suggests", or "Enhances"), or a logical vector. TRUE is shorthand for "Depends", "Imports", "LinkingTo" and "Suggests". NA is shorthand for "Depends", "Imports" and "LinkingTo" and is the default. FALSE is shorthand for no dependencies (i.e. just check this package, not its dependencies). The value "soft" means the same as TRUE, "hard" means the same as NA. You can also specify dependencies from one or more additional fields, common ones include: <ul style="list-style-type: none"> • Config/Needs/website - for dependencies used in building the pkgdown site. • Config/Needs/coverage for dependencies used in calculating test coverage.
clean	Remove all files generated by the build, even if there were copies there before.
upgrade	Should package dependencies be upgraded? One of "default", "ask", "always", or "never". "default" respects the value of the R_REMOTES_UPGRADE environment variable if set, and falls back to "ask" if unset. "ask" prompts the user for which

	out of date packages to upgrade. For non-interactive sessions "ask" is equivalent to "always". TRUE and FALSE are also accepted and correspond to "always" and "never" respectively.
quiet	If TRUE, suppresses most output. Set to FALSE if you need to debug.
install	If TRUE, install the package before building vignettes.
keep_md	If TRUE, move md intermediates as well as rendered outputs. Most useful when using the keep_md YAML option for Rmarkdown outputs. See https://bookdown.org/yihui/rmarkdown/html-document.html#keeping-markdown .

See Also

[clean_vignettes\(\)](#) to remove the pdfs in 'doc' created from vignettes

[clean_vignettes\(\)](#) to remove build tex/pdf files.

check	<i>Build and check a package</i>
-------	----------------------------------

Description

`check()` automatically builds and checks a source package, using all known best practices. `check_built()` checks an already-built package.

Passing R CMD check is essential if you want to submit your package to CRAN: you must not have any **ERRORS** or **WARNINGS**, and you want to ensure that there are as few **NOTES** as possible. If you are not submitting to CRAN, at least ensure that there are no **ERRORS** or **WARNINGS**: these typically represent serious problems.

`check()` automatically builds a package before calling `check_built()`, as this is the recommended way to check packages. Note that this process runs in an independent R session, so nothing in your current workspace will affect the process. Under-the-hood, `check()` and `check_built()` rely on `pkgbuild::build()` and `rcmdcheck::rcmdcheck()`.

Usage

```
check(
  pkg = ".",
  document = NULL,
  build_args = NULL,
  ...,
  manual = FALSE,
  cran = TRUE,
  remote = FALSE,
  incoming = remote,
  force_suggests = FALSE,
  run_dont_test = FALSE,
  args = "--timings",
  env_vars = c(NOT_CRAN = "true"),
```



```

  quiet = FALSE,
  check_dir = NULL,
  cleanup = deprecated(),
  vignettes = TRUE,
  error_on = c("never", "error", "warning", "note")
)

check_built(
  path = NULL,
  cran = TRUE,
  remote = FALSE,
  incoming = remote,
  force_suggests = FALSE,
  run_dont_test = FALSE,
  manual = FALSE,
  args = "--timings",
  env_vars = NULL,
  check_dir = tempdir(),
  quiet = FALSE,
  error_on = c("never", "error", "warning", "note")
)

```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
document	By default (NULL) will document if your installed roxygen2 version matches the version declared in the DESCRIPTION file. Use TRUE or FALSE to override the default.
build_args	Additional arguments passed to R CMD build
...	Additional arguments passed on to <code>pkgbuild::build()</code> .
manual	If FALSE, don't build and check manual (<code>--no-manual</code>).
cran	if TRUE (the default), check using the same settings as CRAN uses. Because this is a moving target and is not uniform across all of CRAN's machine, this is on a "best effort" basis. It is more complicated than simply setting <code>--as-cran</code> .
remote	Sets <code>_R_CHECK_CRAN_INCOMING_REMOTE_</code> env var. If TRUE, performs a number of CRAN incoming checks that require remote access.
incoming	Sets <code>_R_CHECK_CRAN_INCOMING_</code> env var. If TRUE, performs a number of CRAN incoming checks.
force_suggests	Sets <code>_R_CHECK_FORCE_SUGGESTS_</code> . If FALSE (the default), check will proceed even if all suggested packages aren't found.
run_dont_test	Sets <code>--run-donttest</code> so that examples surrounded in <code>\donttest{}</code> are also run. When <code>cran = TRUE</code> , this only affects R 3.6 and earlier; in R 4.0, code in <code>\donttest{}</code> is always run as part of CRAN submission.

args	Character vector of arguments to pass to R CMD check. Pass each argument as a single element of this character vector (do not use spaces to delimit arguments like you would in the shell). For example, to skip running of examples and tests, use <code>args = c("--no-examples", "--no-tests")</code> and not <code>args = "--no-examples --no-tests"</code> . (Note that instead of the <code>--output</code> option you should use the <code>check_dir</code> argument, because <code>--output</code> cannot deal with spaces and other special characters on Windows.)
env_vars	Environment variables set during R CMD check
quiet	if TRUE suppresses output from this function.
check_dir	Path to a directory where the check is performed. If this is not NULL, then the a temporary directory is used, that is cleaned up when the returned object is garbage collected.
cleanup	[Deprecated] See <code>check_dir</code> for details.
vignettes	If FALSE, do not build or check vignettes, equivalent to using <code>args = '--ignore-vignettes'</code> and <code>build_args = '--no-build-vignettes'</code> .
error_on	Whether to throw an error on R CMD check failures. Note that the check is always completed (unless a timeout happens), and the error is only thrown after completion. error_on is passed through to <code>rcmdcheck::rcmdcheck()</code> , which is the definitive source for what the different values mean. If not specified by the user, both <code>check()</code> and <code>check_built()</code> default to <code>error_on = "never"</code> in interactive use and "warning" in a non-interactive setting.
path	Path to built package.

Value

An object containing errors, warnings, notes, and more.

Environment variables

Devtools does its best to set up an environment that combines best practices with how check works on CRAN. This includes:

- The standard environment variables set by devtools: `r_env_vars()`. Of particular note for package tests is the `NOT_CRAN` env var, which lets you know that your tests are running somewhere other than CRAN, and hence can take a reasonable amount of time.
- Debugging flags for the compiler, set by `compiler_flags(FALSE)`.
- If `aspell` is found, `_R_CHECK_CRAN_INCOMING_USE_ASPELL_` is set to TRUE. If no spell checker is installed, a warning is issued.
- Environment variables, controlled by arguments `incoming`, `remote` and `force_suggests`.

See Also

`release()` if you want to send the checked package to CRAN.

check_mac_release *Check a package on macOS*

Description

This function first bundles a source package, then uploads it to <https://mac.r-project.org/macbuilder/submit.html>. This function returns a link to the page where the check results will appear.

Usage

```
check_mac_release(  
  pkg = ".",  
  dep_pkgs = character(),  
  args = NULL,  
  manual = TRUE,  
  quiet = FALSE,  
  ...  
)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
dep_pkgs	Additional custom dependencies to install prior to checking the package.
args	An optional character vector of additional command line arguments to be passed to R CMD build if binary = FALSE, or R CMD install if binary = TRUE.
manual	Should the manual be built?
quiet	If TRUE, suppresses output.
...	Additional arguments passed to pkgbuild::build() .

Value

The url with the check results (invisibly)

See Also

Other build functions: [check_rhub\(\)](#), [check_win\(\)](#)

check_man	<i>Check documentation, as R CMD check does.</i>
-----------	--

Description

This function attempts to run the documentation related checks in the same way that R CMD check does. Unfortunately it can't run them all because some tests require the package to be loaded, and the way they attempt to load the code conflicts with how devtools does it.

Usage

```
check_man(pkg = ".")
```

Arguments

pkg The package to use, can be a file path to the package or a package object. See [as.package\(\)](#) for more information.

Value

Nothing. This function is called purely for its side effects: if no errors there will be no output.

Examples

```
## Not run:  
check_man("mypkg")  
  
## End(Not run)
```

check_rhub	<i>Run CRAN checks for package on R-hub</i>
------------	---

Description

It runs [build\(\)](#) on the package, with the arguments specified in `args`, and then submits it to the R-hub builder at <https://builder.r-hub.io>. The `interactive` option controls whether the function waits for the check output. Regardless, after the check is complete, R-hub sends an email with the results to the package maintainer.

Usage

```

check_rhub(
  pkg = ".",
  platforms = NULL,
  email = NULL,
  interactive = TRUE,
  build_args = NULL,
  ...
)

```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
platforms	R-hub platforms to run the check on. If NULL uses default list of CRAN checkers (one for each major platform, and one with extra checks if you have compiled code). You can also specify your own, see rhub::platforms() for a complete list.
email	email address to notify, defaults to the maintainer address in the package.
interactive	whether to show the status of the build interactively. R-hub will send an email to the package maintainer's email address, regardless of whether the check is interactive or not.
build_args	Arguments passed to R CMD build
...	extra arguments, passed to rhub::check_for_cran() .

Value

a rhub_check object.

About email validation on r-hub

To build and check R packages on R-hub, you need to validate your email address. This is because R-hub sends out emails about build results. See more at [rhub::validate_email\(\)](#).

See Also

Other build functions: [check_mac_release\(\)](#), [check_win\(\)](#)

check_win

Check a package on Windows

Description

This function first bundles a source package, then uploads it to <https://win-builder.r-project.org/>. Once the service has built and checked the package, an email is sent to address of the maintainer listed in DESCRIPTION. This usually takes around 30 minutes. The email contains a link to a directory with the package binary and check logs, which will be deleted after a couple of days.

Usage

```
check_win_devel(  
  pkg = ".",  
  args = NULL,  
  manual = TRUE,  
  email = NULL,  
  quiet = FALSE,  
  ...  
)  
  
check_win_release(  
  pkg = ".",  
  args = NULL,  
  manual = TRUE,  
  email = NULL,  
  quiet = FALSE,  
  ...  
)  
  
check_win_oldrelease(  
  pkg = ".",  
  args = NULL,  
  manual = TRUE,  
  email = NULL,  
  quiet = FALSE,  
  ...  
)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
args	An optional character vector of additional command line arguments to be passed to R CMD build if binary = FALSE, or R CMD install if binary = TRUE.
manual	Should the manual be built?
email	An alternative email address to use. If NULL, the default is to use the package maintainer's email.
quiet	If TRUE, suppresses output.
...	Additional arguments passed to pkgbuild::build() .

Functions

- `check_win_devel()`: Check package on the development version of R.
- `check_win_release()`: Check package on the released version of R.
- `check_win_oldrelease()`: Check package on the previous major release version of R.

See Also

Other build functions: [check_mac_release\(\)](#), [check_rhub\(\)](#)

clean_vignettes	<i>Clean built vignettes.</i>
-----------------	-------------------------------

Description

This uses a fairly rudimentary algorithm where any files in ‘doc’ with a name that exists in ‘vignettes’ are removed.

Usage

```
clean_vignettes(pkg = ".")
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
-----	---

create	<i>Create a package</i>
--------	-------------------------

Description

Create a package

Usage

```
create(path, ..., open = FALSE)
```

Arguments

path	A path. If it exists, it is used. If it does not exist, it is created, provided that the parent path exists.
...	Additional arguments passed to usethis::create_package()
open	If TRUE, activates the new project: <ul style="list-style-type: none"> • If using RStudio desktop, the package is opened in a new session. • If on RStudio server, the current RStudio project is activated. • Otherwise, the working directory and active project is changed.

Value

The path to the created package, invisibly.

`dev_sitrep`*Report package development situation*

Description

`dev_sitrep()` reports

- If R is up to date
- If RStudio is up to date
- If compiler build tools are installed and available for use
- If devtools and its dependencies are up to date
- If the package's dependencies are up to date

Call this function if things seem weird and you're not sure what's wrong or how to fix it. If this function returns no output everything should be ready for package development.

Usage

```
dev_sitrep(pkg = ".", debug = FALSE)
```

Arguments

<code>pkg</code>	The package to use, can be a file path to the package or a package object. See as.package() for more information.
<code>debug</code>	If TRUE, will print out extra information useful for debugging. If FALSE, it will use result cached from a previous run.

Value

A named list, with S3 class `dev_sitrep` (for printing purposes).

Examples

```
## Not run:  
dev_sitrep()  
  
## End(Not run)
```

document *Use roxygen to document a package.*

Description

This function is a wrapper for the `roxygen2::roxygenize()` function from the `roxygen2` package. See the documentation and vignettes of that package to learn how to use `roxygen`.

Usage

```
document(pkg = ".", roclets = NULL, quiet = FALSE)
```

Arguments

<code>pkg</code>	The package to use, can be a file path to the package or a package object. See as.package() for more information.
<code>roclets</code>	Character vector of roclet names to use with package. The default, <code>NULL</code> , uses the <code>roxygen</code> <code>roclets</code> option, which defaults to <code>c("collate", "namespace", "rd")</code> .
<code>quiet</code>	if <code>TRUE</code> suppresses output from this function.

See Also

[roxygen2::roxygenize\(\)](#), [browseVignettes\("roxygen2"\)](#)

install *Install a local development package.*

Description

Uses R CMD `INSTALL` to install the package. Will also try to install dependencies of the package from CRAN, if they're not already installed.

Usage

```
install(
  pkg = ".",
  reload = TRUE,
  quick = FALSE,
  build = !quick,
  args = getOption("devtools.install.args"),
  quiet = FALSE,
  dependencies = NA,
  upgrade = "default",
  build_vignettes = FALSE,
```

```

    keep_source = getOption("keep.source.pkgs"),
    force = FALSE,
    ...
)

```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
reload	if TRUE (the default), will automatically reload the package after installing.
quick	if TRUE skips docs, multiple-architectures, demos, and vignettes, to make installation as fast as possible.
build	if TRUE <code>pkgbuild::build()</code> s the package first: this ensures that the installation is completely clean, and prevents any binary artefacts (like <code>‘.o’</code> , <code>.so</code>) from appearing in your local package directory, but is considerably slower, because every compile has to start from scratch.
args	An optional character vector of additional command line arguments to be passed to R CMD INSTALL. This defaults to the value of the option <code>"devtools.install.args"</code> .
quiet	If TRUE, suppress output.
dependencies	<p>Which dependencies do you want to check? Can be a character vector (selecting from "Depends", "Imports", "LinkingTo", "Suggests", or "Enhances"), or a logical vector.</p> <p>TRUE is shorthand for "Depends", "Imports", "LinkingTo" and "Suggests". NA is shorthand for "Depends", "Imports" and "LinkingTo" and is the default. FALSE is shorthand for no dependencies (i.e. just check this package, not its dependencies).</p> <p>The value "soft" means the same as TRUE, "hard" means the same as NA.</p> <p>You can also specify dependencies from one or more additional fields, common ones include:</p> <ul style="list-style-type: none"> • <code>Config/Needs/website</code> - for dependencies used in building the pkgdown site. • <code>Config/Needs/coverage</code> for dependencies used in calculating test coverage.
upgrade	Should package dependencies be upgraded? One of "default", "ask", "always", or "never". "default" respects the value of the <code>R_REMOTES_UPGRADE</code> environment variable if set, and falls back to "ask" if unset. "ask" prompts the user for which out of date packages to upgrade. For non-interactive sessions "ask" is equivalent to "always". TRUE and FALSE are also accepted and correspond to "always" and "never" respectively.
build_vignettes	if TRUE, will build vignettes. Normally it is <code>build</code> that's responsible for creating vignettes; this argument makes sure vignettes are built even if a build never happens (i.e. because <code>build = FALSE</code>).
keep_source	If TRUE will keep the <code>srcfiles</code> from an installed package. This is useful for debugging (especially inside of RStudio). It defaults to the option <code>"keep.source.pkgs"</code> .
force	Force installation, even if the remote state has not changed since the previous install.

... additional arguments passed to `remotes::install_deps()` when installing dependencies.

Details

If `quick = TRUE`, installation takes place using the current package directory. If you have compiled code, this means that artefacts of compilation will be created in the `src/` directory. If you want to avoid this, you can use `build = TRUE` to first build a package bundle and then install it from a temporary directory. This is slower, but keeps the source directory pristine.

If the package is loaded, it will be reloaded after installation. This is not always completely possible, see `reload()` for caveats.

To install a package in a non-default library, use `withr::with_libpaths()`.

See Also

`update_packages()` to update installed packages from the source location and `with_debug()` to install packages with debugging flags set.

Other package installation: `uninstall()`

install_deps

Install package dependencies if needed.

Description

`install_deps()` will install the user dependencies needed to run the package, `install_dev_deps()` will also install the development dependencies needed to test and build the package.

Usage

```
install_deps(
  pkg = ".",
  dependencies = NA,
  repos = getOption("repos"),
  type = getOption("pkgType"),
  upgrade = c("default", "ask", "always", "never"),
  quiet = FALSE,
  build = TRUE,
  build_opts = c("--no-resave-data", "--no-manual", "--no-build-vignettes"),
  ...
)
```

```
install_dev_deps(
  pkg = ".",
  dependencies = TRUE,
  repos = getOption("repos"),
  type = getOption("pkgType"),
```

```

upgrade = c("default", "ask", "always", "never"),
quiet = FALSE,
build = TRUE,
build_opts = c("--no-resave-data", "--no-manual", " --no-build-vignettes"),
...
)

```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
dependencies	Which dependencies do you want to check? Can be a character vector (selecting from "Depends", "Imports", "LinkingTo", "Suggests", or "Enhances"), or a logical vector. TRUE is shorthand for "Depends", "Imports", "LinkingTo" and "Suggests". NA is shorthand for "Depends", "Imports" and "LinkingTo" and is the default. FALSE is shorthand for no dependencies (i.e. just check this package, not its dependencies). The value "soft" means the same as TRUE, "hard" means the same as NA. You can also specify dependencies from one or more additional fields, common ones include: <ul style="list-style-type: none"> • Config/Needs/website - for dependencies used in building the pkgdown site. • Config/Needs/coverage for dependencies used in calculating test coverage.
repos	A character vector giving repositories to use.
type	Type of package to update.
upgrade	Should package dependencies be upgraded? One of "default", "ask", "always", or "never". "default" respects the value of the R_REMOTES_UPGRADE environment variable if set, and falls back to "ask" if unset. "ask" prompts the user for which out of date packages to upgrade. For non-interactive sessions "ask" is equivalent to "always". TRUE and FALSE are also accepted and correspond to "always" and "never" respectively.
quiet	If TRUE, suppress output.
build	if TRUE <code>pkgbuild::build()</code> s the package first: this ensures that the installation is completely clean, and prevents any binary artefacts (like <code>‘.o’</code> , <code>.so</code>) from appearing in your local package directory, but is considerably slower, because every compile has to start from scratch.
build_opts	Options to pass to R CMD build, only used when build is TRUE.
...	additional arguments passed to <code>remotes::install_deps()</code> when installing dependencies.

Examples

```
## Not run: install_deps(".")
```

lint	<i>Lint all source files in a package</i>
------	---

Description

The default linters correspond to the style guide at <https://style.tidyverse.org/>, however it is possible to override any or all of them using the `linters` parameter.

Usage

```
lint(pkg = ".", cache = TRUE, ...)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
cache	Store the lint results so repeated lints of the same content use the previous results. Consult the <code>lintr</code> package to learn more about its caching behaviour.
...	Additional arguments passed to <code>lintr::lint_package()</code> .

See Also

[lintr::lint_package\(\)](#), [lintr::lint\(\)](#)

load_all	<i>Load complete package</i>
----------	------------------------------

Description

`load_all()` loads a package. It roughly simulates what happens when a package is installed and loaded with `library()`, without having to first install the package. It:

- Loads all data files in `data/`. See [load_data\(\)](#) for more details.
- Sources all R files in the `R` directory, storing results in environment that behaves like a regular package namespace. See [load_code\(\)](#) for more details.
- Adds a shim from `system.file()` to `shim_system.file()` in the imports environment of the package. This ensures that `system.file()` works with both development and installed packages despite their differing directory structures.
- Adds shims from `help()` and `?` to `shim_help()` and `shim_question()` to make it easier to preview development documentation.
- Compiles any C, C++, or Fortran code in the `src/` directory and connects the generated DLL into R. See `pkgbuild::compile_dll()` for more details.
- Loads any compiled translations in `inst/po`.

- Runs `.onAttach()`, `.onLoad()` and `.onUnload()` functions at the correct times.
- If you use **testthat**, will load all test helpers so you can access them interactively. `devtools` sets the `DEVTOOLS_LOAD` environment variable to the package name to let you check whether the helpers are run during package loading.

`is_loading()` returns `TRUE` when it is called while `load_all()` is running. This may be useful e.g. in `.onLoad` hooks.

Usage

```
load_all(
  path = ".",
  reset = TRUE,
  recompile = FALSE,
  export_all = TRUE,
  helpers = TRUE,
  quiet = FALSE,
  ...
)
```

Arguments

<code>path</code>	Path to a package, or within a package.
<code>reset</code>	clear package environment and reset file cache before loading any pieces of the package. This largely equivalent to running <code>unload()</code> , however the old namespaces are not completely removed and no <code>.onUnload()</code> hooks are called. Use <code>reset = FALSE</code> may be faster for large code bases, but is a significantly less accurate approximation.
<code>recompile</code>	DEPRECATED. force a recompile of DLL from source code, if present. This is equivalent to running <code>pkgbuild::clean_dll()</code> before <code>load_all()</code>
<code>export_all</code>	If <code>TRUE</code> (the default), export all objects. If <code>FALSE</code> , export only the objects that are listed as exports in the <code>NAMESPACE</code> file.
<code>helpers</code>	if <code>TRUE</code> loads testthat test helpers.
<code>quiet</code>	if <code>TRUE</code> suppresses output from this function.
<code>...</code>	Additional arguments passed to <code>pkgload::load_all()</code> .

Differences to regular loading

`load_all()` tries its best to reproduce the behaviour of `loadNamespace()` and `library()`. However it deviates from normal package loading in several ways.

- `load_all()` doesn't install the package to a library, so `system.file()` doesn't work. `pkgload` fixes this for the package itself installing a shim, `shim_system.file()`. However, this shim is not visible to third party packages, so they will fail if they attempt to find files within your package. One potential workaround is to use `fs::path_package()` instead of `system.file()`, since that understands the mechanisms that `devtools` uses to load packages.
- `load_all()` loads all packages referenced in `Imports` at load time, but `loadNamespace()` and `library()` only load package dependencies as they are needed.

- `load_all()` copies all objects (not just the ones listed as exports) into the package environment. This is useful during development because it makes internal objects easy to access. To export only the objects listed as exports, use `export_all = FALSE`. This more closely simulates behavior when loading an installed package with `library()`, and can be useful for checking for missing exports.

Examples

```
## Not run:
# Load the package in the current directory
load_all("./")

# Running again loads changed files
load_all("./")

# With reset=TRUE, unload and reload the package for a clean start
load_all("./", TRUE)

# With export_all=FALSE, only objects listed as exports in NAMESPACE
# are exported
load_all("./", export_all = FALSE)

## End(Not run)
```

missing_s3

Find missing s3 exports.

Description

The method is heuristic - looking for objs with a period in their name.

Usage

```
missing_s3(pkg = ".")
```

Arguments

`pkg` The package to use, can be a file path to the package or a package object. See [as.package\(\)](#) for more information.

release	<i>Release package to CRAN.</i>
---------	---------------------------------

Description

Run automated and manual tests, then post package to CRAN.

Usage

```
release(pkg = ".", check = FALSE, args = NULL)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
check	if TRUE, run checking, otherwise omit it. This is useful if you've just checked your package and you're ready to release it.
args	An optional character vector of additional command line arguments to be passed to R CMD build.

Details

The package release process will:

- Confirm that the package passes R CMD check on relevant platforms
- Confirm that important files are up-to-date
- Build the package
- Submit the package to CRAN, using comments in "cran-comments.md"

You can add arbitrary extra questions by defining an (un-exported) function called `release_questions()` that returns a character vector of additional questions to ask.

You also need to read the CRAN repository policy at '<https://cran.r-project.org/web/packages/policies.html>' and make sure you're in line with the policies. `release` tries to automate as many of polices as possible, but it's impossible to be completely comprehensive, and they do change in between releases of devtools.

See Also

[usethis::use_release_issue\(\)](#) to create a checklist of release tasks that you can use in addition to or in place of `release`.

reload	<i>Unload and reload package.</i>
--------	-----------------------------------

Description

This attempts to unload and reload an *installed* package. If the package is not loaded already, it does nothing. It's not always possible to cleanly unload a package: see the caveats in [unload\(\)](#) for some of the potential failure points. If in doubt, restart R and reload the package with [library\(\)](#).

Usage

```
reload(pkg = ".", quiet = FALSE)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
quiet	if TRUE suppresses output from this function.

See Also

[load_all\(\)](#) to load a package for interactive development.

Examples

```
## Not run:  
# Reload package that is in current directory  
reload(".")  
  
# Reload package that is in ./ggplot2/  
reload("ggplot2/")  
  
# Can use inst() to find the package path  
# This will reload the installed ggplot2 package  
reload(pkgload::inst("ggplot2"))  
  
## End(Not run)
```

run_examples	<i>Run all examples in a package.</i>
--------------	---------------------------------------

Description

One of the most frustrating parts of R CMD check is getting all of your examples to pass - whenever one fails you need to fix the problem and then restart the whole process. This function makes it a little easier by making it possible to run all examples from an R function.

Usage

```
run_examples(
  pkg = ".",
  start = NULL,
  show = deprecated(),
  run_donttest = FALSE,
  run_dontrun = FALSE,
  fresh = FALSE,
  document = TRUE,
  run = deprecated(),
  test = deprecated()
)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
start	Where to start running the examples: this can either be the name of Rd file to start with (with or without extensions), or a topic name. If omitted, will start with the (lexicographically) first file. This is useful if you have a lot of examples and don't want to rerun them every time you fix a problem.
show	DEPRECATED.
run_donttest	if TRUE, do run \donttest sections in the Rd files.
run_dontrun	if TRUE, do run \dontrun sections in the Rd files.
fresh	if TRUE, will be run in a fresh R session. This has the advantage that there's no way the examples can depend on anything in the current session, but interactive code (like browser()) won't work.
document	if TRUE, document() will be run to ensure examples are updated before running them.
run, test	Deprecated, see run_dontrun and run_donttest above.

 save_all

Save all documents in an active IDE session.

Description

Helper function wrapping IDE-specific calls to save all documents in the active session. In this form, callers of `save_all()` don't need to execute any IDE-specific code. This function can be extended to include other IDE implementations of their equivalent `rstudioapi::documentSaveAll()` methods.

Usage

```
save_all()
```

show_news	<i>Show package news</i>
-----------	--------------------------

Description

Show package news

Usage

```
show_news(pkg = ".", latest = TRUE, ...)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
latest	if TRUE, only show the news for the most recent version.
...	other arguments passed on to news

source_gist	<i>Run a script on gist</i>
-------------	-----------------------------

Description

“Gist is a simple way to share snippets and pastes with others. All gists are git repositories, so they are automatically versioned, forkable and usable as a git repository.” <https://gist.github.com/>

Usage

```
source_gist(id, ..., filename = NULL, sha1 = NULL, quiet = FALSE)
```

Arguments

id	either full url (character), gist ID (numeric or character of numeric).
...	other options passed to source()
filename	if there is more than one R file in the gist, which one to source (filename ending in '.R')? Default NULL will source the first file.
sha1	The SHA-1 hash of the file at the remote URL. This is highly recommend as it prevents you from accidentally running code that's not what you expect. See source_url() for more information on using a SHA-1 hash.
quiet	if FALSE, the default, prints informative messages.

See Also

[source_url\(\)](#)

Examples

```
## Not run:
# You can run gists given their id
source_gist(6872663)
source_gist("6872663")

# Or their html url
source_gist("https://gist.github.com/hadley/6872663")
source_gist("gist.github.com/hadley/6872663")

# It's highly recommend that you run source_gist with the optional
# sha1 argument - this will throw an error if the file has changed since
# you first ran it
source_gist(6872663, sha1 = "54f1db27e60")
# Wrong hash will result in error
source_gist(6872663, sha1 = "54f1db27e61")

#' # You can specify a particular R file in the gist
source_gist(6872663, filename = "hi.r")
source_gist(6872663, filename = "hi.r", sha1 = "54f1db27e60")

## End(Not run)
```

source_url

Run a script through some protocols such as http, https, ftp, etc.

Description

If a SHA-1 hash is specified with the `sha1` argument, then this function will check the SHA-1 hash of the downloaded file to make sure it matches the expected value, and throw an error if it does not match. If the SHA-1 hash is not specified, it will print a message displaying the hash of the downloaded file. The purpose of this is to improve security when running remotely-hosted code; if you have a hash of the file, you can be sure that it has not changed. For convenience, it is possible to use a truncated SHA1 hash, down to 6 characters, but keep in mind that a truncated hash won't be as secure as the full hash.

Usage

```
source_url(url, ..., sha1 = NULL)
```

Arguments

url	url
...	other options passed to <code>source()</code>
sha1	The (prefix of the) SHA-1 hash of the file at the remote URL.

See Also

[source_gist\(\)](#)

Examples

```
## Not run:

source_url("https://gist.github.com/hadley/6872663/raw/hi.r")

# With a hash, to make sure the remote file hasn't changed
source_url("https://gist.github.com/hadley/6872663/raw/hi.r",
  sha1 = "54f1db27e60bb7e0486d785604909b49e8fef9f9")

# With a truncated hash
source_url("https://gist.github.com/hadley/6872663/raw/hi.r",
  sha1 = "54f1db27e60")

## End(Not run)
```

spell_check

Spell checking

Description

Runs a spell check on text fields in the package description file, manual pages, and optionally vignettes. Wraps the [spelling](#) package.

Usage

```
spell_check(pkg = ".", vignettes = TRUE, use_wordlist = TRUE)
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
vignettes	also check all rmd and rnw files in the pkg vignettes folder
use_wordlist	ignore words in the package WORDLIST file

test

Execute testthat tests in a package

Description

- `test()` runs all tests in a package. It's a shortcut for `testthat::test_dir()`
- `test_active_file()` runs `test()` on the active file.
- `test_coverage()` computes test coverage for your package. It's a shortcut for `covr::package_coverage()` plus `covr::report()`.
- `test_coverage_active_file()` computes test coverage for the active file. It's a shortcut for `covr::file_coverage()` plus `covr::report()`.

Usage

```

test(pkg = ".", filter = NULL, stop_on_failure = FALSE, export_all = TRUE, ...)

test_active_file(file = find_active_file(), ...)

test_coverage(pkg = ".", show_report = interactive(), ...)

test_coverage_active_file(
  file = find_active_file(),
  filter = TRUE,
  show_report = interactive(),
  export_all = TRUE,
  ...
)

```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
filter	If not NULL, only tests with file names matching this regular expression will be executed. Matching is performed on the file name after it's stripped of "test-" and ".R".
stop_on_failure	If TRUE, throw an error if any tests fail.
export_all	If TRUE (the default), export all objects. If FALSE, export only the objects that are listed as exports in the NAMESPACE file.
...	additional arguments passed to wrapped functions.
file	One or more source or test files. If a source file the corresponding test file will be run. The default is to use the active file in RStudio (if available).
show_report	Show the test coverage report.

uninstall

Uninstall a local development package

Description

Uses `remove.packages()` to uninstall the package. To uninstall a package from a non-default library, use in combination with `withr::with_libpaths()`.

Usage

```
uninstall(pkg = ".", unload = TRUE, quiet = FALSE, lib = .libPaths()[[1]])
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
unload	if TRUE (the default), ensures the package is unloaded, prior to uninstalling.
quiet	If TRUE, suppress output.
lib	a character vector giving the library directories to remove the packages from. If missing, defaults to the first element in .libPaths() .

See Also

[with_debug\(\)](#) to install packages with debugging flags set.

Other package installation: [install\(\)](#)

wd	<i>Set working directory.</i>
----	-------------------------------

Description

Set working directory.

Usage

```
wd(pkg = ".", path = "")
```

Arguments

pkg	The package to use, can be a file path to the package or a package object. See as.package() for more information.
path	path within package. Leave empty to change working directory to package directory.

Index

- * **build functions**
 - check_mac_release, 11
 - check_rhub, 12
 - check_win, 13
- * **example functions**
 - run_examples, 25
- * **package installation**
 - install, 17
 - uninstall, 30
- * **programming**
 - build_vignettes, 7
 - run_examples, 25
- .libPaths, 31
- activates, 15
- as.package(), 3–5, 7, 9, 11–18, 20, 21, 23–27, 29–31
- bash, 3
- browser(), 26
- build, 3
- build(), 12
- build_manual, 5
- build_readme (build_rmd), 6
- build_rmd, 6
- build_site, 6
- build_vignettes, 7
- check, 8
- check_built (check), 8
- check_mac_release, 11, 13, 15
- check_man, 12
- check_rhub, 11, 12, 15
- check_win, 11, 13, 13
- check_win_devel (check_win), 13
- check_win_oldrelease (check_win), 13
- check_win_release (check_win), 13
- clean_vignettes, 15
- clean_vignettes(), 8
- compiler_flags(FALSE), 10
- covr::file_coverage(), 29
- covr::package_coverage(), 29
- covr::report(), 29
- create, 15
- dev_sitrep, 16
- document, 17
- document(), 26
- fs::path_package(), 22
- install, 17, 31
- install_deps, 19
- install_dev_deps (install_deps), 19
- library(), 21–23, 25
- lint, 21
- lintr::lint(), 21
- lintr::lint_package(), 21
- load_all, 21
- load_all(), 25
- load_code(), 21
- load_data(), 21
- loadNamespace(), 22
- missing_s3, 23
- pkgbuild::build, 4
- pkgbuild::build(), 8, 9, 11, 14, 18, 20
- pkgbuild::clean_dll(), 22
- pkgbuild::compile_dll(), 21
- pkgdown::build_site(), 6
- pkgload::load_all(), 22
- r_env_vars(), 10
- rcmdcheck::rcmdcheck(), 8, 10
- Rd2pdf(), 5
- release, 24
- release(), 5, 10
- reload, 25
- reload(), 19

remotes::install_deps(), 19, 20
rhub::check_for_cran(), 13
rhub::platforms(), 13
rhub::validate_email(), 13
rmarkdown::render(), 6
roxygen2::roxygenize(), 17
run_examples, 25

save_all, 26
shim_help(), 21
shim_question(), 21
shim_system.file(), 21, 22
show_news, 27
source(), 27, 28
source_gist, 27
source_gist(), 28
source_url, 28
source_url(), 27
spell_check, 29
spelling, 29
submit_cran(), 5
system.file(), 21, 22

test, 29
test_active_file(test), 29
test_coverage(test), 29
test_coverage_active_file(test), 29
testthat::test_dir(), 29

uninstall, 19, 30
unload(), 22, 25
update_packages(), 19
usethis::create_package(), 15
usethis::use_release_issue(), 24
utils::glob2rx(), 4

wd, 31
with_debug(), 19, 31
withr::with_libpaths(), 19, 30
WORDLIST, 29