

Package: gtfstools (via r-universe)

October 19, 2026

Type Package

Title General Transit Feed Specification (GTFS) Editing and Analysing Tools

Version 1.4.0.9000

Description Utility functions to read, manipulate, analyse and write transit feeds in the General Transit Feed Specification (GTFS) data format.

License MIT + file LICENSE

URL <https://ipea.github.io/gtfstools/>,
<https://github.com/ipea/gtfstools>

BugReports <https://github.com/ipea/gtfstools/issues>

Depends R (>= 4.1.0)

Imports checkmate, cli, curl, data.table, gtfsio (>= 1.2.2), httr2, parallelly, processx, sf, sfheaders, stats, units (>= 1.0-1), utils, zip

Suggests covr, dplyr, ggplot2, jsonlite, knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

NeedsCompilation yes

Roxygen list(markdown = TRUE)

LinkingTo cpp11

Config/roxygen2/version 8.1.0

Config/pak/sysreqs libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev make libuv1-dev libssl-dev libproj-dev libudunits2-dev zlib1g-dev

Repository <https://ar-puuk.r-universe.dev>

Date/Publication 2026-10-19 02:57:40 UTC

RemoteUrl <https://github.com/ipeaGIT/gtfstools>

RemoteRef HEAD

RemoteSha fc02063e5e88248add628cf46a8d2964fae454c6

Contents

as_dt_gtfs	3
convert_sf_to_shapes	5
convert_shapes_to_sf	6
convert_stops_to_sf	6
convert_stops_to_shapes	7
convert_time_to_seconds	8
download_validator	10
filter_by_agency_id	11
filter_by_date	12
filter_by_period	13
filter_by_route_id	15
filter_by_route_type	16
filter_by_service_id	19
filter_by_sf	20
filter_by_shape_id	21
filter_by_spatial_extent	22
filter_by_stop_id	23
filter_by_time_of_day	25
filter_by_trip_id	28
filter_by_weekday	29
fix_gtfs	31
frequencies_to_stop_times	32
get_active_services	34
get_calendar_overlap	35
get_children_stops	37
get_dates	38
get_dwell_time	39
get_parent_station	41
get_route_frequency	42
get_route_geometry	43
get_route_speed	45
get_route_timetable	46
get_shape_length	47
get_shapes_geometry	48
get_start_and_end_times	49
get_stop_distances	50
get_stop_frequency	52
get_stop_times_patterns	53
get_stop_timetable	55
get_stops	56
get_stops_geometry	57
get_summary	58

get_trip_duration	61
get_trip_geometry	62
get_trip_length	63
get_trip_segment_duration	65
get_trip_speed	67
interpolate_stop_times	68
list_validator_versions	70
merge_gtfs	71
read_gtfs	72
remove_duplicates	74
remove_unused_ids	74
set_dwell_time	75
set_max_speed	78
set_route_frequency	80
set_route_speed	82
set_trip_speed	84
stop_times_to_frequencies	86
validate_gtfs	88
write_gtfs	90
Index	92

as_dt_gtfs	<i>Coerce lists and GTFS objects from other packages into gtfstools-compatible GTFS objects</i>
------------	---

Description

Coerces an existing object, such as a list or a GTFS object created from other packages (`{tidytransit}` and `{gtfsio}`, for example) into a gtfstools-compatible GTFS object - i.e. one whose internal tables are represented with `data.tables` and whose fields are formatted like the fields of a feed read with `read_gtfs()`.

`as_dt_gtfs()` is an S3 generic, with methods for:

- `tidygtfs`: the class of GTFS objects read with `tidytransit::read_gtfs()`. This method converts all tibbles to `data.tables` and convert time columns, represented as `hms` objects in a `tidygtfs`, to strings in the "HH:MM:SS" format.
- `gtfs`: the class of GTFS objects read with `gtfsio::import_gtfs()`. This method convert all date fields, represented as integers in `{gtfsio}`'s representation, to Date objects.
- `list`: this method tries to convert the elements of a list into `data.tables`. Please note that all list elements must inherit from `data.frame` and must be named. Like the `gtfs` method, it converts date fields represented as integers (YYYYMMDD) to Date objects; other fields are kept as they are.

Usage

```
as_dt_gtfs(gtfs, ...)  
  
## S3 method for class 'tidygtfs'  
as_dt_gtfs(gtfs, calculate_distance = TRUE, ...)  
  
## S3 method for class 'gtfs'  
as_dt_gtfs(gtfs, ...)  
  
## S3 method for class 'list'  
as_dt_gtfs(gtfs, ...)
```

Arguments

gtfs	The object that should be coerced to a dt_gtfs.
...	Ignored.
calculate_distance	A logical. Passed to convert_sf_to_shapes() , which only affects the output when the object to be converted includes a shapes element. Controls whether this function, used to convert a LINESTRING sf into a GTFS shapes table, should calculate and populate the shape_dist_traveled column. This column is used to describe the distance along the shape from each one of its points to its first point. Defaults to TRUE.

Value

A dt_gtfs GTFS object.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")  
  
gtfsio_gtfs <- gtfsio::import_gtfs(data_path)  
class(gtfsio_gtfs)  
  
gtfstools_gtfs <- as_dt_gtfs(gtfsio_gtfs)  
class(gtfstools_gtfs)  
  
gtfs_like_list <- unclass(gtfsio_gtfs)  
class(gtfs_like_list)  
  
gtfstools_gtfs <- as_dt_gtfs(gtfs_like_list)  
class(gtfstools_gtfs)
```

convert_sf_to_shapes *Convert a simple feature object into a shapes table*

Description

Converts a LINESTRING sf object into a GTFS shapes table.

Usage

```
convert_sf_to_shapes(sf_shapes, shape_id = NULL, calculate_distance = TRUE)
```

Arguments

sf_shapes	A LINESTRING sf associating each shape_ids to a geometry. This object must use CRS WGS 84 (EPSG code 4326).
shape_id	A character vector specifying the shape_ids to be converted. If NULL (the default), all shapes are converted.
calculate_distance	A logical. Whether to calculate and populate the shape_dist_traveled column. This column is used to describe the distance along the shape from each one of its points to its first point, in meters. Distances are great-circle distances on a sphere with the same radius used by {s2} (6,371,010 meters), regardless of whether sf::sf_use_s2() is enabled. Defaults to TRUE.

Value

A data.table representing a GTFS shapes table.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# first converting existing shapes table into a sf object
shapes_sf <- get_shapes_geometry(gtfs)
head(shapes_sf)

# by default converts all shapes
result <- convert_sf_to_shapes(shapes_sf)
result

# shape_id argument controls which shapes are converted
result <- convert_sf_to_shapes(shapes_sf, shape_id = c("17846", "17847"))
result

# calculate_distance argument controls whether to calculate
# shape_dist_traveled or not
result <- convert_sf_to_shapes(shapes_sf, calculate_distance = TRUE)
```

result

convert_shapes_to_sf	<i>Convert shapes table to simple feature object (deprecated)</i>
----------------------	---

Description

This function is deprecated: calling it raises a warning. Please use [get_shapes_geometry\(\)](#) instead, which takes the same arguments (except sort_sequence) and returns the same result.

Usage

```
convert_shapes_to_sf(gtfs, shape_id = NULL, crs = 4326, sort_sequence)
```

Arguments

- gtfs A GTFS object, as created by [read_gtfs\(\)](#).
- shape_id A character vector including the shape_ids to be converted. If NULL (the default), all shapes are converted.
- crs The CRS of the resulting object, either as an EPSG code or as an crs object. Defaults to 4326 (WGS 84).
- sort_sequence Deprecated; do not supply. Shapes are now always sorted by shape_pt_sequence. Passing TRUE raises a warning, and passing FALSE raises an error.

Value

A LINESTRING sf object.

See Also

[get_shapes_geometry\(\)](#), which replaces this function.

convert_stops_to_sf	<i>Convert stops table to simple feature object (deprecated)</i>
---------------------	--

Description

This function is deprecated: calling it raises a warning. Please use [get_stops_geometry\(\)](#) instead, which takes the same arguments and returns the same result.

Usage

```
convert_stops_to_sf(gtfs, stop_id = NULL, crs = 4326)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
stop_id	A character vector including the stop_ids to be converted. If NULL (the default), all stops are converted.
crs	The CRS of the resulting object, either as an EPSG code or as an crs object. Defaults to 4326 (WGS 84).

Value

A POINT sf object.

See Also

[get_stops_geometry\(\)](#), which replaces this function.

convert_stops_to_shapes

Convert stops into shapes

Description

Creates shapes for the given trips, linking their consecutive stops along straight lines, and assigns them to the trips. Useful for feeds without shapes, or in which some trips are not linked to a shape.

Usage

```
convert_stops_to_shapes(gtfs, trip_id = NULL)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A character vector including the trip_ids to get new shapes, which replace the shapes they are currently linked to. If NULL (the default), only the trips that are not linked to a usable shape get new shapes (see details).

Value

The GTFS object passed to the gtfs parameter, with the new shapes added to the shapes table (created if needed) and assigned to the trips in the trips table.

Details

The shape of a trip links its stops, in `stop_sequence` order, along straight lines. Stops without coordinates, or not listed in `stops`, are skipped. Trips that visit the same sequence of stops share the same shape. The new shapes get new `shape_ids` ("stops_shape_1", "stops_shape_2", etc.), different from any `shape_id` already listed in `shapes` or `trips`. Their `shape_dist_traveled` is not calculated, because the distance unit used by the feed is unknown, and the `shape_dist_traveled` of the `stop_times` entries of the trips that get new shapes, if present, is set to NA. Shapes no longer used by any trip are kept (please use `remove_unused_ids()` to remove them).

A shape is usable if it has at least two distinct points with coordinates. With `trip_id = NULL`, the trips that get new shapes are those not linked to a `shape_id`, or linked to a `shape_id` that is not listed in `shapes` or whose shape is not usable (all trips, if the feed doesn't have a `shapes` table). These are the trips that `get_trip_length()` and `get_trip_geometry()` can't measure along a shape.

Trips with fewer than two distinct stops with coordinates, or without `stop_times` entries, can't get a usable shape, so they keep their current `shape_id`, with a warning.

See Also

`get_trip_geometry()`, `convert_sf_to_shapes()`, `remove_unused_ids()`

Examples

```
library(dplyr)

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# a feed without shapes gets one shape for each sequence of stops
gtfs$shapes <- NULL
new_gtfs <- convert_stops_to_shapes(gtfs)
head(new_gtfs$shapes)
new_gtfs$trips |>
  select(trip_id, shape_id) |>
  head()
```

convert_time_to_seconds

Convert time fields to seconds after midnight

Description

Converts `stop_times`' and `frequencies`' fields in the "HH:MM:SS" format to seconds after midnight. Instead of overwriting the existing fields, creates new fields with the `_secs` suffix.

Usage

```
convert_time_to_seconds(gtfs, file = NULL, by_reference = FALSE)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>file</code>	A character vector, specifying the file whose fields should be converted. If <code>NULL</code> (the default), the function attempts to convert the times from both files, but only raises an error if none of them exist.
<code>by_reference</code>	Whether to update the tables by reference. Defaults to <code>FALSE</code> .

Details

Other `gtfstools` functions use existing `_secs` columns as-is. The functions that edit times keep them in sync, but other edits (e.g. made directly to the tables) don't, so re-run `convert_time_to_seconds()` after them.

Value

If `by_reference` is `FALSE`, returns a GTFS object with additional time in seconds columns (identified by a `_secs` suffix). Else, returns a GTFS object invisibly (please note that in such case the original GTFS object is altered).

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

# by default converts both 'stop_times' and 'frequencies' times
converted_gtfs <- convert_time_to_seconds(gtfs)
head(converted_gtfs$stop_times)
head(converted_gtfs$frequencies)

# choose which table to convert with 'file'
converted_gtfs <- convert_time_to_seconds(gtfs, file = "frequencies")
head(converted_gtfs$stop_times)
head(converted_gtfs$frequencies)

# original gtfs remained unchanged, as seen with the frequencies table above
# change original object without creating a copy with 'by_reference = TRUE'
convert_time_to_seconds(gtfs, by_reference = TRUE)
head(gtfs$stop_times)
head(gtfs$frequencies)
```

download_validator	<i>Download MobilityData's GTFS validator</i>
--------------------	---

Description

Downloads MobilityData's command line tool to validate GTFS feeds.

Usage

```
download_validator(path, version = "latest", force = FALSE, quiet = TRUE)
```

Arguments

path	A string. The directory where the validator should be saved to.
version	A string. The version of the validator that should be downloaded. Defaults to "latest", but accepts version numbers as strings (i.e. to download version v6.0.0 please enter "6.0.0"). Please check MobilityData/gtfs-validator releases for the full set of available versions.
force	A logical. Whether to overwrite a previously downloaded validator in path. Defaults to FALSE.
quiet	A logical. Whether to hide log messages and progress bars. Defaults to TRUE.

Value

Invisibly returns the normalized path to the downloaded validator.

See Also

Other validation: [list_validator_versions\(\)](#), [validate_gtfs\(\)](#)

Examples

```
path <- tempdir()

download_validator(path)

# specifying a specific version
download_validator(path, version = "6.0.0")
```

filter_by_agency_id	<i>Filter GTFS object by agency_id</i>
---------------------	--

Description

Filters a GTFS object by agency_ids, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_agency_id(gtfs, agency_id, keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
agency_id	A character vector. The agency_ids used to filter the data.
keep	A logical. Whether the entries related to the specified agency_ids should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

See Also

Other filtering functions: [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```
data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
agency_id <- "92"

object.size(gtfs)

# keeps entries related to passed agency_id
smaller_gtfs <- filter_by_agency_id(gtfs, agency_id)
object.size(smaller_gtfs)

# drops entries related to passed agency_id
smaller_gtfs <- filter_by_agency_id(gtfs, agency_id, keep = FALSE)
object.size(smaller_gtfs)
```

filter_by_date	<i>Filter GTFS object by date</i>
----------------	-----------------------------------

Description

Filters a GTFS object by the services that run on the given dates, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_date(gtfs, date, keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
date	A Date vector (including IDate) or a character vector of dates in the "YYYYMMDD" or "YYYY-MM-DD" formats. The dates used to filter the data.
keep	A logical. Whether the entries related to the services that run on the specified dates should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the `gtfs` parameter, after the filtering process.

Details

The services that run on at least one of the given dates are kept (or dropped) as a whole: their `calendar` and `calendar_dates` entries are not trimmed to the given dates, so they may still run on other dates.

A service runs on a date if its `calendar` entry spans the date and flags its weekday, unless the date is removed from it in `calendar_dates` (exception_type 2), or if the date is added to it in `calendar_dates` (exception_type 1). An addition wins over a removal on the same date. Either table may be missing. If both are missing, the GTFS object is returned unchanged, with a warning.

See Also

[filter_by_weekday\(\)](#), [get_calendar_overlap\(\)](#)

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```

data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# on 2006-07-03 (a monday) the weekday service "WD" is replaced by the
# weekend service "WE", according to the calendar_dates table
gtfs$calendar_dates

smaller_gtfs <- filter_by_date(gtfs, "2006-07-03")
smaller_gtfs$calendar

# dates may also be given as Date objects. drops the services that run on
# 2006-07-05 (a wednesday)
smaller_gtfs <- filter_by_date(gtfs, as.Date("2006-07-05"), keep = FALSE)
smaller_gtfs$calendar

```

filter_by_period	<i>Filter GTFS object by period</i>
------------------	-------------------------------------

Description

Filters a GTFS object by the services that run on at least one day of a period, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_period(gtfs, start_date, end_date, keep = TRUE, trim = TRUE)
```

Arguments

gtfs	A GTFS object, as created by <code>read_gtfs()</code> .
start_date, end_date	A Date (including IDate) or a string in the "YYYYMMDD" or "YYYY-MM-DD" formats. The first and last days of the period, both included. end_date must not be earlier than start_date.
keep	A logical. Whether the entries related to the services that run in the specified period should be kept or dropped (defaults to TRUE, which keeps the entries).
trim	A logical. Whether the calendars of the kept services should be cut to the period (defaults to TRUE), so that the GTFS object has no service outside it. Ignored when keep is FALSE.

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

Details

The services are selected as when filtering by each day of the period with `filter_by_date()`, whose details also apply here: the services that run on at least one day of the period are kept (or dropped).

With `trim = TRUE`, the kept services are then cut to the period: the `start_date` and `end_date` of their calendar entries are clipped to it (entries left without any day are removed), and the `calendar_dates` entries outside it are removed. Each service then runs on exactly the same days within the period as before, and on no day outside it. The `feed_info` table is not changed. With `trim = FALSE`, the services are kept as a whole, so they may still run on days outside the period.

The period is first clipped to the dates covered by the `calendar` and `calendar_dates` tables, on which the services can run, so the days of the period outside them add no work. The memory used still grows with the number of days the period shares with each service's calendar.

See Also

`filter_by_date()`, `get_active_services()`, `get_dates()`

Other filtering functions: `filter_by_agency_id()`, `filter_by_date()`, `filter_by_route_id()`, `filter_by_route_type()`, `filter_by_service_id()`, `filter_by_shape_id()`, `filter_by_spatial_extent()`, `filter_by_stop_id()`, `filter_by_time_of_day()`, `filter_by_trip_id()`, `filter_by_weekday()`

Examples

```
data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

gtfs$calendar
gtfs$calendar_dates

# keeps the services that run in the first week of july 2006, with their
# calendars cut to that week
smaller_gtfs <- filter_by_period(gtfs, "2006-07-01", "2006-07-07")
smaller_gtfs$calendar

# keeps the same services, with their whole calendars
smaller_gtfs <- filter_by_period(
  gtfs,
  "2006-07-01",
  "2006-07-07",
  trim = FALSE
)
smaller_gtfs$calendar

# dates may also be given as Date objects. drops the services that run in
# the period
smaller_gtfs <- filter_by_period(
  gtfs,
  as.Date("2006-07-03"),
  as.Date("2006-07-04"),
  keep = FALSE
)
```

```
smaller_gtfs$calendar
```

filter_by_route_id	<i>Filter GTFS object by route_id</i>
--------------------	---------------------------------------

Description

Filters a GTFS object by route_ids, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_route_id(gtfs, route_id, keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
route_id	A character vector. The route_ids used to filter the data.
keep	A logical. Whether the entries related to the specified route_ids should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
route_ids <- c("6450-51", "CPTM L11")

object.size(gtfs)

# keeps entries related to passed route_ids
smaller_gtfs <- filter_by_route_id(gtfs, route_ids)
object.size(smaller_gtfs)

# drops entries related to passed route_ids
smaller_gtfs <- filter_by_route_id(gtfs, route_ids, keep = FALSE)
object.size(smaller_gtfs)
```

filter_by_route_type *Filter GTFS object by route_type (transport mode)*

Description

Filters a GTFS object by route_types, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_route_type(gtfs, route_type, keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
route_type	An integer vector. The route_types used to filter the data.
keep	A logical. Whether the entries related to the specified route_types should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

Route types

Valid options include the route types listed in the GTFS Schedule specification and in the Google Transit implementation. The types specified in the GTFS Schedule specification are:

- 0 - Tram, Streetcar, Light rail. Any light rail or street level system within a metropolitan area.
- 1 - Subway, Metro. Any underground rail system within a metropolitan area.
- 2 - Rail. Used for intercity or long-distance travel.
- 3 - Bus. Used for short- and long-distance bus routes.
- 4 - Ferry. Used for short- and long-distance boat service.
- 5 - Cable tram. Used for street-level rail cars where the cable runs beneath the vehicle, e.g., cable car in San Francisco.
- 6 - Aerial lift, suspended cable car (e.g., gondola lift, aerial tramway). Cable transport where cabins, cars, gondolas or open chairs are suspended by means of one or more cables.
- 7 - Funicular. Any rail system designed for steep inclines.
- 11 - Trolleybus. Electric buses that draw power from overhead wires using poles.
- 12 - Monorail. Railway in which the track consists of a single rail or a beam.

The types defined in Google Transit's extension are listed below, including some examples (not available for all types):

- 100 - Railway Service - Not applicable (N/A)
- 101 - High Speed Rail Service - TGV (FR), ICE (DE), Eurostar (GB)

- 102 - Long Distance Trains - InterCity/EuroCity
- 103 - Inter Regional Rail Service - InterRegio (DE), Cross County Rail (GB)
- 104 - Car Transport Rail Service
- 105 - Sleeper Rail Service - GNER Sleeper (GB)
- 106 - Regional Rail Service - TER (FR), Regionalzug (DE)
- 107 - Tourist Railway Service - Romney, Hythe & Dymchurch (GB)
- 108 - Rail Shuttle (Within Complex) - Gatwick Shuttle (GB), Sky Line (DE)
- 109 - Suburban Railway - S-Bahn (DE), RER (FR), S-tog (Kopenhagen)
- 110 - Replacement Rail Service
- 111 - Special Rail Service
- 112 - Lorry Transport Rail Service
- 113 - All Rail Services
- 114 - Cross-Country Rail Service
- 115 - Vehicle Transport Rail Service
- 116 - Rack and Pinion Railway - Rochers de Naye (CH), Dolderbahn (CH)
- 117 - Additional Rail Service
- 200 - Coach Service
- 201 - International Coach Service - EuroLine, Touring
- 202 - National Coach Service - National Express (GB)
- 203 - Shuttle Coach Service - Roissy Bus (FR), Reading-Heathrow (GB)
- 204 - Regional Coach Service
- 205 - Special Coach Service
- 206 - Sightseeing Coach Service
- 207 - Tourist Coach Service
- 208 - Commuter Coach Service
- 209 - All Coach Services
- 400 - Urban Railway Service
- 401 - Metro Service - Métro de Paris
- 402 - Underground Service - London Underground, U-Bahn
- 403 - Urban Railway Service
- 404 - All Urban Railway Services
- 405 - Monorail
- 700 - Bus Service
- 701 - Regional Bus Service - Eastbourne-Maidstone (GB)
- 702 - Express Bus Service - X19 Wokingham-Heathrow (GB)
- 703 - Stopping Bus Service - 38 London: Clapton Pond-Victoria (GB)
- 704 - Local Bus Service

- 705 - Night Bus Service - N prefixed buses in London (GB)
- 706 - Post Bus Service - Maidstone P4 (GB)
- 707 - Special Needs Bus
- 708 - Mobility Bus Service
- 709 - Mobility Bus for Registered Disabled
- 710 - Sightseeing Bus
- 711 - Shuttle Bus - 747 Heathrow-Gatwick Airport Service (GB)
- 712 - School Bus
- 713 - School and Public Service Bus
- 714 - Rail Replacement Bus Service
- 715 - Demand and Response Bus Service
- 716 - All Bus Services
- 800 - Trolleybus Service
- 900 - Tram Service
- 901 - City Tram Service
- 902 - Local Tram Service - Munich (DE), Brussels (BE), Croydon (GB)
- 903 - Regional Tram Service
- 904 - Sightseeing Tram Service - Blackpool Seafront (GB)
- 905 - Shuttle Tram Service
- 906 - All Tram Services
- 1000 - Water Transport Service
- 1100 - Air Service
- 1200 - Ferry Service
- 1300 - Aerial Lift Service - Telefèric de Montjuïc (ES), Saleve (CH), Roosevelt Island Tramway (US)
- 1301 - Telecabin Service
- 1302 - Cable Car Service
- 1303 - Elevator Service
- 1304 - Chair Lift Service
- 1305 - Drag Lift Service
- 1306 - Small Telecabin Service
- 1307 - All Telecabin Services
- 1400 - Funicular Service - Rigiblick (Zürich, CH)
- 1500 - Taxi Service
- 1501 - Communal Taxi Service - Marshrutka (RU), dolmuş (TR)
- 1502 - Water Taxi Service
- 1503 - Rail Taxi Service

- 1504 - Bike Taxi Service
- 1505 - Licensed Taxi Service
- 1506 - Private Hire Service Vehicle
- 1507 - All Taxi Services
- 1700 - Miscellaneous Service
- 1702 - Horse-drawn Carriage

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```
# read gtfs
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

object.size(gtfs)

# keeps entries related to passed route_types
smaller_gtfs <- filter_by_route_type(gtfs, route_type = 1)
object.size(smaller_gtfs)

# drops entries related to passed route_types
smaller_gtfs <- filter_by_route_type(gtfs, route_type = 1, keep = FALSE)
object.size(smaller_gtfs)
```

`filter_by_service_id` *Filter GTFS object by service_id*

Description

Filters a GTFS object by service_ids, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_service_id(gtfs, service_id, keep = TRUE)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>service_id</code>	A character vector. The service_ids used to filter the data.
<code>keep</code>	A logical. Whether the entries related to the specified service_ids should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the `gtfs` parameter, after the filtering process.

See Also

Other filtering functions: `filter_by_agency_id()`, `filter_by_date()`, `filter_by_period()`, `filter_by_route_id()`, `filter_by_route_type()`, `filter_by_shape_id()`, `filter_by_spatial_extent()`, `filter_by_stop_id()`, `filter_by_time_of_day()`, `filter_by_trip_id()`, `filter_by_weekday()`

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
service_ids <- c("USD", "U__")

object.size(gtfs)

# keeps entries related to the specified service_ids
smaller_gtfs <- filter_by_service_id(gtfs, service_ids)
object.size(smaller_gtfs)

# drops entries related to the specified service_ids
smaller_gtfs <- filter_by_service_id(gtfs, service_ids, keep = FALSE)
object.size(smaller_gtfs)
```

filter_by_sf

Filter a GTFS object using a simple features object (defunct)

Description

This function was deprecated in `gtfstools` 1.3.0 and is now defunct: calling it raises an error. Please use `filter_by_spatial_extent()` instead, which takes the same arguments.

Usage

```
filter_by_sf(...)
```

Arguments

```
...           Ignored.
```

Value

Doesn't return: always raises an error.

See Also

`filter_by_spatial_extent()`, which replaces this function.

filter_by_shape_id	<i>Filter GTFS object by shape_id</i>
--------------------	---------------------------------------

Description

Filters a GTFS object by shape_ids, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_shape_id(gtfs, shape_id, keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
shape_id	A character vector. The shape_ids used to filter the data.
keep	A logical. Whether the entries related to the specified shape_ids should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
shape_ids <- c("17846", "68962")

object.size(gtfs)

# keeps entries related to passed shape_ids
smaller_gtfs <- filter_by_shape_id(gtfs, shape_ids)
object.size(smaller_gtfs)

# drops entries related to passed shape_ids
smaller_gtfs <- filter_by_shape_id(gtfs, shape_ids, keep = FALSE)
object.size(smaller_gtfs)
```

filter_by_spatial_extent

Filter a GTFS object using a spatial extent

Description

Filters a GTFS object using a spatial extent (passed as an `sf` object), keeping (or dropping) entries related to shapes and trips whose geometries are selected through a specified spatial operation.

Usage

```
filter_by_spatial_extent(
  gtfs,
  geom,
  spatial_operation = sf::st_intersects,
  keep = TRUE
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>geom</code>	An <code>sf</code> , <code>sfc</code> or <code>bbox</code> object, in WGS 84 (EPSG 4326). Describes the spatial extent used to filter the data.
<code>spatial_operation</code>	A spatial operation function from the set of options listed in geos_binary_pred . Defaults to sf::st_intersects , which tests if the shapes and trips have ANY intersection with the object specified in <code>geom</code> . Please note that <code>geom</code> is passed as the <code>x</code> argument of these functions. sf::st_equals_exact() and sf::st_is_within_distance() are not supported, since they require additional arguments.
<code>keep</code>	A logical. Whether the entries related to the shapes and trips selected by the given spatial operation should be kept or dropped (defaults to <code>TRUE</code> , which keeps the entries).

Value

The GTFS object passed to the `gtfs` parameter, after the filtering process.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

shape_id <- "68962"
shape_sf <- get_shapes_geometry(gtfs, shape_id)
bbox <- sf::st_bbox(shape_sf)
object.size(gtfs)

# keeps entries that intersect with the specified polygon
smaller_gtfs <- filter_by_spatial_extent(gtfs, bbox)
object.size(smaller_gtfs)

# drops entries that intersect with the specified polygon
smaller_gtfs <- filter_by_spatial_extent(gtfs, bbox, keep = FALSE)
object.size(smaller_gtfs)

# uses a different function to filter the gtfs
smaller_gtfs <- filter_by_spatial_extent(
  gtfs,
  bbox,
  spatial_operation = sf::st_contains
)
object.size(smaller_gtfs)

```

filter_by_stop_id	<i>Filter GTFS object by stop_id</i>
-------------------	--------------------------------------

Description

Filters a GTFS object by stop_ids, keeping (or dropping) relevant entries in each file.

Usage

```

filter_by_stop_id(
  gtfs,
  stop_id,
  keep = TRUE,
  include_children = TRUE,
  include_parents = keep,
  full_trips
)

```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
stop_id	A character vector. The stop_ids used to filter the data.

<code>keep</code>	A logical. Whether the <code>stop_times</code> entries at the specified <code>stop_ids</code> (and the entries related to them in other tables) should be kept or dropped (defaults to <code>TRUE</code> , which keeps the entries). Trips that still have entries in <code>stop_times</code> are kept. To keep or drop entire trips, pass the <code>trip_ids</code> that serve these stops to filter_by_trip_id() .
<code>include_children</code>	A logical. Whether the filtered output should keep/drop children stops of those specified in <code>stop_id</code> . Defaults to <code>TRUE</code> - i.e. by default children stops are kept if their parents are kept and dropped if their parents are dropped.
<code>include_parents</code>	A logical. Whether the filtered output should keep/drop parent stations of those specified in <code>stop_id</code> . Defaults to the same value of <code>keep</code> - i.e. by default parent stations are kept both when their children are kept and dropped, because they can be parents of multiple stops that are not necessarily dropped, even if their sibling are.
<code>full_trips</code>	Defunct. Deprecated in version 1.3.0 and removed in the following major version: using it, with any value, raises an error. The function now always filters by the specified stops. To keep all stops of the trips that pass through them, subset <code>stop_times</code> by <code>stop_id</code> and pass the resulting <code>trip_ids</code> to filter_by_trip_id() .

Value

The GTFS object passed to the `gtfs` parameter, after the filtering process.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
stop_ids <- c("18848", "940004157")

object.size(gtfs)

# keeps the stop_times entries at the specified stop_ids
smaller_gtfs <- filter_by_stop_id(gtfs, stop_ids)
object.size(smaller_gtfs)

# drops the stop_times entries at the specified stop_ids
smaller_gtfs <- filter_by_stop_id(gtfs, stop_ids, keep = FALSE)
object.size(smaller_gtfs)
```

filter_by_time_of_day *Filter GTFS object by time of day*

Description

Filters a GTFS object by time of day, keeping (or dropping) the relevant entries in each file. Please see the details section for more information on how this function filters the frequencies and stop_times tables, as well as how it handles stop_times tables that contain trips with some empty departure and arrival times.

Usage

```
filter_by_time_of_day(  
  gtfs,  
  from,  
  to,  
  keep = TRUE,  
  full_trips = FALSE,  
  update_frequencies = TRUE  
)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
from	A string. The starting point of the time of day, in the "HH:MM:SS" format.
to	A string. The ending point of the time of day, in the "HH:MM:SS" format.
keep	A logical. Whether the entries related to the specified time of day should be kept or dropped (defaults to TRUE, which keeps the entries).
full_trips	A logical. Whether trips should be treated as immutable blocks or each of its stops should be considered separately when filtering the stop_times table (defaults to FALSE, which considers each stop individually). Please check the details section for more information on how this parameter changes the function behaviour.
update_frequencies	A logical. Whether the frequencies table should have its start_time and end_time fields updated to fit inside/outside the specified time of day (defaults to TRUE, which updates the fields).

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

Details

When filtering the frequencies table, `filter_by_time_of_day()` respects the `exact_times` field. This field indicates whether the service follows a fixed schedule throughout the day or not. If it's 0 (or if it's not present), the service does not follow a fixed schedule. Instead, the operators try to maintain the listed headways. In such cases, if `update_frequencies` is `TRUE` we just update `start_time` and `end_time` to the appropriate value of `from` or `to` (which of this value is used depends on `keep`). The time of day includes both `from` and `to`. As required by the GTFS specification, no trip departs at the `end_time` of an entry, so when `keep` is `TRUE`, `end_time` is set to one second after `to`, which keeps a departure that happens exactly at `to` (e.g. when converting the filtered feed with `frequencies_to_stop_times()`). When `keep` is `FALSE`, the entries that cross to start one second after it. Entries left without any departure are removed.

If `exact_times` is 1, however, operators try to strictly adhere to the start times and headway. As a result, when updating the `start_time` field we need to follow the listed headway. For example, take a trip that has its start time listed as 06:00:00, its end time listed as 08:00:00 and its headway listed as 300 secs (5 minutes). If you decide to filter the feed to keep the time of day between 06:32:00 and 08:00:00 while updating frequencies, the `start_time` field must be updated to 06:35:00 in order to preserve the correct departure times of this trips, instead of simply updating it to 06:32:00.

Another things to keep an eye on when filtering the frequencies table is that the corresponding `stop_times` entries of trips listed in the frequencies table should not be filtered, even if their departure and arrival times fall outside the specified time of day. This is because the `stop_times` entries of frequencies' trips are just templates that describe how long a segment between two stops takes, so the departure and arrival times listed there do not actually represent the actual departure and arrival times seen in practice. Taking the same example listed above, the corresponding `stop_times` entries of that trip could describe a departure from the first stop at 12:00:00 and an arrival at the second stop at 12:03:00. That doesn't mean the trip will actually leave and arrive at the stops at these times, but rather that it takes 3 minutes to get from the first to the second stop. So when the trip departs from the first stop at 06:35:00, it will get to the second at 06:38:00.

When filtering the `stop_times` table, a few other details should be observed. First, one could wish to filter a GTFS object in order to keep all trips that cross a given time of day, whereas others may want to keep only the specific entries that fall inside the specified time of day. For example, take a trip that leaves the first stop at 06:30:00, gets to the second at 06:35:00 and then gets to the third at 06:45:00. When filtering to keep entire trips that cross the time of day between 06:30:00 and 06:40:00, all three stops will have to be kept. If, however, you want to keep only the entries that fall within the specified time of day, only the first two should be kept. To control such behaviour you need to set the `full_trips` parameter. When it's `TRUE`, the function behaves like the first case, and when it's `FALSE`, like the second.

When using `full_trips` in conjunction with `keep`, please note how their behaviour stack. When both are `TRUE`, trips are always fully kept. When `keep` is `FALSE`, however, trips are fully dropped, even if some of their stops are visited outside the specified time of day.

Finally, please note that many GTFS feeds may contain `stop_times` entries with empty departure and arrival times. In such cases, filtering by time of day with `full_trips` as `FALSE` will drop the entries with empty times. Please set `full_trips` to `TRUE` to preserve these entries.

Existing `_secs` columns in `stop_times` and `frequencies` (e.g. created with `convert_time_to_seconds()`) are used as-is, not recalculated from the time strings.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_weekday\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# taking a look at the original frequencies and stop_times
head(gtfs$frequencies)
head(gtfs$stop_times)

smaller_gtfs <- filter_by_time_of_day(gtfs, "05:00:00", "06:00:00")

# filter_by_time_of_day filters the frequencies table but doesn't filter the
# stop_times table because they're just templates
head(smaller_gtfs$frequencies)
head(smaller_gtfs$stop_times)

# frequencies entries are adjusted by default. use update_frequencies =
# FALSE to keep their original times
smaller_gtfs <- filter_by_time_of_day(
  gtfs,
  "05:30:00",
  "06:00:00",
  update_frequencies = FALSE
)
head(smaller_gtfs$frequencies)

# when keep = FALSE, the behaviour of the function in general, and of
# update_frequencies in particular, is a bit different
smaller_gtfs <- filter_by_time_of_day(
  gtfs,
  "05:30:00",
  "06:00:00",
  keep = FALSE,
  update_frequencies = TRUE
)
head(smaller_gtfs$frequencies)

# let's remove the frequencies table to check the behaviour of full_trips
gtfs$frequencies <- NULL
smaller_gtfs <- filter_by_time_of_day(
  gtfs,
  "05:30:00",
  "06:00:00"
)
head(smaller_gtfs$stop_times)

smaller_gtfs <- filter_by_time_of_day(
```

```

gtfs,
"05:30:00",
"06:00:00",
full_trips = TRUE
)
head(smaller_gtfs$stop_times)

```

filter_by_trip_id	<i>Filter GTFS object by trip_id</i>
-------------------	--------------------------------------

Description

Filters a GTFS object by trip_ids, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_trip_id(gtfs, trip_id, keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A character vector. The trip_ids used to filter the data.
keep	A logical. Whether the entries related to the specified trip_ids should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the gtfs parameter, after the filtering process.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_weekday\(\)](#)

Examples

```

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
trip_ids <- c("CPTM L07-0", "2002-10-0")

object.size(gtfs)

# keeps entries related to passed trip_ids
smaller_gtfs <- filter_by_trip_id(gtfs, trip_ids)
object.size(smaller_gtfs)

# drops entries related to passed trip_ids
smaller_gtfs <- filter_by_trip_id(gtfs, trip_ids, keep = FALSE)

```

```
object.size(smaller_gtfs)
```

filter_by_weekday	<i>Filter GTFS object by weekday</i>
-------------------	--------------------------------------

Description

Filters a GTFS object by weekday, keeping (or dropping) the relevant entries in each file.

Usage

```
filter_by_weekday(gtfs, weekday, combine = "or", keep = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
weekday	A character vector. The weekdays used to filter the data. Possible values are <code>c("monday", "tuesday", "wednesday", "thursday", "friday", "saturday", "sunday")</code> .
combine	A string. Specifies which logic operation (OR or AND) should be used to filter the calendar table when multiple weekdays are specified. Defaults to "or". Please check the details and examples sections for more information on this argument usage.
keep	A logical. Whether the entries related to the specified weekdays should be kept or dropped (defaults to TRUE, which keeps the entries).

Value

The GTFS object passed to the `gtfs` parameter, after the filtering process.

combine usage

When filtering the calendar table using weekdays, one could reason about the process in different ways. For example, you may want to keep only services who run on Mondays AND Tuesdays. Or you may want to keep services that run EITHER on Mondays OR on Tuesdays. The first case is the equivalent of filtering using the expression `monday == 1 & tuesday == 1`, while the second uses `monday == 1 | tuesday == 1`. You can use the `combine` argument to control this behaviour.

Please note that `combine` also works together with `keep`. Using the same examples listed above, you could either keep the entries related to services that run on Mondays and Tuesdays or drop them, depending on the value you pass to `keep`.

See Also

Other filtering functions: [filter_by_agency_id\(\)](#), [filter_by_date\(\)](#), [filter_by_period\(\)](#), [filter_by_route_id\(\)](#), [filter_by_route_type\(\)](#), [filter_by_service_id\(\)](#), [filter_by_shape_id\(\)](#), [filter_by_spatial_extent\(\)](#), [filter_by_stop_id\(\)](#), [filter_by_time_of_day\(\)](#), [filter_by_trip_id\(\)](#)

Examples

```
library(dplyr)

# read gtfs
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

object.size(gtfs)

# keeps entries related to services than run EITHER on monday OR on sunday
smaller_gtfs <- filter_by_weekday(gtfs, weekday = c("monday", "sunday"))
smaller_gtfs$calendar |>
  select(service_id, monday, sunday)
object.size(smaller_gtfs)

# keeps entries related to services than run on monday AND on sunday
smaller_gtfs <- filter_by_weekday(
  gtfs,
  weekday = c("monday", "sunday"),
  combine = "and"
)
smaller_gtfs$calendar |>
  select(service_id, monday, sunday)
object.size(smaller_gtfs)

# drops entries related to services than run EITHER on monday OR on sunday
# the resulting gtfs shouldn't include any trips running on these days
smaller_gtfs <- filter_by_weekday(
  gtfs,
  weekday = c("monday", "sunday"),
  keep = FALSE
)
smaller_gtfs$calendar |>
  select(service_id, monday, sunday)
object.size(smaller_gtfs)

# drops entries related to services than run on monday AND on sunday
# the resulting gtfs may include trips that run on these days, but no trips
# that run on both these days
smaller_gtfs <- filter_by_weekday(
  gtfs,
  weekday = c("monday", "sunday"),
  combine = "and",
  keep = FALSE
)
smaller_gtfs$calendar |>
  select(service_id, monday, sunday)
object.size(smaller_gtfs)
```

Description

Cleans a GTFS feed in one call, by removing duplicated entries and unused ids, optionally capping the speed of trips, and filling blank stop times.

Usage

```
fix_gtfs(gtfs, max_speed = NULL, unit = "km/h")
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
max_speed	A number. The maximum speed of trips, in the unit given by unit. If NULL (the default), speeds are not capped.
unit	A string representing the unit in which max_speed is given. One of "km/h" (the default), "m/s" or "mph" (miles per hour).

Value

The fixed GTFS object.

Details

The feed goes through the following steps, in this order:

1. [remove_duplicates\(\)](#) removes duplicated entries from every table;
2. [remove_unused_ids\(\)](#) removes the trips without stop_times, and the entries of every table that no remaining trip uses (see its documentation for the exceptions). Note that this removes data from the feed;
3. [set_max_speed\(\)](#), only if max_speed is given, slows down the parts of trips that are faster than max_speed. Only spans between stops with known times are capped, and spans that end before they start (e.g. times after midnight written as "00:30:00") are left unchanged, with a warning;
4. [interpolate_stop_times\(\)](#) fills blank stop times from the times of the stops around them. Speeds are capped before interpolating, so the filled times follow the capped times. Interpolated times are rounded to the second. Stops whose times can't be interpolated are left blank, with a warning.

The trips and stop_times tables are always required, and stops is required to cap speeds and to fill blank times. The warnings raised are those of the functions above, so some warnings (e.g. about a missing shapes table) may be raised twice.

See Also

[remove_duplicates\(\)](#), [remove_unused_ids\(\)](#), [set_max_speed\(\)](#), [interpolate_stop_times\(\)](#)

Examples

```
library(dplyr)

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

fixed_gtfs <- fix_gtfs(gtfs, max_speed = 40)

# duplicated agencies were removed, and the trip is now slower
gtfs$agency
fixed_gtfs$agency

gtfs$stop_times |>
  filter(trip_id == "CPTM L07-0") |>
  slice_tail(n = 1)

fixed_gtfs$stop_times |>
  filter(trip_id == "CPTM L07-0") |>
  slice_tail(n = 1)
```

frequencies_to_stop_times

Convert frequencies to stop times

Description

Creates stop_times entries based on the frequencies specified in the frequencies table.

Usage

```
frequencies_to_stop_times(
  gtfs,
  trip_id = NULL,
  force = FALSE,
  strategy = "exact"
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>trip_id</code>	A character vector including the <code>trip_ids</code> to have their frequencies converted to <code>stop_times</code> entries. If <code>NULL</code> (the default), the function converts all trips listed in the frequencies table.
<code>force</code>	Whether to convert trips specified in the frequencies table even if they are not described in <code>stop_times</code> (defaults to <code>FALSE</code>). When set to <code>TRUE</code> , these mismatched trip are removed from the frequencies table and their correspondent entries in trips are substituted by what would be their converted counterpart.
<code>strategy</code>	A string. The strategy used to set the departure times of the trips created from frequency-based entries of the frequencies table (i.e. those whose <code>exact_times</code> is not 1). One of: • "exact" (the default): trips depart every <code>headway_secs</code> from <code>start_time</code>; • "half_headway": departures are shifted by half the headway, rounded down to whole seconds; • "random": departures are shifted by a random whole number of seconds, from 0 up to (but not including) the headway, drawn independently for each entry. Uses R's random number generator, so results can be made reproducible with <code>set.seed()</code>.

In entries shorter than their headway, the duration of the entry (from `start_time` to `end_time`) is used in place of the headway, so that no departure is shifted to or past `end_time` and each entry still yields at least one trip. As departures are shifted towards `end_time`, an entry may yield one trip fewer than with "exact". Entries whose `exact_times` is 1 follow an exact schedule and are always converted as with "exact".

Value

A GTFS object with updated frequencies, `stop_times` and trips tables.

Details

A single trip described in a frequencies table may yield multiple trips after converting the GTFS. Let's say, for example, that the frequencies table describes a trip called "example_trip", that starts at 08:00 and stops at 09:00, with a 30 minutes headway.

In practice, with the default `strategy = "exact"`, that means that one trip will depart at 08:00 and another at 08:30. As required by the GTFS specification, no trip departs at the `end_time` (09:00), which is when the headway changes or the service ceases. An entry whose `start_time` and `end_time` are equal yields a single trip, departing at that time. `frequencies_to_stop_times()` appends a "`_<n>`" suffix to the newly created trips to differentiate each one of them (e.g. in this case, the new trips, described in the trips and `stop_times` tables, would be called "example_trip_1" and "example_trip_2").

The times of each new trip are those of its template, shifted so that it departs from the first stop at the departure time. When the template has a dwell time at the first stop, a departure close to midnight may yield an arrival before 00:00:00, which is set to 00:00:00 instead.

Existing `_secs` columns in `stop_times` and frequencies (e.g. created with `convert_time_to_seconds()`) are used as-is, not recalculated from the time strings.

Examples

```
library(dplyr)

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
trip <- "CPTM L07-0"

# converts all trips listed in the frequencies table
converted_gtfs <- frequencies_to_stop_times(gtfs)

# converts only the specified trip_id
converted_gtfs <- frequencies_to_stop_times(gtfs, trip)

# how the specified trip_id was described in the frequencies table
gtfs$frequencies |>
  filter(trip_id == trip) |>
  head()

# the first row of each equivalent stop_times entry in the converted gtfs
converted_gtfs$stop_times |>
  filter(grepl(trip, trip_id)) |>
  distinct(trip_id, .keep_all = TRUE)
```

get_active_services	<i>Get active services</i>
---------------------	----------------------------

Description

Returns the services that are active on the given dates.

Usage

```
get_active_services(gtfs, date)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
date	A Date vector (including IDate) or a character vector of dates in the "YYYYMMDD" or "YYYY-MM-DD" formats.

Value

A data.table with the columns date (of class Date) and service_id, with one row for each service active on each of the given dates, sorted by date and then by service_id (in the C locale, so uppercase letters come before lowercase ones). Dates on which no service is active have no rows. service_id is never NA.

Details

A service is active on a date if its calendar entry spans the date and flags its weekday, unless the date is removed from it in `calendar_dates` (exception_type 2), or if the date is added to it in `calendar_dates` (exception_type 1). An addition wins over a removal on the same date, and either table may be missing. If the `trips` table has a `service_id` field, services not used by any trip are not returned, as in `get_dates()`. If no service is active, an empty table is returned without a warning.

See Also

`get_dates()`, `filter_by_date()`

Examples

```
data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

get_active_services(gtfs, "20060703")

# several dates, also as Date objects. only the weekend service "WE" is
# returned, because the weekday service "WD" is not used by any trip
get_active_services(gtfs, as.Date(c("2006-07-01", "2006-07-05")))
```

`get_calendar_overlap` *Get calendar overlap*

Description

Returns the periods in which all the given GTFS feeds have service, or the number of trips each feed runs on each of its service days. Either result can also be plotted. Useful to pick a date on which several feeds can be analysed together (e.g. when routing on the networks of different agencies).

Usage

```
get_calendar_overlap(gtfs, resolution = "daily", plot = FALSE)
```

Arguments

<code>gtfs</code>	Either a character vector with the paths to GTFS .zip files or a list of GTFS objects, as created by <code>read_gtfs()</code> (a single GTFS object must be wrapped in a list).
<code>resolution</code>	A string. "daily" (the default) returns the number of trips of each feed on each of its service days, and "periods" the periods in which all feeds have service.
<code>plot</code>	A logical. Whether to return a plot of the result instead of the result itself (requires the {ggplot2} package). Defaults to FALSE.

Value

If `plot = FALSE` and `resolution = "periods"`, a `data.table` with one row per period of consecutive days on which all feeds have service, and the columns `start_date`, `end_date` (both included in the period) and `n_days`. It has no rows if there is no such day.

If `plot = FALSE` and `resolution = "daily"`, a `data.table` with one row per feed and service day, and the columns `feed`, `date`, `n_trips` (the number of trips that run on the day) and `overlap` (whether all feeds have service on the day).

If `plot = TRUE`, a `ggplot` object. With `resolution = "periods"`, it shows one bar per feed (top to bottom in the given order) spanning its service days. With `resolution = "daily"`, it shows the density of each feed's trips over time (weighted by the number of trips per day), one panel per feed. In both, the overlap periods are shaded.

Details

A feed has service on a day if at least one of its services runs on it. A service runs on the days between the `start_date` and `end_date` of its calendar entry whose weekday is flagged, minus the days removed from it in `calendar_dates` (`exception_type 2`), plus the days added to it (`exception_type 1`). If a service is both added and removed on a day, the addition wins. Either table may be missing. If the feed has a `trips` table with a `service_id` field, services not used by any trip are ignored. `feed_info` dates are not used. A warning is raised for feeds without any service day.

The number of trips on a day is the number of trips of the services that run on it. A trip listed in `frequencies` counts once per departure, every `headway_secs` from `start_time` until (but not including) `end_time` (an entry whose `start_time` and `end_time` are equal departs once), and the departures of overlapping entries of the same trip are added up (identical entries count once), unlike in `frequencies_to_stop_times()`, which keeps only their unique departures. A trip with an invalid `frequencies` entry counts once, with a warning. Trips count on their service day, so departures after midnight (with times later than "24:00:00") count on the previous day. If the feed has no `trips` table with a `service_id` field, `n_trips` is `NA`, and the daily plot shows the density of its service days instead.

Feeds are named after their file names (without the extension) or after the list names. Unnamed feeds are named after their position ("feed_1", "feed_2", etc.), and duplicated names are made unique. Plots of feeds spanning long periods can be zoomed in with `ggplot2::coord_cartesian()`.

See Also

`merge_gtfs()`, `filter_by_service_id()`

Examples

```
spo_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
poa_path <- system.file("extdata/poa_gtfs.zip", package = "gtfstools")

# feeds may be given as paths to their .zip files
daily_trips <- get_calendar_overlap(c(spo_path, poa_path))
head(daily_trips)

# or as a list of GTFS objects, whose names are used as feed names
```

```

feeds <- list(spo = read_gtfs(spo_path), poa = read_gtfs(poa_path))
get_calendar_overlap(feeds, resolution = "periods")

if (requireNamespace("ggplot2", quietly = TRUE)) {
  get_calendar_overlap(feeds, plot = TRUE)
}

```

get_children_stops	<i>Get children stops recursively</i>
--------------------	---------------------------------------

Description

Returns the (recursive) children stops of each specified `stop_id`. Recursive in this context means it returns all children's children (i.e. first children, then children's children, and then their children, and so on).

Usage

```
get_children_stops(gtfs, stop_id = NULL)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>stop_id</code>	A string vector including the <code>stop_ids</code> to have their children returned. If <code>NULL</code> (the default), the function returns the children of every <code>stop_id</code> in the GTFS.

Value

A `data.table` containing the `stop_ids` and their children's `stop_ids`. If a stop doesn't have a child, its correspondent `child_id` entry is marked as `""`.

Examples

```

data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

children <- get_children_stops(gtfs)
head(children)

# use the stop_id argument to control which stops are analyzed
children <- get_children_stops(gtfs, stop_id = c("F12S", "F12N"))
children

```

get_dates

*Get service dates***Description**

Returns the dates on which the GTFS object has service.

Usage

```
get_dates(gtfs, as_date = TRUE)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
as_date	A logical. Whether to return the dates as a Date vector (TRUE, the default) or as a character vector in the "YYYYMMDD" format used by GTFS (FALSE).

Value

A sorted vector of unique dates, either of class Date or a character vector, depending on as_date. It is empty, without a warning, if the GTFS object has no service date.

Details

The GTFS object has service on a date if at least one of its services runs on it. A service runs on the dates between the start_date and end_date of its calendar entry whose weekday is flagged, minus the dates removed from it in calendar_dates (exception_type 2), plus the dates added to it (exception_type 1). Either table may be missing. If the trips table has a service_id field, services not used by any trip are ignored, so each returned date keeps at least one trip when passed to [filter_by_date\(\)](#). feed_info dates are not used.

See Also

[get_calendar_overlap\(\)](#), [filter_by_date\(\)](#)

Examples

```
data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# the calendar covers all of July 2006, but only weekends (plus 2006-07-03
# and 2006-07-04, added by calendar_dates) are returned, because the
# weekday service "WD" is not used by any trip
get_dates(gtfs)

# dates may also be returned in the "YYYYMMDD" format used by GTFS
get_dates(gtfs, as_date = FALSE)
```

get_dwell_time	<i>Get dwell time</i>
----------------	-----------------------

Description

Returns the dwell time of each specified `trip_id` at each specified `stop_id`, i.e. the time the vehicle stays at the stop, as specified in the `stop_times` table.

Usage

```
get_dwell_time(
  gtfs,
  trip_id = NULL,
  stop_id = NULL,
  unit = "s",
  from = NULL,
  to = NULL
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>trip_id</code>	A character vector including the <code>trip_ids</code> to have their dwell times calculated. If NULL (the default), the function calculates the dwell times of every <code>trip_id</code> in the GTFS.
<code>stop_id</code>	A character vector including the <code>stop_ids</code> to have their dwell times calculated. If NULL (the default), the function calculates the dwell times at every <code>stop_id</code> in the GTFS.
<code>unit</code>	A string representing the time unit in which the dwell times are desired. One of "s" (seconds, the default), "min" (minutes), "h" (hours) or "d" (days).
<code>from</code>	A string, in the "HH:MM:SS" format. Only visits whose arrival time is at or after <code>from</code> are included. If NULL (the default), there is no lower limit.
<code>to</code>	A string, in the "HH:MM:SS" format. Only visits whose arrival time is at or before <code>to</code> are included. If NULL (the default), there is no upper limit.

Value

A `data.table` with the columns `trip_id`, `stop_id`, `stop_sequence` and `dwell_time`, with one row per visit of a specified trip to a specified stop (within the time of day, if `from` or `to` is given), ordered by `trip_id` and `stop_sequence`. `dwell_time` is numeric, in the given unit, and NA where a time is blank.

Details

The dwell time of a trip at a stop is the time difference between the `departure_time` and the `arrival_time` of that visit in `stop_times`. When both `trip_id` and `stop_id` are given, the function returns the visits of every specified trip to every specified stop (not of pairs formed by their elements).

The dwell time is NA when either time is blank, as is common at stops that are not timepoints. Use [interpolate_stop_times\(\)](#) to fill these times beforehand. The first and last stops of each trip are included, usually with a dwell time of 0. Negative dwell times mean that the departure is earlier than the arrival, which usually indicates inconsistent times.

A stop visited more than once by the same trip (e.g. in a loop) has one row per visit, told apart by `stop_sequence`. For trips listed in frequencies, the times in `stop_times` are a template that applies to each of their departures, so one dwell time is returned per visit, not per departure.

from and to are compared with the `arrival_time` of each visit, as written in `stop_times`, so use times past "24:00:00" for arrivals after midnight. For trips listed in frequencies, these are template times, not the times of each departure. Visits with a blank arrival time are never included when from or to is given.

`stop_ids` are matched exactly against the `stop_ids` in `stop_times`, which are never stations. To get the dwell times at a station, use [get_children_stops\(\)](#) to list its children and pass those that appear in `stop_times`.

Times are read from the time strings: existing `_secs` columns in `stop_times` (e.g. created with [convert_time_to_seconds\(\)](#)) are not used.

See Also

[set_dwell_time\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

dwell_times <- get_dwell_time(gtfs)
head(dwell_times)

# use the trip_id and stop_id arguments to control which trips and stops
# are analyzed
get_dwell_time(gtfs, trip_id = "CPTM L07-0")
get_dwell_time(gtfs, stop_id = "18960")
get_dwell_time(
  gtfs,
  trip_id = c("CPTM L08-0", "CPTM L09-0"),
  stop_id = "18960"
)

# blank times result in NA dwell times. use the unit argument to control in
# which unit the dwell times are calculated
ggl_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
ggl_gtfs <- read_gtfs(ggl_path)
```

```
get_dwell_time(ggl_gtfs, trip_id = "AWE1", unit = "min")
```

get_parent_station	<i>Get parent stations recursively</i>
--------------------	--

Description

Returns the (recursive) parent stations of each specified `stop_id`. Recursive in this context means it returns all parents' parents (i.e. first parents, then parents' parents, and then their parents, and so on).

Usage

```
get_parent_station(gtfs, stop_id = NULL)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>stop_id</code>	A string vector including the <code>stop_ids</code> to have their parents returned. If <code>NULL</code> (the default), the function returns the parents of every <code>stop_id</code> in the GTFS.

Value

A `data.table` containing the `stop_ids` and their `parent_stations`. If a stop doesn't have a parent, its correspondent `parent_station` entry is marked as `""`.

See Also

[get_children_stops\(\)](#)

Examples

```
data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

parents <- get_parent_station(gtfs)
head(parents)

# use the stop_id argument to control which stops are analyzed
parents <- get_parent_station(gtfs, c("B1", "B2"))
parents
```

get_route_frequency	<i>Get route frequency</i>
---------------------	----------------------------

Description

Returns the number of departures and the mean headway of each specified `route_id` within a given time of day, by `service_id` (and by `direction_id`, if the field is present in the trips table).

Usage

```
get_route_frequency(gtfs, route_id = NULL, from, to)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>route_id</code>	A character vector including the <code>route_ids</code> to have their frequencies calculated. If <code>NULL</code> (the default), the function calculates the frequency of every <code>route_id</code> in the GTFS. <code>route_ids</code> not listed in trips are ignored, with a warning.
<code>from</code>	A string. The starting point of the time of day, in the "HH:MM:SS" format.
<code>to</code>	A string. The ending point of the time of day, in the "HH:MM:SS" format. Must be later than <code>from</code> .

Value

A `data.table` with the columns `route_id`, `direction_id` (only if present in the trips table), `service_id`, `departures` (the number of departures within the time of day, including each departure generated from the frequencies table) and `mean_headway` (the mean headway within the time of day, in minutes). Routes with no departures within the time of day are not included.

Details

The function counts trips, not stop visits: each trip is counted once, at its departure time, however many stops it visits within the time of day. Its results are therefore not comparable to those of functions that count the departures from each stop of a route, such as `tidytransit::get_route_frequency()`.

The departure time of a trip is the earliest departure time listed for it in `stop_times` (blank times are ignored). Trips listed in the frequencies table depart every `headway_secs` from `start_time` until (but not including) `end_time`, as in [frequencies_to_stop_times\(\)](#), so their `stop_times` entries, which are just templates, are not used (and these trips are counted even if they are not listed in `stop_times`). Trips not listed in frequencies use their `stop_times` departure times, and trips without any departure time are ignored. An error is raised if the frequencies table has invalid entries for the specified routes.

A departure is counted when it happens at or after `from` and before `to`, so that consecutive time windows (e.g. "06:00:00"-"07:00:00" and "07:00:00"-"08:00:00") don't count the same departure twice. Please note that this differs from [filter_by_time_of_day\(\)](#), which keeps entries whose times are equal to `to`. Departures after midnight are listed with times greater than "24:00:00" and

belong to the previous service day, so a time of day such as "24:00:00"- "26:00:00" should be used to account for them.

The mean headway is the length of the time of day divided by the number of departures. It is an average over the whole time of day, so it is larger than the actual headway when service starts or ends within it. When the trips table does not have a `direction_id` field, the departures of both directions are pooled together. Trips with an NA `direction_id` are grouped together.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

route_frequency <- get_route_frequency(
  gtfs,
  from = "07:00:00",
  to = "09:00:00"
)
head(route_frequency)

route_ids <- c("CPTM L07", "2002-10")
route_frequency <- get_route_frequency(
  gtfs,
  route_id = route_ids,
  from = "07:00:00",
  to = "09:00:00"
)
route_frequency
```

get_route_geometry	<i>Get route geometry</i>
--------------------	---------------------------

Description

Returns the distinct geometries of the trips of each specified `route_id` (its "variants", e.g. each direction and each short-turn service), with the `trip_id` that identifies each of them and the number of trips that follow them.

Usage

```
get_route_geometry(gtfs, route_id = NULL, method = "shapes", crs = 4326)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>route_id</code>	A character vector including the <code>route_ids</code> to have their geometries generated. If NULL (the default), the function generates geometries for every <code>route_id</code> in the GTFS. <code>route_ids</code> not listed in trips are ignored, with a warning.

method	A string, either "shapes" (the default) or "euclidean", specifying how the geometry of each trip is generated. Please see get_trip_geometry() for details. If the GTFS object doesn't have a shapes table, or if its trips table doesn't have a shape_id column, "euclidean" is used instead, with a warning.
crs	The CRS of the resulting object, either as an EPSG code or as an crs object. Defaults to 4326 (WGS 84).

Value

A `LINestring sf` with one row per route and distinct trip geometry, with the columns `route_id`, `trip_pattern` (the first `trip_id`, in alphabetical order, of the route's trips with that geometry, which identifies it), `n_trips` (the number of trips of the route with that geometry) and `geometry`. Rows are ordered by `route_id` (with NA last) and, within each route, by decreasing `n_trips`.

Details

The geometry of each trip is generated as in [get_trip_geometry\(\)](#), so it goes from the trip's first to its last stop, either along its shape or as straight lines between its stops, and the same limitations and warnings apply. The trips of a route whose geometries are identical are then merged into a single row. Trips that visit stops at different points of the same shape thus result in different rows, even if their geometries overlap.

Only trips listed both in `trips` and in `stop_times` are considered, so routes without any trip listed in `stop_times` are not included in the output. When a `trip_id` is listed more than once in `trips`, only its first entry is considered. With `route_id = NULL`, trips with a missing `route_id` are grouped together, under an NA `route_id`. Trips without any stop with coordinates (and, with `method = "shapes"`, trips that can't be located along a shape) get an empty geometry, as in [get_trip_geometry\(\)](#), and these trips are counted in an empty-geometry row of their route.

See Also

[get_trip_geometry\(\)](#), [get_shapes_geometry\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

route_geometry <- get_route_geometry(gtfs)
head(route_geometry)

route_geometry <- get_route_geometry(gtfs, route_id = "CPTM L07")
route_geometry
plot(route_geometry["n_trips"])
```

get_route_speed	<i>Get route speed</i>
-----------------	------------------------

Description

Returns summary statistics of the average speeds of the trips of each specified route_id.

Usage

```
get_route_speed(gtfs, route_id = NULL, method = "shapes", unit = "km/h")
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
route_id	A character vector including the route_ids to have their speeds summarised. If NULL (the default), the function summarises the speeds of every route_id in the GTFS. route_ids not listed in trips are ignored, with a warning.
method	A string, either "shapes" (the default) or "euclidean". "shapes" measures lengths along the trip's shape, described in the shapes table, while "euclidean" measures the straight-line (great-circle) distances between consecutive stops. If the GTFS object doesn't have a shapes table, or if its trips table doesn't have a shape_id column, "euclidean" is used instead, with a warning.
unit	A string representing the unit in which the speeds are desired. One of "km/h" (the default), "m/s" or "mph" (miles per hour).

Value

A data.table with the route_id and the minimum (min_speed), mean (mean_speed), median (median_speed), maximum (max_speed) and standard deviation (sd_speed) of the speeds of its trips, ordered by route_id.

Details

The speed of each trip is calculated with [get_trip_speed\(\)](#) (with by = "trip"), whose details also apply here. Each trip is linked to its route by the trips table. mean_speed is the unweighted mean of the trip speeds, not the total length of the trips divided by their total duration. Trips listed in frequencies count once, regardless of their headways.

Trips with NA speeds are ignored. Routes whose trips all have NA speeds get NA statistics, and sd_speed is NA for routes with a single trip with a known speed. Routes without any trip in stop_times are not returned.

See Also

[get_trip_speed\(\)](#), [set_route_speed\(\)](#), [set_trip_speed\(\)](#)

Examples

```

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

route_speed <- get_route_speed(gtfs)
head(route_speed)

route_ids <- c("CPTM L07", "2002-10")
route_speed <- get_route_speed(gtfs, route_ids)
route_speed

route_speed <- get_route_speed(gtfs, route_ids, method = "euclidean")
route_speed

route_speed <- get_route_speed(gtfs, route_ids, unit = "m/s")
route_speed

```

get_route_timetable	<i>Get route timetable</i>
---------------------	----------------------------

Description

Returns the timetable of the given routes on the given dates: one row for each stop time of their trips on each date on which the trip runs.

Usage

```
get_route_timetable(gtfs, route_id = NULL, date = NULL)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
route_id	A character vector including the route_ids whose timetable should be built. If NULL (the default), the timetable of all routes is built.
date	A Date vector (including IDate) or a character vector of dates in the "YYYYMMDD" or "YYYY-MM-DD" formats. If NULL (the default), all the dates on which the GTFS object has service (as returned by get_dates()) are used, which may result in a very large table.

Value

A data.table with the column date (of class Date), followed by all the columns of trips and all the columns of stop_times (trip_id appears only once). It is sorted by date and route_id, and then the trips of each route are sorted by their first departure time (and trip_id), each with its stop times sorted by stop_sequence. If the given routes have no trips on the given dates, an empty table with the same columns is returned, without a warning.

Details

A trip runs on a date if its service is active on it, as in [get_active_services\(\)](#), so dates outside the period covered by the GTFS object are skipped. Trips listed in `stop_times` but not in `trips` are not included. Departure times are sorted as times, not as strings, and trips without any departure time come last in their route. Duplicated rows in `trips` and `stop_times` are kept.

Without `calendar` and `calendar_dates` tables, no trip runs, and an empty table is returned. Columns other than `trip_id` present in both `trips` and `stop_times` (not defined by the GTFS reference) appear twice, the one from `stop_times` prefixed with `i.`, and the ones from `trips` are used to sort the timetable.

`date` is the service date: stop times past 24:00:00 happen on the following calendar day.

The `frequencies` table is not used: frequency-based trips appear with the times of their template trips, as listed in `stop_times`. To include all their departures, convert them with [frequencies_to_stop_times\(\)](#) first.

See Also

[get_stop_timetable\(\)](#), [get_active_services\(\)](#), [get_dates\(\)](#)

Examples

```
data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

timetable <- get_route_timetable(gtfs, "1922_3", "20210104")
head(timetable)

# several routes and dates, also as Date objects
timetable <- get_route_timetable(
  gtfs,
  route_id = c("1922_3", "1921_3"),
  date = as.Date(c("2021-01-04", "2021-01-09"))
)
table(timetable$date, timetable$route_id)
```

get_shape_length	<i>Get shape length</i>
------------------	-------------------------

Description

Returns the length of each specified `shape_id`, from its first to its last point.

Usage

```
get_shape_length(gtfs, shape_id = NULL, unit = "km")
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
shape_id	A character vector including the shape_ids to have their length calculated. If NULL (the default), the function calculates the length of every shape_id in the GTFS.
unit	A string representing the unit in which lengths are desired. Either "km" (the default) or "m".

Value

A data.table with the shape_id and the length of each shape.

Details

The points of each shape are sorted by shape_pt_sequence before the length is calculated. Lengths are great-circle distances calculated with the haversine formula, on a sphere with the same radius used by {s2} (6,371,010 meters), regardless of whether sf::sf_use_s2() is enabled. Shapes with any point with missing coordinates have NA lengths.

A trip usually travels only part of its shape, from its first to its last stop. Use [get_trip_length\(\)](#) to calculate the length of the trips.

See Also

[get_trip_length\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

shape_length <- get_shape_length(gtfs)
head(shape_length)

shape_length <- get_shape_length(gtfs, c("17846", "68962"), unit = "m")
shape_length
```

get_shapes_geometry	<i>Get the shapes table with spatial geometry</i>
---------------------	---

Description

Converts the shapes table to a LINESTRING sf object.

Usage

```
get_shapes_geometry(gtfs, shape_id = NULL, crs = 4326)
```

Arguments

gtfs	A GTFS object, as created by <code>read_gtfs()</code> .
shape_id	A character vector including the shape_ids to be converted. If NULL (the default), all shapes are converted.
crs	The CRS of the resulting object, either as an EPSG code or as an crs object. Defaults to 4326 (WGS 84).

Value

A LINESTRING sf object.

Examples

```
# read gtfs
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

shapes_sf <- get_shapes_geometry(gtfs)
head(shapes_sf)

shapes_sf <- get_shapes_geometry(gtfs, shape_id = "17846")
shapes_sf
```

```
get_start_and_end_times
```

Get start and end times

Description

Returns the earliest departure time and the latest arrival time listed in the stop_times table, optionally restricted to the given trips and/or to the trips active on the given dates.

Usage

```
get_start_and_end_times(gtfs, trip_id = NULL, date = NULL)
```

Arguments

gtfs	A GTFS object, as created by <code>read_gtfs()</code> .
trip_id	A character vector including the trip_ids to consider. If NULL (the default), all trips are considered.
date	A Date vector (including IDate) or a character vector of dates in the "YYYYMMDD" or "YYYY-MM-DD" formats. If given, only trips whose services are active on any of these dates are considered. If NULL (the default), trips are not restricted by date.

Value

A named character vector of length 2, with the elements `start_time` (the earliest departure_time) and `end_time` (the latest arrival_time), in the "HH:MM:SS" format. Times past midnight keep hours of 24 and above. If no stop time is considered, or if all their times are empty, both elements are NA, without a warning.

Details

Times are compared as seconds, not as strings, so "5:00:00" comes before "10:00:00" (and is returned as "05:00:00"). Empty times are ignored, and malformed ones are ignored with a warning.

When both `trip_id` and `date` are given, only the given trips that are active on the given dates are considered. The services active on each date are found with `get_active_services()`. Trips listed in `stop_times` but not in `trips` are not considered when `date` is given, and if the GTFS object has no `calendar` nor `calendar_dates` tables, no trip is active.

The `frequencies` table is not used: the times of frequency-based trips are taken from their template trips as they are listed in `stop_times`. To consider all their departures, convert them with `frequencies_to_stop_times()` first.

See Also

`get_active_services()`, `get_trip_duration()`

Examples

```
data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

get_start_and_end_times(gtfs)

get_start_and_end_times(gtfs, trip_id = c("146389748", "146389727"))

# restricted to the trips active on a given date
data_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

get_start_and_end_times(gtfs, date = "20060701")
```

get_stop_distances	<i>Get distances between stops</i>
--------------------	------------------------------------

Description

Returns the great-circle distance between each pair of stops visited by the given trips and/or routes.

Usage

```
get_stop_distances(gtfs, trip_id = NULL, route_id = NULL)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A character vector including the trip_ids whose stops should be considered. If NULL (the default), all trips are considered. An empty vector selects no trip.
route_id	A character vector including the route_ids whose stops should be considered. If NULL (the default), all routes are considered. An empty vector selects no route.

Value

A data.table with the columns from_stop_id, to_stop_id and distance (in meters), with one row for each pair of distinct stops, sorted by from_stop_id and to_stop_id. It is empty if fewer than two stops are selected.

Details

The stops are selected as in [get_stops\(\)](#): only the stops listed in the stop_times entries of the selected trips are considered.

Distances are great-circle distances ("as the crow flies") between the stops' coordinates, not distances along the trips' shapes or the street network.

Each pair of stops appears only once, with the stop_id that comes first in the C locale (the order used by data.table) as from_stop_id. If a stop_id is listed more than once in stops, only its first entry is used. Stops without coordinates have NA distances.

The size of the result grows with the square of the number of stops: about 1 GB of memory is used for 5,500 stops, and about 3 GB for 10,000 stops. A warning is raised when more than 1 GB is needed, so on large feeds please select only the trips or routes of interest. More than 65,536 stops can't be used at once, raising an error.

See Also

[get_stops\(\)](#), [get_trip_length\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# distances between the stops visited by a trip
distances <- get_stop_distances(gtfs, trip_id = "CPTM L07-0")
head(distances)

# distances between the stops visited by the trips of a route
distances <- get_stop_distances(gtfs, route_id = "CPTM L07")
head(distances)
```

get_stop_frequency	<i>Get stop frequency</i>
--------------------	---------------------------

Description

Returns the number of departures and the mean headway at each specified `stop_id` within a given time of day, by `service_id`. Optionally, the departures can also be counted by `route_id` (and by `direction_id`, if the field is present in the trips table).

Usage

```
get_stop_frequency(gtfs, stop_id = NULL, by_route = FALSE, from, to)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>stop_id</code>	A character vector including the <code>stop_ids</code> to have their frequencies calculated. If <code>NULL</code> (the default), the function calculates the frequency of every <code>stop_id</code> in the GTFS.
<code>by_route</code>	A logical. Whether the departures should be counted by <code>route_id</code> (and by <code>direction_id</code> , if present in the trips table) at each stop. Defaults to <code>FALSE</code> , in which case the departures of every route that serves a stop are pooled together.
<code>from</code>	A string. The starting point of the time of day, in the "HH:MM:SS" format.
<code>to</code>	A string. The ending point of the time of day, in the "HH:MM:SS" format. Must be later than <code>from</code> .

Value

A `data.table` with the columns `stop_id`, `route_id` and `direction_id` (only if `by_route` is `TRUE`, the latter only if present in the trips table), `service_id`, `departures` (the number of departures from the stop within the time of day, including each departure generated from the frequencies table) and `mean_headway` (the mean headway within the time of day, in minutes). Stops with no departures within the time of day are not included.

Details

The function counts stop departures: each `stop_times` entry with a departure time is a departure from its stop, except for the entry of the last stop of each trip (the one with the highest `stop_sequence`), from which vehicles don't depart. Entries with blank departure times (such as those of stops that are not timepoints) are not counted, so their times should be interpolated beforehand to count them. A stop visited twice by the same trip is counted twice. Its results are therefore not comparable to those of [get_route_frequency\(\)](#), which counts trips.

The `stop_times` entries of trips listed in the frequencies table are just templates: these trips depart every `headway_secs` from `start_time` until (but not including) `end_time`, and each of these departures visits the template's stops with the times shifted accordingly, as in [frequencies_to_stop_times\(\)](#). Trips without any departure time in `stop_times` don't generate departures. An error is raised if the

frequencies table has invalid entries for the trips that serve the specified stops, even if they don't have any departure time.

The stops are those listed in `stop_times`, which are never stations. Use `get_children_stops()` to get the stops of a station and sum their departures.

A departure is counted when it happens at or after `from` and before `to`, so that consecutive time windows (e.g. "06:00:00"- "07:00:00" and "07:00:00"- "08:00:00") don't count the same departure twice. Please note that this differs from `filter_by_time_of_day()`, which keeps entries whose times are equal to `to`. Departures after midnight are listed with times greater than "24:00:00" and belong to the previous service day, so a time of day such as "24:00:00"- "26:00:00" should be used to account for them.

The mean headway is the length of the time of day divided by the number of departures. It is an average over the whole time of day, so it is larger than the actual headway when service starts or ends within it. Trips with an NA `direction_id` are grouped together.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

stop_frequency <- get_stop_frequency(
  gtfs,
  from = "07:00:00",
  to = "09:00:00"
)
head(stop_frequency)

stop_ids <- c("18848", "18960")
stop_frequency <- get_stop_frequency(
  gtfs,
  stop_id = stop_ids,
  by_route = TRUE,
  from = "07:00:00",
  to = "09:00:00"
)
stop_frequency
```

get_stop_times_patterns

Get stop times patterns

Description

Identifies spatial and spatiotemporal patterns within the `stop_times` table. Please see the details to understand what a "pattern" means in each of these cases.

Usage

```
get_stop_times_patterns(gtfs, trip_id = NULL, type = "spatial", sort_sequence)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>trip_id</code>	A character vector including the <code>trip_ids</code> to have their <code>stop_times</code> entries analyzed. If <code>NULL</code> (the default), the function analyses the pattern of every <code>trip_id</code> in the GTFS.
<code>type</code>	A string specifying the type of patterns to be analyzed. Either "spatial" (the default) or "spatiotemporal".
<code>sort_sequence</code>	Deprecated; do not supply. Timetables are now always sorted by <code>stop_sequence</code> . Passing <code>TRUE</code> raises a warning, and passing <code>FALSE</code> raises an error.

Value

A `data.table` associating each `trip_id` to a `pattern_id`.

Details

Two trips are assigned to the same spatial `pattern_id` if they travel along the same sequence of stops. They are assigned to the same spatiotemporal `pattern_id`, on the other hand, if they travel along the same sequence of stops and they take the same time between stops. Please note that, in such case, only the time between stops is taken into account, and the time that the trip started is ignored (e.g. if two trips depart from stop A and follow the same sequence of stops to arrive at stop B, taking both 1 hour to do so, their spatiotemporal pattern will be considered the same, even if one departed at 6 am and another at 7 am). Please also note that only the order given by `stop_sequence` matters, not its values - e.g. if trip X lists stops A followed by stop B with `stop_sequences` 1 and 2, and trip Y lists stops A followed by stop B with `stop_sequences` 1 and 3, they are assigned to the same `pattern_id`.

Existing `_secs` columns in `stop_times` (e.g. created with `convert_time_to_seconds()`) are used as-is, not recalculated from the time strings.

Examples

```
data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

patterns <- get_stop_times_patterns(gtfs)
head(patterns)

# use the trip_id argument to control which trips are analyzed
patterns <- get_stop_times_patterns(
  gtfs,
  trip_id = c("143765658", "143765659", "143765660")
)
patterns
```

```
# use the type argument to control the type of pattern analyzed
patterns <- get_stop_times_patterns(
  gtfs,
  trip_id = c("143765658", "143765659", "143765660"),
  type = "spatiotemporal"
)
patterns
```

get_stop_timetable	<i>Get stop timetable</i>
--------------------	---------------------------

Description

Returns the timetable of the given stops on the given dates: one row for each stop time at these stops on each date on which its trip runs.

Usage

```
get_stop_timetable(gtfs, stop_id = NULL, date = NULL)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
stop_id	A character vector including the stop_ids whose timetable should be built. If NULL (the default), the timetable of all stops is built.
date	A Date vector (including IDate) or a character vector of dates in the "YYYYMMDD" or "YYYY-MM-DD" formats. If NULL (the default), all the dates on which the GTFS object has service (as returned by get_dates()) are used, which may result in a very large table.

Value

A data.table with the column date (of class Date), followed by all the columns of trips and all the columns of stop_times (trip_id appears only once). It is sorted by date, stop_id, departure time and trip_id. If no trip stops at the given stops on the given dates, an empty table with the same columns is returned, without a warning.

Details

A trip runs on a date if its service is active on it, as in [get_active_services\(\)](#), so dates outside the period covered by the GTFS object are skipped. Trips listed in stop_times but not in trips are not included. Departure times are sorted as times, not as strings, and stop times with an empty departure_time come last at each stop. Duplicated rows in trips and stop_times are kept.

Without calendar and calendar_dates tables, no trip runs, and an empty table is returned. Columns other than trip_id present in both trips and stop_times (not defined by the GTFS reference) appear twice, the one from stop_times prefixed with i., and the ones from trips are used to sort the timetable.

date is the service date: stop times past 24:00:00 happen on the following calendar day.
Only the exact given stops are included: to include the stops of a station, pass them with `get_children_stops()`.
The frequencies table is not used: frequency-based trips appear with the times of their template trips, as listed in `stop_times`. To include all their departures, convert them with `frequencies_to_stop_times()` first.

See Also

`get_route_timetable()`, `get_active_services()`, `get_dates()`

Examples

```
data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

timetable <- get_stop_timetable(gtfs, "100000720101", "20210104")
head(timetable)

# several dates, also as Date objects
timetable <- get_stop_timetable(
  gtfs,
  stop_id = "100000720101",
  date = as.Date(c("2021-01-04", "2021-01-09"))
)
table(timetable$date)
```

get_stops	<i>Get stops</i>
-----------	------------------

Description

Returns the stops visited by the given trips and/or routes.

Usage

```
get_stops(gtfs, trip_id = NULL, route_id = NULL)
```

Arguments

- gtfs A GTFS object, as created by `read_gtfs()`.
- trip_id A character vector including the `trip_ids` whose stops should be returned. If NULL (the default), all trips are considered. An empty vector selects no trip.
- route_id A character vector including the `route_ids` whose stops should be returned. If NULL (the default), all routes are considered. An empty vector selects no route.

Value

A data.table with the entries of the stops table that are visited by the selected trips, with all its columns and in its original order.

Details

A trip is selected if it is listed in `trip_id` (when given) and belongs to one of the routes listed in `route_id` (when given), so when both are given only the trips that satisfy both are selected. When `route_id` is given, trips not listed in the `trips` table can't be matched to a route and are not selected. Ids not found in the feed raise a warning.

Only the stops listed in the `stop_times` entries of the selected trips are returned, so their parent stations, entrances, etc. are not. Please use [get_parent_station\(\)](#) and [get_children_stops\(\)](#) to get these. Stops listed in `stop_times` but not in `stops` are not returned.

See Also

[get_parent_station\(\)](#), [get_children_stops\(\)](#), [filter_by_trip_id\(\)](#), [filter_by_route_id\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# stops visited by a trip
stops <- get_stops(gtfs, trip_id = "CPTM L07-0")
head(stops)

# stops visited by the trips of a route
stops <- get_stops(gtfs, route_id = "CPTM L07")
head(stops)

# stops visited by any trip
stops <- get_stops(gtfs)
nrow(stops)
```

get_stops_geometry	<i>Get the stops table with spatial geometry</i>
--------------------	--

Description

Converts the stops table to a POINT sf object.

Usage

```
get_stops_geometry(gtfs, stop_id = NULL, crs = 4326)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>stop_id</code>	A character vector including the <code>stop_ids</code> to be converted. If <code>NULL</code> (the default), all stops are converted.
<code>crs</code>	The CRS of the resulting object, either as an EPSG code or as an <code>crs</code> object. Defaults to 4326 (WGS 84).

Value

A POINT sf object.

Examples

```
# read gtfs
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

stops_sf <- get_stops_geometry(gtfs)
head(stops_sf)

stops_sf <- get_stops_geometry(gtfs, stop_id = "18848")
stops_sf
```

get_summary	<i>Get a summary of a GTFS feed</i>
-------------	-------------------------------------

Description

Runs a set of diagnostics on a GTFS feed (optionally restricted to some dates, routes, modes, agencies and a time of day), writes them to a report with tables and figures, renders the report to HTML and opens it in the browser (in interactive sessions). The diagnostics are also returned as a list of data.tables. This function does not validate or look for quality issues in the GTFS feed. To do that, use [validate_gtfs\(\)](#).

Usage

```
get_summary(
  gtfs,
  date = NULL,
  route_id = NULL,
  mode = NULL,
  agency = NULL,
  from = NULL,
  to = NULL,
  output_dir = NULL,
  open_browser = TRUE
)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() , or the path to a GTFS file.
date	A Date vector (including IDate) or a character vector of dates in the "YYYYMMDD" or "YYYY-MM-DD" formats. If given, only the services that run on these dates are described. If NULL (the default), the whole period covered by the feed is described.

route_id	A character vector. If given, only these routes are described. If NULL (the default), all routes are described.
mode	An integer vector of route_types (see filter_by_route_type()) or a character vector of mode names ("tram", "subway", "rail", "bus", "ferry", "cable_tram", "aerial_lift", "funicular", "trolleybus" and "monorail", which correspond to the basic route_types). If given, only routes of these modes are described. If NULL (the default), all modes are described.
agency	A character vector of agency_ids. If given, only the services of these agencies are described. If NULL (the default), all agencies are described.
from, to	Strings in the "HH:MM:SS" format. If given (both must be), only the trips that run within this time of day are described. If NULL (the default), the whole day is described.
output_dir	A string. The directory in which the report is saved (created if needed). If NULL (the default), a gtfstools directory inside tempdir() is used. Existing reports in this directory are overwritten.
open_browser	A logical. Whether to open the HTML report in the browser, in interactive sessions (defaults to TRUE).

Value

A named list of data.tables (invisibly, if the report was opened in the browser):

- files: the tables in the feed (file) and their number of rows (n_rows), before any filtering;
- agency: the agency_id, agency_name, agency_timezone, agency_url and agency_lang columns (those present in the feed) of the agencies that run the selected trips (all agencies, if the selected routes have no agency_id);
- services: a single row summarising the calendar of the selected services, with the columns start_date and end_date (the first and last days with service), n_days (the number of days between them, both included), n_service_days (the number of days with service), n_services (the number of service_ids), mean_trips_per_day (over the days with service), busiest_date and max_trips_per_day (the day with the most trips and its number of trips) and feed_start_date and feed_end_date (from feed_info, NA if absent);
- totals: the columns indicator, value and unit, with the number of agencies, routes, trips and stops, the total and mean length of the shapes and of the trips (in km), the total duration of the trips (in hours), the mean duration of the trips (in minutes), the mean trip speed (in km/h) and the mean route headway (in minutes). The means are taken over the shapes and trips whose value is known;
- speed, distance and frequency: summary statistics (n, min, q25, median, mean, q75, max and unit) of the trip speeds (in km/h), of the trip lengths (in km) and of the route headways (in minutes). frequency also has the columns date, from and to, with the day and the time of day in which the headways were measured.

The report is saved as gtfs_summary.md and gtfs_summary.html (together with its figures) in output_dir.

Details

The report requires the {ggplot2}, {knitr} and {rmarkdown} packages, and **Pandoc**, which is shipped with RStudio.

The feed is filtered by agency, mode, route, date and time of day, in this order. The time-of-day filter keeps the whole trips that run within it (see `filter_by_time_of_day()` with `full_trips = TRUE`), so the trip speeds and lengths refer to whole trips.

Trip lengths, durations and speeds are calculated with `get_trip_length()`, `get_trip_duration()` and `get_trip_speed()`. Each trip is counted once, however many days it runs on and however many departures the frequencies table lists for it. Trips with a zero or negative duration count in the total and mean durations, but have no speed. The total and mean shape lengths count each shape used by the selected trips once, and the number of stops counts the stops visited by the selected trips.

The services summary and the calendar chart in the report describe the whole calendar of the selected services: when date is given, the services that run on these dates are kept as a whole (see `filter_by_date()`), so they may also cover other days. The number of trips on each day is calculated as in `get_calendar_overlap()`, counting each departure listed in frequencies.

Route headways are calculated with `get_route_frequency()`, by route (and by `direction_id`, if the field is present in the trips table), on a single day: the day with the most trips among the given dates, or in the whole feed if date is NULL (the earliest one, in case of ties). They are measured within the given time of day or, if from and to are NULL, from the first to the last departure of that day, rounded out to whole hours. Trips that start on the previous day and run after midnight are not counted, and times are in the local time of each agency.

Examples

```
if (
  requireNamespace("ggplot2", quietly = TRUE) &&
  requireNamespace("knitr", quietly = TRUE) &&
  requireNamespace("rmarkdown", quietly = TRUE) &&
  rmarkdown::pandoc_available()
) {
  data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

  feed_summary <- get_summary(
    data_path,
    output_dir = tempdir(),
    open_browser = FALSE
  )
  feed_summary$totals

  feed_summary <- get_summary(
    data_path,
    mode = "bus",
    from = "07:00:00",
    to = "09:00:00",
    output_dir = tempdir(),
    open_browser = FALSE
  )
}
```

```

    feed_summary$frequency
  }

```

get_trip_duration	<i>Get trip duration</i>
-------------------	--------------------------

Description

Returns the duration of each specified trip_id.

Usage

```
get_trip_duration(gtfs, trip_id = NULL, unit = "min")
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A string vector including the trip_ids to have their duration calculated. If NULL (the default) the function calculates the duration of every trip_id in the GTFS.
unit	A string representing the time unit in which the duration is desired. One of "s" (seconds), "min" (minutes, the default), "h" (hours) or "d" (days).

Value

A data.table containing the duration of each specified trip.

Details

The duration of a trip is defined as the time difference between its last arrival time and its first departure time, as specified in the stop_times table. Trips without any arrival time or without any departure time get a NA duration, with a warning.

Existing _secs columns in stop_times (e.g. created with [convert_time_to_seconds\(\)](#)) are used as-is, not recalculated from the time strings.

Examples

```

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

trip_duration <- get_trip_duration(gtfs)
head(trip_duration)

trip_ids <- c("CPTM L07-0", "2002-10-0")
trip_duration <- get_trip_duration(gtfs, trip_id = trip_ids)
trip_duration

```

```
trip_duration <- get_trip_duration(gtfs, trip_id = trip_ids, unit = "h")
trip_duration
```

get_trip_geometry	<i>Get trip geometry</i>
-------------------	--------------------------

Description

Returns the geometry of each specified `trip_id`, from its first to its last stop, either along the trip’s shape or as straight lines between stops.

Usage

```
get_trip_geometry(
  gtfs,
  trip_id = NULL,
  method = "shapes",
  crs = 4326,
  sort_sequence,
  file = NULL
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>trip_id</code>	A character vector including the <code>trip_ids</code> to have their geometries generated. If <code>NULL</code> (the default), the function generates geometries for every <code>trip_id</code> in the GTFS.
<code>method</code>	A string, either <code>"shapes"</code> (the default) or <code>"euclidean"</code> . <code>"shapes"</code> returns the part of the trip’s shape, described in the shapes table, between its first and last stops, while <code>"euclidean"</code> links the consecutive stops of the trip along straight lines. If the GTFS object doesn’t have a shapes table, or if its trips table doesn’t have a <code>shape_id</code> column, <code>"euclidean"</code> is used instead, with a warning.
<code>crs</code>	The CRS of the resulting object, either as an EPSG code or as an <code>crs</code> object. Defaults to 4326 (WGS 84).
<code>sort_sequence</code>	Deprecated; do not supply. Timetables and shapes are now always sorted by <code>stop_sequence</code> and <code>shape_pt_sequence</code> . Passing <code>TRUE</code> raises a warning, and passing <code>FALSE</code> raises an error.
<code>file</code>	Deprecated. Use <code>method</code> instead (<code>file = "stop_times"</code> corresponds to <code>method = "euclidean"</code>).

Value

A `LINestring sf` with the `trip_id` and the geometry of each trip listed in `stop_times`.

Details

With `method = "shapes"`, the first and last stops of each trip are projected onto its shape, as in `get_trip_length()`, and the geometry is the part of the shape between them. Thus, its length matches the length returned by `get_trip_length()` (when this length is not NA, see below), and the limitations described there apply. Trips whose stops are all located at the same point of the shape get a zero-length geometry. Use `get_shapes_geometry()` for the geometry of entire shapes.

With `method = "euclidean"`, the geometry links the consecutive stops of each trip along straight lines (stops' coordinates are retrieved from the stops table), so its resolution tends to be much lower than that of the geometry generated from the shapes. Trips with a single stop get a single-point geometry.

Both methods ignore stops with missing coordinates, or not listed in stops (for which `get_trip_length()` returns NA lengths). Trips without any stop with coordinates get an empty geometry, as do, with `method = "shapes"`, trips with fewer than two stops with coordinates or not linked to a shape with at least two distinct points (the latter with a warning). Geometries along shapes that cross the antimeridian are not handled correctly.

See Also

[get_trip_length\(\)](#), [get_shapes_geometry\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

# geometry along the shape from the first to the last stop of each trip
trip_geometry <- get_trip_geometry(gtfs)
head(trip_geometry)

# straight lines between consecutive stops
trip_ids <- c("CPTM L07-0", "2002-10-0")
straight_geometry <- get_trip_geometry(
  gtfs,
  trip_id = trip_ids,
  method = "euclidean"
)
straight_geometry
plot(straight_geometry["trip_id"])
```

get_trip_length

Get trip length

Description

Returns the length of each specified `trip_id`, measured either from the first to the last stop of the trip or between each pair of consecutive stops. Lengths can be measured along the trip's shape or as straight lines between stops.

Usage

```
get_trip_length(
  gtfs,
  trip_id = NULL,
  method = "shapes",
  by = "trip",
  unit = "km",
  sort_sequence,
  file = NULL
)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A character vector including the trip_ids to have their lengths calculated. If NULL (the default), the function calculates the lengths of every trip_id in the GTFS.
method	A string, either "shapes" (the default) or "euclidean". "shapes" measures lengths along the trip's shape, described in the shapes table, while "euclidean" measures the straight-line (great-circle) distances between consecutive stops. If the GTFS object doesn't have a shapes table, or if its trips table doesn't have a shape_id column, "euclidean" is used instead, with a warning.
by	A string, either "trip" (the default) or "segment". "trip" returns the length from the first to the last stop of each trip, while "segment" returns the length between each pair of consecutive stops.
unit	A string representing the unit in which lengths are desired. Either "km" (the default) or "m".
sort_sequence	Deprecated; do not supply. Timetables and shapes are now always sorted by stop_sequence and shape_pt_sequence. Passing TRUE raises a warning, and passing FALSE raises an error.
file	Deprecated. Use method instead (file = "stop_times" corresponds to method = "euclidean").

Value

With by = "trip", a data.table with the trip_id and the length of each trip. With by = "segment", a data.table with the trip_id, the segment number, the from_stop_id and to_stop_id that delimit the segment and its length.

Details

Segments are numbered as in [get_trip_segment_duration\(\)](#), so both outputs can be joined by trip_id and segment. Trips with a single stop have a length of 0.

With method = "shapes", each stop is projected onto the closest point of its trip's shape, with stops advancing along the shape in stop_sequence order, so loops and shapes that pass by the same place more than once are handled. Some limitations remain:

- a stop slightly behind the previous one along the shape (e.g. due to imprecise coordinates) is placed at the previous stop's position, so their segment has a length of 0. On shapes that pass the same place twice in the same direction, such a stop may be matched to the later pass instead;
- on shapes whose outbound and return legs overlap exactly, the stops just before and after the turnaround may be placed at the same position. The trip length is unaffected, but the segment between them gets a length of 0 and the next one is longer.

shape_dist_traveled is ignored. Trips not linked to a shape with at least two distinct points have NA lengths, with a warning. Use [get_shape_length\(\)](#) for the length of entire shapes.

Lengths are great-circle (haversine) distances on the sphere used by {s2}. Stops with missing coordinates, or not listed in stops, result in NA lengths for their segments and trips.

See Also

[get_shape_length\(\)](#), [get_trip_speed\(\)](#), [get_trip_segment_duration\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# length along the shape from the first to the last stop of each trip
trip_length <- get_trip_length(gtfs)
head(trip_length)

# length along the shape between consecutive stops
segment_length <- get_trip_length(gtfs, "CPTM L07-0", by = "segment")
head(segment_length)

# straight-line distances between consecutive stops, in meters
straight_length <- get_trip_length(
  gtfs,
  "CPTM L07-0",
  method = "euclidean",
  by = "segment",
  unit = "m"
)
head(straight_length)
```

get_trip_segment_duration

Get trip segments' duration

Description

Returns the duration of segments between stops of each specified trip_id.

Usage

```
get_trip_segment_duration(gtfs, trip_id = NULL, unit = "min", sort_sequence)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>trip_id</code>	A string vector including the <code>trip_ids</code> to have their segments' duration calculated. If <code>NULL</code> (the default) the function calculates the segments' duration of every <code>trip_id</code> in the GTFS.
<code>unit</code>	A string representing the time unit in which the duration is desired. One of "s" (seconds), "min" (minutes, the default), "h" (hours) or "d" (days).
<code>sort_sequence</code>	Deprecated; do not supply. Timetables are now always sorted by <code>stop_sequence</code> . Passing <code>TRUE</code> raises a warning, and passing <code>FALSE</code> raises an error.

Value

A data.table containing the segments' duration of each specified trip.

Details

A trip segment is defined as the path between two subsequent stops in the same trip. The duration of a segment is defined as the time difference between its arrival time and its departure time, as specified in the `stop_times` file.

Existing `_secs` columns in `stop_times` (e.g. created with `convert_time_to_seconds()`) are used as-is, not recalculated from the time strings.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

trip_segment_dur <- get_trip_segment_duration(gtfs)
head(trip_segment_dur)

# use the trip_id argument to control which trips are analyzed
trip_segment_dur <- get_trip_segment_duration(gtfs, trip_id = "CPTM L07-0")
trip_segment_dur

# use the unit argument to control in which unit the durations are calculated
trip_segment_dur <- get_trip_segment_duration(gtfs, "CPTM L07-0", unit = "s")
trip_segment_dur
```

get_trip_speed	<i>Get trip speed</i>
----------------	-----------------------

Description

Returns the average speed of each specified `trip_id`, either from the first to the last stop of the trip or between each pair of consecutive stops.

Usage

```
get_trip_speed(
  gtfs,
  trip_id = NULL,
  method = "shapes",
  by = "trip",
  unit = "km/h",
  sort_sequence,
  file = NULL
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by <code>read_gtfs()</code> .
<code>trip_id</code>	A character vector including the <code>trip_ids</code> to have their speeds calculated. If <code>NULL</code> (the default), the function calculates the speed of every <code>trip_id</code> in the GTFS.
<code>method</code>	A string, either <code>"shapes"</code> (the default) or <code>"euclidean"</code> . <code>"shapes"</code> measures lengths along the trip's shape, described in the <code>shapes</code> table, while <code>"euclidean"</code> measures the straight-line (great-circle) distances between consecutive stops. If the GTFS object doesn't have a <code>shapes</code> table, or if its <code>trips</code> table doesn't have a <code>shape_id</code> column, <code>"euclidean"</code> is used instead, with a warning.
<code>by</code>	A string, either <code>"trip"</code> (the default) or <code>"segment"</code> . <code>"trip"</code> returns the average speed from the first to the last stop of each trip, while <code>"segment"</code> returns the average speed between each pair of consecutive stops.
<code>unit</code>	A string representing the unit in which the speeds are desired. One of <code>"km/h"</code> (the default), <code>"m/s"</code> or <code>"mph"</code> (miles per hour).
<code>sort_sequence</code>	Deprecated; do not supply. Timetables and shapes are now always sorted by <code>stop_sequence</code> and <code>shape_pt_sequence</code> . Passing <code>TRUE</code> raises a warning, and passing <code>FALSE</code> raises an error.
<code>file</code>	Deprecated. Use <code>method</code> instead (<code>file = "stop_times"</code> corresponds to <code>method = "euclidean"</code>).

Value

With `by = "trip"`, a `data.table` with the `route_id`, the `trip_id` and the average speed of each trip. With `by = "segment"`, a `data.table` with the `route_id`, the `trip_id`, the segment number, the `from_stop_id` and `to_stop_id` that delimit the segment and its average speed.

Details

The speed is the length calculated by `get_trip_length()` divided by the duration calculated by `get_trip_duration()` (with `by = "trip"`) or by `get_trip_segment_duration()` (with `by = "segment"`). Speeds are NA when the length is NA (e.g. trips not linked to a shape) or when the duration is missing (e.g. blank times at intermediate stops) or not positive. With `by = "trip"`, trips without any arrival or departure time raise the warning of `get_trip_duration()`.

The `route_id` of each trip comes from the trips table, which is required (also with `method = "euclidean"`). Trips not listed in trips have an NA `route_id`.

Existing `_secs` columns in `stop_times` (e.g. created with `convert_time_to_seconds()`) are used as-is, not recalculated from the time strings.

See Also

`get_route_speed()`, `set_trip_speed()`, `set_route_speed()`, `get_trip_length()`, `get_trip_duration()`, `get_trip_segment_duration()`

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

trip_speed <- get_trip_speed(gtfs)
head(trip_speed)

trip_ids <- c("CPTM L07-0", "2002-10-0")
trip_speed <- get_trip_speed(gtfs, trip_ids)
trip_speed

trip_speed <- get_trip_speed(gtfs, trip_ids, method = "euclidean")
trip_speed

trip_speed <- get_trip_speed(gtfs, trip_ids, unit = "m/s")
trip_speed

segment_speed <- get_trip_speed(gtfs, "CPTM L07-0", by = "segment")
head(segment_speed)
```

interpolate_stop_times

Interpolate missing stop times

Description

Fills blank `arrival_times` and `departure_times` in `stop_times`, assuming that vehicles travel at a constant speed between consecutive stops with known times (timepoints).

Usage

```
interpolate_stop_times(gtfs, trip_id = NULL, method = "shapes")
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A character vector including the trip_ids to have their stop times interpolated. If NULL (the default), the function interpolates the stop times of every trip_id in the GTFS.
method	A string, either "shapes" (the default) or "euclidean". "shapes" measures lengths along the trip's shape, described in the shapes table, while "euclidean" measures the straight-line (great-circle) distances between consecutive stops. If the GTFS object doesn't have a shapes table, or if its trips table doesn't have a shape_id column, "euclidean" is used instead, with a warning.

Value

A GTFS object whose stop_times has its blank times filled in. The order of the rows and the other columns are kept. The given GTFS object is not modified.

Details

Within each trip, ordered by stop_sequence, a stop whose arrival and departure times are both blank gets a time interpolated linearly on the distance travelled from the preceding timepoint, as measured by [get_trip_length\(\)](#). In other words, the vehicle travels between two timepoints at a constant speed: the distance between them divided by the time from the departure at the first to the arrival at the second. Interpolated stops get equal arrival and departure times (no dwell time), rounded to the nearest second. Times past "24:00:00" are supported. If the distance between two timepoints is 0, their times are spread evenly between the stops in between.

A timepoint with only one of its two times blank gets the other time in both columns. If stop_times has a timepoint column, interpolated stops get timepoint = 0 (approximate times). The column is not created if it doesn't exist.

Some stops are left blank, with a warning:

- stops before a trip's first or after its last timepoint, including every stop of trips with fewer than two timepoints;
- stops between timepoints whose distance can't be calculated, e.g. trips not linked to a shape or stops without coordinates;
- stops between timepoints in which the arrival is earlier than the previous departure. This usually happens when times after midnight are written as "00:30:00" instead of "24:30:00".

Times are blank when they are NA, empty or whitespace-only strings, or "NA". Malformed time strings are left unchanged, with a warning, and are not used as timepoints. Rows without a trip_id are left unchanged. Times are read from the time strings, and existing _secs columns (e.g. created with [convert_time_to_seconds\(\)](#)) are updated to match. For trips listed in frequencies, the template times are interpolated.

The stops table is required to interpolate times between timepoints, as well as the shapes table and the shape_id column in trips with method = "shapes" (see [get_trip_length\(\)](#)).

See Also

[get_trip_length\(\)](#), [get_trip_speed\(\)](#), [set_trip_speed\(\)](#)

Examples

```
library(dplyr)

data_path <- system.file("extdata/poa_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
trip <- "T2-1@1#520"

# only the first and last stops of each trip have times
gtfs$stop_times |>
  filter(trip_id == trip) |>
  head()

# distances measured along the trips' shapes. some trips of this feed have
# times past midnight written as "00:xx:xx", so they are left blank
interpolated_gtfs <- suppressWarnings(interpolate_stop_times(gtfs))
interpolated_gtfs$stop_times |>
  filter(trip_id == trip) |>
  head()

# the speed is now known between every pair of consecutive stops
head(get_trip_speed(interpolated_gtfs, trip, by = "segment"))

# straight-line distances between stops, for a single trip
interpolated_gtfs <- interpolate_stop_times(
  gtfs,
  trip_id = trip,
  method = "euclidean"
)
interpolated_gtfs$stop_times |>
  filter(trip_id == trip) |>
  head()
```

list_validator_versions

List MobilityData's GTFS validator versions

Description

Lists available versions of MobilityData's command line tool to validate GTFS feeds.

Usage

```
list_validator_versions()
```

Value

A data.table with each CLI version, published date, and download URL.

See Also

Other validation: [download_validator\(\)](#), [validate_gtfs\(\)](#)

merge_gtfs	<i>Merge GTFS files</i>
------------	-------------------------

Description

Combines many GTFS objects into a single one.

Usage

```
merge_gtfs(..., files = NULL, prefix = FALSE)
```

Arguments

...	GTFS objects to be merged. Each argument can either be a GTFS or a list of GTFS objects.
files	A character vector listing the GTFS tables to be merged. If NULL (the default), all tables are merged. Elements that are not tables, such as the locations of GTFS-Flex feeds (read from a geojson file), are not merged and are left out of the result, with a warning.
prefix	Either a logical or a character vector (defaults to FALSE). Whether to add a prefix to the value of id fields that identify from which GTFS object the value comes from. If TRUE, the prefixes will range from "1" to n, where n is the number of objects passed to the function. If a character vector, its elements will be used to identify the GTFS objects, and the length of the vector must equal the total amount of objects passed in ... (the first element will identify the first GTFS, the second element the second GTFS, and so on).

Value

A GTFS object in which each table is a combination (by row) of the tables from the specified GTFS objects.

Examples

```
spo_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
ggl_path <- system.file("extdata/ggl_gtfs.zip", package = "gtfstools")

spo_gtfs <- read_gtfs(spo_path)
names(spo_gtfs)
```

```

ggl_gtfs <- read_gtfs(ggl_path)
names(ggl_gtfs)

merged_gtfs <- merge_gtfs(spo_gtfs, ggl_gtfs)
names(merged_gtfs)

# use a list() to programatically merge many GTFS objects
gtfs_list <- list(spo_gtfs, ggl_gtfs)
merged_gtfs <- merge_gtfs(gtfs_list)

# 'prefix' helps disambiguating from which GTFS each id comes from.
# if TRUE, the ids range from 1:n, where n is the number of gtfs
merged_gtfs <- merge_gtfs(gtfs_list, prefix = TRUE)
merged_gtfs$agency

# if a character vector, its elements will be used to identify the each gtfs
merged_gtfs <- merge_gtfs(gtfs_list, prefix = c("spo", "ggl"))
merged_gtfs$agency

```

read_gtfs

Read GTFS files

Description

Reads GTFS text files from either a local .zip file or an URL.

Usage

```

read_gtfs(
  path,
  files = NULL,
  fields = NULL,
  skip = NULL,
  quiet = TRUE,
  encoding = "unknown"
)

```

Arguments

path	The path to a GTFS .zip file.
files	A character vector containing the text files to be read from the GTFS (without the .txt extension). If NULL (the default) all existing files are read.
fields	A named list containing the fields to be read from each text file, in the format <code>list(file = c("field1", "field2"))</code> . If NULL (the default), all fields from the files specified in <code>files</code> are read. If a file is specified in <code>files</code> but not in <code>fields</code> , all fields from that file will be read (i.e. you may specify in <code>fields</code> only files whose fields you want to subset).

skip	A character vector containing the text files that should not be read from the GTFS, without the .txt extension. If NULL (the default), no files are skipped. Cannot be used if files is already set.
quiet	Whether to hide log messages and progress bars (defaults to TRUE).
encoding	A string, ultimately passed to <code>data.table::fread()</code> . Defaults to "unknown". Other possible options are "UTF-8" and "Latin-1". Please note that this is not used to re-encode the input, but to enable handling encoded strings in their native encoding.

Value

A data.table-based GTFS object: a list of data.tables in which each table represents a GTFS text file.

Details

The column types of each data.table in the final GTFS object conform as closely as possible to the [Google's Static GTFS Reference](#). Exceptions are date-related columns (such as calendar.txt's start_date and end_date, for example), which are converted to Date objects, instead of being kept as integers, allowing for easier data manipulation. These columns are converted back to integers when writing the GTFS object to a .zip file using `write_gtfs()`.

See Also

Other io functions: `write_gtfs()`

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)
names(gtfs)

gtfs <- read_gtfs(data_path, files = c("trips", "stop_times"))
names(gtfs)

gtfs <- read_gtfs(data_path, skip = "trips")
names(gtfs)

gtfs <- read_gtfs(data_path, fields = list(agency = "agency_id"))
names(gtfs)
names(gtfs$agency)
```

remove_duplicates	<i>Remove duplicated entries</i>
-------------------	----------------------------------

Description

Removes duplicated entries from GTFS objects tables.

Usage

```
remove_duplicates(gtfs)
```

Arguments

gtfs A GTFS object, as created by [read_gtfs\(\)](#).

Value

A GTFS object containing only unique entries.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# this gtfs includes some duplicated entries
gtfs$agency

gtfs <- remove_duplicates(gtfs)
gtfs$agency
```

remove_unused_ids	<i>Remove unused ids</i>
-------------------	--------------------------

Description

Removes the ids that the feed doesn't use, with their entries in every file. A trip is used if it has stop_times, and anything that a used trip refers to, directly or indirectly, is used too. Entries that refer to removed ids are removed as well, including those in attributions and translations. When there are no fare_rules, fare_attributes and their agencies are kept, since these fares apply to the whole feed. Fares v2 and GTFS-Flex files are left unchanged, so they may still refer to removed ids.

Usage

```
remove_unused_ids(gtfs)
```

Arguments

gtfs A GTFS object, as created by [read_gtfs\(\)](#).

Value

The GTFS object without unused ids.

See Also

[filter_by_trip_id\(\)](#), [remove_duplicates\(\)](#)

Examples

```
data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)
nrow(gtfs$agency)

gtfs <- remove_unused_ids(gtfs)
nrow(gtfs$agency)
```

set_dwell_time

Set dwell time

Description

Sets the dwell time of each specified trip_id at each specified stop_id, i.e. the time the vehicle stays at the stop, by changing the departure_time at these stops in stop_times and shifting the later times of the trips accordingly.

Usage

```
set_dwell_time(
  gtfs,
  trip_id = NULL,
  stop_id = NULL,
  dwell_time,
  unit = "s",
  from = NULL,
  to = NULL,
  by_reference = FALSE
)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
trip_id	A character vector including the <code>trip_ids</code> to have their dwell times set. If NULL (the default), the dwell times of every <code>trip_id</code> in the GTFS are set.
stop_id	A character vector including the <code>stop_ids</code> at which the dwell times are set. If NULL (the default), the dwell times are set at every <code>stop_id</code> in the GTFS.
dwell_time	A non-negative number, the dwell time to be set, in unit. It's rounded to the nearest whole second and applies to every specified visit (call the function once per value to set different dwell times).
unit	A string representing the time unit in which <code>dwell_time</code> is given. One of "s" (seconds, the default), "min" (minutes), "h" (hours) or "d" (days).
from	A string, in the "HH:MM:SS" format. Only visits whose arrival time is at or after <code>from</code> are changed. If NULL (the default), there is no lower limit.
to	A string, in the "HH:MM:SS" format. Only visits whose arrival time is at or before <code>to</code> are changed. If NULL (the default), there is no upper limit.
by_reference	Whether to update <code>stop_times</code> ' data.table by reference. Defaults to FALSE.

Value

If `by_reference` is set to FALSE, returns a GTFS object with the time columns of its `stop_times` adjusted. Else, returns a GTFS object invisibly (note that in this case the original GTFS object is altered).

Details

The dwell time of a trip at a stop is the time difference between the `departure_time` and the `arrival_time` of that visit in `stop_times`, as returned by [get_dwell_time\(\)](#). The function sets it at the visits of every specified trip to every specified stop (not of pairs formed by their elements), within the time of day if `from` or `to` is given. At each of these visits, the arrival time is kept and the departure time is set to the arrival time plus `dwell_time`. All the later times of the trip, in `stop_sequence` order, are shifted by the change in the dwell time, so the travel times between stops are kept and the trip ends earlier or later. Changes at several visits of the same trip add up.

Setting the dwell time at a trip's first stop shifts the rest of the trip. At its last stop, only the departure time changes. A stop visited more than once by the same trip (e.g. in a loop) has its dwell time set at each visit.

Blank times are never filled, and later blank times stay blank. Selected visits with a blank arrival or departure time have no dwell time to change, so their dwell time is not set and they don't shift the later times. When `stop_id` is given, this raises a warning. Use [interpolate_stop_times\(\)](#) to fill blank times beforehand. The function raises an error if a shift would result in a negative time, which only happens when the times of a trip are not in chronological order, or in a time later than "9999:59:59", the latest time that can be written. The visits of each trip are ordered by `stop_sequence`, which is assumed to be unique within each trip and not NA, as required by the GTFS specification. When both `trip_id` and `stop_id` are given, but none of the trips visits any of the stops, the function raises a warning and returns the GTFS unchanged.

For trips listed in `frequencies`, the times in `stop_times` are a template: the trips depart at the times listed in `frequencies`, starting from their first departure (see [frequencies_to_stop_times\(\)](#)).

Setting the dwell time at the first stop of such a trip therefore changes only how long before each departure the vehicle arrives there, while changes at later stops lengthen or shorten every departure of the trip.

from and to are compared with the arrival_time of each visit, as written in stop_times before any change, so use times past "24:00:00" for arrivals after midnight. A shift caused by an earlier visit may thus move a changed visit out of the time of day, or another visit into it. For trips listed in frequencies, these are template times, not the times of each departure. Visits with a blank arrival time are never selected when from or to is given, so they don't raise the warning above. When the time of day contains no visit of the specified trips to the specified stops, the GTFS is returned unchanged.

stop_ids are matched exactly against the stop_ids in stop_times, which are never stations. To set the dwell times at a station, use `get_children_stops()` to list its children and pass those that appear in stop_times.

Changed times are written in the "HH:MM:SS" format. Existing _secs columns in stop_times (e.g. created with `convert_time_to_seconds()`) are updated to match.

See Also

`get_dwell_time()`, `set_trip_speed()`

Examples

```
library(dplyr)

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# set a 30 seconds dwell time at a stop of a trip. the later times of the
# trip are shifted by 30 seconds
new_gtfs <- set_dwell_time(
  gtfs,
  trip_id = "CPTM L07-0",
  stop_id = "18920",
  dwell_time = 30
)
new_gtfs$stop_times |>
  filter(trip_id == "CPTM L07-0") |>
  head()

# set the dwell time at a stop in every trip that visits it. use the unit
# argument to give the dwell time in another unit
new_gtfs <- set_dwell_time(
  gtfs,
  stop_id = "18960",
  dwell_time = 1,
  unit = "min"
)
get_dwell_time(new_gtfs, stop_id = "18960")
```

```
# set the dwell time only at the visits that arrive within a time of day
new_gtfs <- set_dwell_time(
  gtfs,
  trip_id = "CPTM L07-0",
  dwell_time = 30,
  from = "05:00:00",
  to = "06:00:00"
)
get_dwell_time(new_gtfs, trip_id = "CPTM L07-0")

# original gtfs remains unchanged
get_dwell_time(gtfs, stop_id = "18960")

# when doing by reference, original gtfs is changed
set_dwell_time(
  gtfs,
  trip_id = "CPTM L07-0",
  stop_id = "18920",
  dwell_time = 30,
  by_reference = TRUE
)
gtfs$stop_times |>
  filter(trip_id == "CPTM L07-0") |>
  head()
```

set_max_speed	<i>Set trip maximum speed</i>
---------------	-------------------------------

Description

Caps the speed of the specified trips: each part of a trip that is faster than max_speed is slowed down to max_speed, by changing the arrival_time and departure_time columns in stop_times. Parts of the trips that are already slower are left unchanged.

Usage

```
set_max_speed(gtfs, max_speed, route_id = NULL, trip_id = NULL, unit = "km/h")
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
max_speed	A number. The maximum speed allowed, in the unit given by unit.
route_id	A character vector including the route_ids whose trips have their speeds capped. If both route_id and trip_id are NULL (the default), the speeds of every trip in the GTFS are capped. route_ids not listed in trips are ignored, with a warning.

trip_id	A character vector including the trip_ids to have their speeds capped. When given together with route_id, the trips of both are capped.
unit	A string representing the unit in which the speed is given. One of "km/h" (the default), "m/s" or "mph" (miles per hour).

Value

A GTFS object with the time columns of its stop_times adjusted.

Details

The speed of each span between two consecutive stops with times is its length, as calculated by [get_trip_length\(\)](#) along the trip's shape (or as straight lines between stops, with a warning, if there are no shapes), divided by the time between the departure from the first stop and the arrival at the second. Stops with blank times inside a span are kept blank. The stops table is required. Spans whose length is NA (e.g. in trips not linked to a shape) are left unchanged.

Each span faster than max_speed has its duration increased to its length divided by max_speed, rounded up to the next second, so new times may include seconds even if the original times were given in whole minutes. Spans with zero duration are treated the same way. All the later times of the trip are shifted by the accumulated extra time, so dwell times are kept. Spans whose arrival is earlier than the previous departure are left unchanged, with a warning. This usually happens when times after midnight are written as "00:30:00" instead of "24:30:00". Only stop_times is modified.

See Also

[set_trip_speed\(\)](#), [get_trip_speed\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

# the trip is faster than 30 km/h between some of its stops
get_trip_speed(gtfs, "CPTM L07-0", by = "segment")

gtfs_capped <- set_max_speed(gtfs, max_speed = 30, trip_id = "CPTM L07-0")
get_trip_speed(gtfs_capped, "CPTM L07-0", by = "segment")

# the later stops are shifted, so the trip ends later
get_start_and_end_times(gtfs, trip_id = "CPTM L07-0")
get_start_and_end_times(gtfs_capped, trip_id = "CPTM L07-0")

# cap the speed of all the trips of all routes of the GTFS feed
gtfs_capped <- set_max_speed(gtfs, max_speed = 8)
```

set_route_frequency	<i>Set route frequency</i>
---------------------	----------------------------

Description

Sets the headway of each specified `route_id` within a given time of day, by replacing its trips in that time of day with a single frequency-based trip, described in the frequencies table.

Usage

```
set_route_frequency(gtfs, route_id, headway, from, to)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>route_id</code>	A character vector including the <code>route_ids</code> to have their frequency set. <code>route_ids</code> not listed in trips are ignored, with a warning.
<code>headway</code>	A number. The headway to be set, in minutes. It is rounded to whole seconds and applies to every <code>route_id</code> (call the function once per route to set different headways).
<code>from</code>	A string. The starting point of the time of day, in the "HH:MM:SS" format.
<code>to</code>	A string. The ending point of the time of day, in the "HH:MM:SS" format. Must be later than <code>from</code> .

Value

A GTFS object with updated frequencies, trips and stop_times tables (and transfers, when present). If the given GTFS object has no frequencies table, one is created.

Details

The departures of the routes are grouped as in [get_route_frequency\(\)](#): by `route_id`, `service_id` and `direction_id` (if present in trips). The function changes existing service, it does not create it, so groups with no departure within the time of day are not modified. In each of the other groups:

- the trips that depart within the time of day are replaced by a single template trip: among the trips of the stop pattern (as identified by [get_stop_times_patterns\(\)](#)) with the most departures within the time of day, the one that departs first. Its travel times apply to all the new departures. The trips of other patterns that depart within the time of day are removed (frequency-based ones lose their frequencies entries within the time of day, see below);
- a frequencies entry is added for the template, from `from` to `to`, with `headway_secs` set to `headway` and `exact_times = 0` (frequency-based service). A scheduled template thus becomes a frequency-based trip, and the transfers entries that refer to it now apply to all of its departures;

- the existing frequencies entries of the group's trips are clipped to the time of day, keeping the departures outside it exactly as before (when converted with `frequencies_to_stop_times()` with `strategy = "exact"`). Trips left without any departure are removed from trips, stop_times and transfers.

As in `get_route_frequency()`, a departure is within the time of day when it happens at or after from and before to, so `get_route_frequency()` reports the new headway (exactly, when the length of the time of day is a multiple of headway). Departures after midnight are listed with times greater than "24:00:00", so a time of day such as "24:00:00"- "26:00:00" should be used for them. Scheduled trips that depart before from are not changed, even if they run within the time of day. Groups whose trips within the time of day have no departure time in stop_times can't have a template, and are left unchanged with a warning. Removed trips may leave unused entries in other tables, such as shapes and calendar, which can be removed with `remove_unused_ids()`.

The stop_times table requires the stop_id and stop_sequence fields. Existing _secs columns in frequencies (e.g. created with `convert_time_to_seconds()`) are updated.

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

get_route_frequency(
  gtfs,
  route_id = "CPTM L07",
  from = "07:00:00",
  to = "09:00:00"
)

# sets a 10 minutes headway from 7 to 9 am
new_gtfs <- set_route_frequency(
  gtfs,
  route_id = "CPTM L07",
  headway = 10,
  from = "07:00:00",
  to = "09:00:00"
)

get_route_frequency(
  new_gtfs,
  route_id = "CPTM L07",
  from = "07:00:00",
  to = "09:00:00"
)

# use frequencies_to_stop_times() to get the scheduled trips
new_gtfs <- frequencies_to_stop_times(new_gtfs)
```

set_route_speed	<i>Set route average speed</i>
-----------------	--------------------------------

Description

Sets the average speed of the trips of each specified `route_id`, or of a segment of them, by changing the `arrival_time` and `departure_time` columns in `stop_times`.

Usage

```
set_route_speed(
  gtfs,
  route_id,
  speed,
  unit = "km/h",
  first_stop = NULL,
  last_stop = NULL,
  from = NULL,
  to = NULL,
  by_reference = FALSE
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>route_id</code>	A character vector including the <code>route_ids</code> to have the average speed of their trips set. <code>route_ids</code> not listed in trips are ignored, with a warning.
<code>speed</code>	A number representing the speed to be set for the trips of all <code>route_ids</code> . Must be positive and finite.
<code>unit</code>	A string representing the unit in which the speed is given. One of "km/h" (the default), "m/s" or "mph" (miles per hour).
<code>first_stop</code>	A string. The <code>stop_id</code> where the segment whose speed is set starts. If NULL (the default), the segment starts at each trip's first stop.
<code>last_stop</code>	A string. The <code>stop_id</code> where the segment ends. If NULL (the default), the segment ends at each trip's last stop.
<code>from</code>	A string, in the "HH:MM:SS" format. Only trips that depart from the segment's first stop at or after <code>from</code> are changed. If NULL (the default), there is no lower limit.
<code>to</code>	A string, in the "HH:MM:SS" format. Only trips that depart from the segment's first stop at or before <code>to</code> are changed. If NULL (the default), there is no upper limit.
<code>by_reference</code>	Whether to update <code>stop_times</code> ' <code>data.table</code> by reference. Defaults to FALSE.

Value

If `by_reference` is set to `FALSE`, returns a GTFS object with the time columns of its `stop_times` adjusted. Else, returns a GTFS object invisibly (note that in this case the original GTFS object is altered).

Details

Every trip of each route, as listed in `trips`, gets the given speed, as in `set_trip_speed()`, whose details also apply here: the duration of each trip's segment (by default, the whole trip) is set to its length divided by speed, the times at stops inside the segment are set to "", and from and to restrict the changes to the trips that depart from the segment's first stop within the time of day. Warnings about trips that can't be changed refer to their `trip_ids`. Trips without `stop_times` entries are ignored.

See Also

[set_trip_speed\(\)](#), [get_trip_speed\(\)](#), [get_route_speed\(\)](#)

Examples

```
library(dplyr)

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

get_route_speed(gtfs, route_id = "CPTM L07")

new_speed_gtfs <- set_route_speed(gtfs, route_id = "CPTM L07", speed = 50)
get_route_speed(new_speed_gtfs, route_id = "CPTM L07")

# set the speed only of the trips that depart within a time of day
poa_path <- system.file("extdata/poa_gtfs.zip", package = "gtfstools")
poa_gtfs <- read_gtfs(poa_path)

poa_new_speed <- set_route_speed(
  poa_gtfs,
  route_id = "T2",
  speed = 25,
  from = "07:00:00",
  to = "09:00:00"
)

# the arrival at the last stop of a trip that departs at 07:02 changes
poa_gtfs$stop_times |>
  filter(trip_id == "T2-1@1#702") |>
  slice_tail(n = 1)

poa_new_speed$stop_times |>
  filter(trip_id == "T2-1@1#702") |>
  slice_tail(n = 1)
```

set_trip_speed	<i>Set trip average speed</i>
----------------	-------------------------------

Description

Sets the average speed of each specified `trip_id`, or of a segment of it, by changing the `arrival_time` and `departure_time` columns in `stop_times`.

Usage

```
set_trip_speed(
  gtfs,
  trip_id,
  speed,
  unit = "km/h",
  first_stop = NULL,
  last_stop = NULL,
  from = NULL,
  to = NULL,
  by_reference = FALSE
)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>trip_id</code>	A string vector including the <code>trip_ids</code> to have their average speed set.
<code>speed</code>	A numeric representing the speed to be set. Its length must either equal 1, in which case the value is recycled for all <code>trip_ids</code> , or equal <code>trip_id</code> 's length. Must be positive and finite. A <code>trip_id</code> listed more than once must be given the same speed.
<code>unit</code>	A string representing the unit in which the speed is given. One of "km/h" (the default), "m/s" or "mph" (miles per hour).
<code>first_stop</code>	A string. The <code>stop_id</code> where the segment whose speed is set starts. If NULL (the default), the segment starts at each trip's first stop.
<code>last_stop</code>	A string. The <code>stop_id</code> where the segment ends. If NULL (the default), the segment ends at each trip's last stop.
<code>from</code>	A string, in the "HH:MM:SS" format. Only trips that depart from the segment's first stop at or after <code>from</code> are changed. If NULL (the default), there is no lower limit.
<code>to</code>	A string, in the "HH:MM:SS" format. Only trips that depart from the segment's first stop at or before <code>to</code> are changed. If NULL (the default), there is no upper limit.
<code>by_reference</code>	Whether to update <code>stop_times</code> ' <code>data.table</code> by reference. Defaults to FALSE.

Value

If `by_reference` is set to `FALSE`, returns a GTFS object with the time columns of its `stop_times` adjusted. Else, returns a GTFS object invisibly (note that in this case the original GTFS object is altered).

Details

The duration of each trip's segment (from the departure at `first_stop` to the arrival at `last_stop`; by default the whole trip) is set to its length, as calculated by `get_trip_length()` along the trip's shape (or as straight lines between stops, with a warning, if there are no shapes), divided by speed. The stops table is required. Trips whose length is NA (e.g. trips not linked to a shape) are left unchanged.

The arrival and departure times at stops strictly inside the segment are set to "", which is written as NA by `write_gtfs()`. Some routing software, such as [OpenTripPlanner](#), interpolates these times from the average speed.

`first_stop` is matched at its first visit in `stop_sequence` order, and `last_stop` at its next visit after that (which may be the same stop). Times after `last_stop` are shifted by the change in the segment's duration. Dwell times at `first_stop` and `last_stop` are kept, except at the trip's first and last stops. Trips that don't visit `first_stop` and then `last_stop`, or that have blank times there, are left unchanged with a warning. `from` and `to` are compared with the `departure_time` at `first_stop` as written in `stop_times`, so use times past "24:00:00" for departures after midnight. For trips listed in frequencies, these are template times, not actual departures. Trips whose departure there is blank are left unchanged.

See Also

`set_route_speed()`, `get_trip_speed()`, `get_route_speed()`

Examples

```
library(dplyr)

data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")

gtfs <- read_gtfs(data_path)

gtfs_new_speed <- set_trip_speed(gtfs, trip_id = "CPTM L07-0", 50)
gtfs_new_speed$stop_times |>
  filter(trip_id == "CPTM L07-0")

# use the unit argument to change the speed unit
gtfs_new_speed <- set_trip_speed(
  gtfs,
  trip_id = "CPTM L07-0",
  speed = 15,
  unit = "m/s"
)
gtfs_new_speed$stop_times |>
  filter(trip_id == "CPTM L07-0")
```

```

# set the speed only between two stops. later stops are shifted
gtfs_new_speed <- set_trip_speed(
  gtfs,
  trip_id = "CPTM L07-0",
  speed = 30,
  first_stop = "18917",
  last_stop = "18922"
)
gtfs_new_speed$stop_times |>
  filter(trip_id == "CPTM L07-0")

# set the speed only of the trips that depart within a time of day
poa_path <- system.file("extdata/poa_gtfs.zip", package = "gtfstools")
poa_gtfs <- read_gtfs(poa_path)

poa_new_speed <- set_trip_speed(
  poa_gtfs,
  trip_id = poa_gtfs$trips$trip_id,
  speed = 25,
  from = "07:00:00",
  to = "09:00:00"
)

# the arrival at the last stop of a trip that departs at 07:02 changes
poa_gtfs$stop_times |>
  filter(trip_id == "T2-1@1#702") |>
  slice_tail(n = 1)

poa_new_speed$stop_times |>
  filter(trip_id == "T2-1@1#702") |>
  slice_tail(n = 1)

# original gtfs remains unchanged
gtfs$stop_times |>
  filter(trip_id == "CPTM L07-0")

# when doing by reference, original gtfs is changed
set_trip_speed(gtfs, trip_id = "CPTM L07-0", 50, by_reference = TRUE)

gtfs$stop_times |>
  filter(trip_id == "CPTM L07-0")

```

Description

Converts scheduled trips, described only in `stop_times`, into frequency-based trips, described in `frequencies`. Trips that follow the same route and sequence of stops are summarised, in each hour of the day, by a single template trip and the headway between their departures. This is a lossy approximation of the original schedule.

Usage

```
stop_times_to_frequencies(gtfs, trip_id = NULL)
```

Arguments

<code>gtfs</code>	A GTFS object, as created by read_gtfs() .
<code>trip_id</code>	A character vector including the <code>trip_ids</code> to be converted. If <code>NULL</code> (the default), the function converts all trips listed in <code>stop_times</code> that are not already listed in <code>frequencies</code> .

Value

A GTFS object with updated `frequencies`, `stop_times` and `trips` tables (and `transfers`, when present). If the given GTFS object has no `frequencies` table, one is created.

Details

Trips are grouped together when they share the same `route_id`, `service_id`, `direction_id` and `shape_id` (these last two only when present in `trips`) and the same sequence of stops (their spatial pattern, as identified by [get_stop_times_patterns\(\)](#)). Each group is then split into one-hour slots of the clock, from HH:00:00 (included) to the next HH:00:00 (not included), according to the earliest `departure_time` of each trip in `stop_times`, regardless of `stop_sequence`. This is the departure from the trip's first stop in valid feeds, but not when later times are written incorrectly (e.g. times after midnight written as "00:30:00" instead of "24:30:00"). Slots after midnight are kept as such (e.g. from "25:00:00" to "26:00:00").

In each slot with `n` trips:

- the trip with the earliest departure (ties broken by `trip_id`) becomes the template. It keeps its `trip_id`, its `trips` entry and its `stop_times` entries, so travel times may differ from one hour to another. As in any frequency-based trip, only its times relative to its first departure matter;
- a `frequencies` entry is added for the template, from the start to the end of the slot, with `headway_secs = ceiling(3600 / n)` and `exact_times = 0` (frequency-based service);
- the other trips are removed from `trips`, `stop_times` and `transfers`. Their own departure times, travel times and other trips fields (e.g. `trip_headsign`, `block_id`) are lost. `transfers` entries that refer to the template now apply to all of its departures. Other tables that may refer to trips, such as `attributions` and `translations`, are not changed.

Slots with a single trip are also converted (with a headway of one hour), so that every converted trip becomes frequency-based. Only the trips in `trip_id` are grouped and converted: other trips are never removed, even if they share a group and a slot with converted ones. Trips already listed in

frequencies (with a warning, if listed in `trip_id`), trips not listed in `trips` and trips without any `departure_time` are left unchanged.

This conversion is useful for tools that treat frequency-based trips differently from scheduled ones, such as the `time_window` parameter of `{r5r}`, which draws departure times within the headways of frequency-based trips.

Converting the result back with `frequencies_to_stop_times()` yields the same number of trips in each slot, as long as it has at most 60 trips (one departure per minute). Slots with more trips yield approximately the same number of trips. The departures of the new trips, however, are evenly spaced from the start of the slot.

Existing `_secs` columns in `stop_times` and `frequencies` (e.g. created with `convert_time_to_seconds()`) are used as-is, not recalculated from the time strings, and are filled in for the new frequencies entries.

Examples

```
library(dplyr)

data_path <- system.file("extdata/ber_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

# converts all trips
converted_gtfs <- stop_times_to_frequencies(gtfs)
nrow(gtfs$trips)
nrow(converted_gtfs$trips)
head(converted_gtfs$frequencies)

# converts only the trips of one route
route_trips <- gtfs$trips |>
  filter(route_id == gtfs$trips$route_id[1]) |>
  pull(trip_id)
converted_gtfs <- stop_times_to_frequencies(gtfs, route_trips)

# converting back yields evenly spaced scheduled trips
back_gtfs <- frequencies_to_stop_times(converted_gtfs)
```

validate_gtfs

Validate GTFS feed

Description

Uses MobilityData's **GTFS validator** to perform a GTFS business rule validation. The results are available as an HTML report (if validator v3.1.0 or higher is used) and in JSON format. Please check the complete set of rules used in the validation [here](#). Please note that this function requires a working installation of Java 11 or higher to work. Recent versions of the validator require Java 17 or higher.

Usage

```
validate_gtfs(
  gtfs,
  output_path,
  validator_path,
  overwrite = TRUE,
  html_preview = TRUE,
  pretty_json = FALSE,
  quiet = TRUE,
  n_threads = 1
)
```

Arguments

gtfs	The GTFS to be validated. Can be in the format of a GTFS object, of a path to a GTFS file, of a path to a directory or an URL to a feed.
output_path	A string. The path to the directory that the validator will create and in which the results will be saved to.
validator_path	A string. The path to the GTFS validator, previously downloaded with download_validator() .
overwrite	A logical. Whether to overwrite existing validation results in output_path. Defaults to TRUE.
html_preview	A logical. Whether to show HTML report in a viewer, such as RStudio or a browser. Defaults to TRUE (only works on interactive sessions).
pretty_json	A logical. Whether JSON results should be printed in a readable way, that allows it to be inspected without manually formatting. Defaults to FALSE.
quiet	A logical. Whether to hide informative messages. Defaults to TRUE.
n_threads	An integer between 1 and the number of cores in the running machine. Control how many threads are used during the validation. Defaults to 1.

Value

Invisibly returns the normalized path to the directory where the validation results were saved to.

See Also

Other validation: [download_validator\(\)](#), [list_validator_versions\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
output_path <- tempfile("validation_result")
validator_path <- download_validator(tempdir())
gtfs <- read_gtfs(data_path)

validate_gtfs(gtfs, output_path, validator_path)
list.files(output_path)
```

```
# works with feeds saved to disk
new_output_path <- tempfile("new_validation_result")
validate_gtfs(data_path, new_output_path, validator_path)
list.files(new_output_path)

# and with feeds pointed by an url
newer_output_path <- tempfile("newer_validation_result")
gtfs_url <- "https://github.com/ipea/gtfstools/raw/main/inst/extdata/spo_gtfs.zip"
validate_gtfs(gtfs_url, newer_output_path, validator_path)
list.files(newer_output_path)
```

write_gtfs

Write GTFS files

Description

Writes GTFS objects as GTFS .zip files.

Usage

```
write_gtfs(
  gtfs,
  path,
  files = NULL,
  standard_only = FALSE,
  as_dir = FALSE,
  overwrite = TRUE,
  quiet = TRUE,
  compression_level = 6
)
```

Arguments

gtfs	A GTFS object, as created by read_gtfs() .
path	The path to the .zip file in which the feed should be written to.
files	A character vector containing the name of the elements to be written to the feed. If NULL (the default), all elements inside the GTFS object are written.
standard_only	Whether to write only standard files and fields (defaults to FALSE, which doesn't drop extra files and fields).
as_dir	Whether to write the feed as a directory, instead of a .zip file (defaults to FALSE, which means that the field is written as a zip file).
overwrite	Whether to overwrite existing .zip file (defaults to TRUE).
quiet	Whether to hide log messages and progress bars (defaults to TRUE).

compression_level

A number between 1 and 9 indicating how much the .zip file should be compressed. Lower levels write faster but create larger files. Defaults to 6, which is usually several times faster than 9 and creates files of very similar size. Ignored when as_dir = TRUE.

Value

Invisibly returns the same GTFS object passed to the gtfs parameter.

See Also

Other io functions: [read_gtfs\(\)](#)

Examples

```
data_path <- system.file("extdata/spo_gtfs.zip", package = "gtfstools")
gtfs <- read_gtfs(data_path)

tmp_dir <- file.path(tempdir(), "tmpdir")
dir.create(tmp_dir)
list.files(tmp_dir) #'
tmp_file <- tempfile(pattern = "gtfs", tmpdir = tmp_dir, fileext = ".zip")
write_gtfs(gtfs, tmp_file)
list.files(tmp_dir)

gtfs_all_files <- read_gtfs(tmp_file)
names(gtfs_all_files)

write_gtfs(gtfs, tmp_file, files = "stop_times")
gtfs_stop_times <- read_gtfs(tmp_file)
names(gtfs_stop_times)
```

Index

* filtering functions

- `filter_by_agency_id`, 11
- `filter_by_date`, 12
- `filter_by_period`, 13
- `filter_by_route_id`, 15
- `filter_by_route_type`, 16
- `filter_by_service_id`, 19
- `filter_by_shape_id`, 21
- `filter_by_spatial_extent`, 22
- `filter_by_stop_id`, 23
- `filter_by_time_of_day`, 25
- `filter_by_trip_id`, 28
- `filter_by_weekday`, 29

* io functions

- `read_gtfs`, 72
- `write_gtfs`, 90

* validation

- `download_validator`, 10
- `list_validator_versions`, 70
- `validate_gtfs`, 88

`as_dt_gtfs`, 3

`convert_sf_to_shapes`, 5

`convert_sf_to_shapes()`, 4, 8

`convert_shapes_to_sf`, 6

`convert_stops_to_sf`, 6

`convert_stops_to_shapes`, 7

`convert_time_to_seconds`, 8

`convert_time_to_seconds()`, 26, 33, 40, 54, 61, 66, 68, 69, 77, 81, 88

`data.table::fread()`, 73

`download_validator`, 10

`download_validator()`, 71, 89

`filter_by_agency_id`, 11

`filter_by_agency_id()`, 12, 14, 15, 19–22, 24, 27–29

`filter_by_date`, 12

`filter_by_date()`, 11, 14, 15, 19–22, 24, 27–29, 35, 38, 60

`filter_by_period`, 13

`filter_by_period()`, 11, 12, 15, 19–22, 24, 27–29

`filter_by_route_id`, 15

`filter_by_route_id()`, 11, 12, 14, 19–22, 24, 27–29, 57

`filter_by_route_type`, 16

`filter_by_route_type()`, 11, 12, 14, 15, 20–22, 24, 27–29, 59

`filter_by_service_id`, 19

`filter_by_service_id()`, 11, 12, 14, 15, 19, 21, 22, 24, 27–29, 36

`filter_by_sf`, 20

`filter_by_shape_id`, 21

`filter_by_shape_id()`, 11, 12, 14, 15, 19, 20, 22, 24, 27–29

`filter_by_spatial_extent`, 22

`filter_by_spatial_extent()`, 11, 12, 14, 15, 19–21, 24, 27–29

`filter_by_stop_id`, 23

`filter_by_stop_id()`, 11, 12, 14, 15, 19–22, 27–29

`filter_by_time_of_day`, 25

`filter_by_time_of_day()`, 11, 12, 14, 15, 19–22, 24, 28, 29, 42, 53, 60

`filter_by_trip_id`, 28

`filter_by_trip_id()`, 11, 12, 14, 15, 19–22, 24, 27, 29, 57, 75

`filter_by_weekday`, 29

`filter_by_weekday()`, 11, 12, 14, 15, 19–22, 24, 27, 28

`fix_gtfs`, 31

`frequencies_to_stop_times`, 32

`frequencies_to_stop_times()`, 26, 36, 42, 47, 50, 52, 56, 76, 81, 88

`geos_binary_pred`, 22

`get_active_services`, 34

[get_active_services\(\)](#), [14](#), [47](#), [50](#), [55](#), [56](#)
[get_calendar_overlap](#), [35](#)
[get_calendar_overlap\(\)](#), [12](#), [38](#), [60](#)
[get_children_stops](#), [37](#)
[get_children_stops\(\)](#), [40](#), [41](#), [53](#), [56](#), [57](#), [77](#)
[get_dates](#), [38](#)
[get_dates\(\)](#), [14](#), [35](#), [46](#), [47](#), [55](#), [56](#)
[get_dwell_time](#), [39](#)
[get_dwell_time\(\)](#), [76](#), [77](#)
[get_parent_station](#), [41](#)
[get_parent_station\(\)](#), [57](#)
[get_route_frequency](#), [42](#)
[get_route_frequency\(\)](#), [52](#), [60](#), [80](#), [81](#)
[get_route_geometry](#), [43](#)
[get_route_speed](#), [45](#)
[get_route_speed\(\)](#), [68](#), [83](#), [85](#)
[get_route_timetable](#), [46](#)
[get_route_timetable\(\)](#), [56](#)
[get_shape_length](#), [47](#)
[get_shape_length\(\)](#), [65](#)
[get_shapes_geometry](#), [48](#)
[get_shapes_geometry\(\)](#), [6](#), [44](#), [63](#)
[get_start_and_end_times](#), [49](#)
[get_stop_distances](#), [50](#)
[get_stop_frequency](#), [52](#)
[get_stop_times_patterns](#), [53](#)
[get_stop_times_patterns\(\)](#), [80](#), [87](#)
[get_stop_timetable](#), [55](#)
[get_stop_timetable\(\)](#), [47](#)
[get_stops](#), [56](#)
[get_stops\(\)](#), [51](#)
[get_stops_geometry](#), [57](#)
[get_stops_geometry\(\)](#), [6](#), [7](#)
[get_summary](#), [58](#)
[get_trip_duration](#), [61](#)
[get_trip_duration\(\)](#), [50](#), [60](#), [68](#)
[get_trip_geometry](#), [62](#)
[get_trip_geometry\(\)](#), [8](#), [44](#)
[get_trip_length](#), [63](#)
[get_trip_length\(\)](#), [8](#), [48](#), [51](#), [60](#), [63](#), [68–70](#), [79](#), [85](#)
[get_trip_segment_duration](#), [65](#)
[get_trip_segment_duration\(\)](#), [64](#), [65](#), [68](#)
[get_trip_speed](#), [67](#)
[get_trip_speed\(\)](#), [45](#), [60](#), [65](#), [70](#), [79](#), [83](#), [85](#)
[ggplot2::coord_cartesian\(\)](#), [36](#)
[gtfsio::import_gtfs\(\)](#), [3](#)
[interpolate_stop_times](#), [68](#)
[interpolate_stop_times\(\)](#), [31](#), [32](#), [40](#), [76](#)
[list_validator_versions](#), [70](#)
[list_validator_versions\(\)](#), [10](#), [89](#)
[merge_gtfs](#), [71](#)
[merge_gtfs\(\)](#), [36](#)
[read_gtfs](#), [72](#)
[read_gtfs\(\)](#), [3](#), [6](#), [7](#), [9](#), [11–13](#), [15](#), [16](#), [19](#), [21–23](#), [25](#), [28](#), [29](#), [31](#), [33–35](#), [37–39](#), [41–43](#), [45](#), [46](#), [48](#), [49](#), [51](#), [52](#), [54–58](#), [61](#), [62](#), [64](#), [66](#), [67](#), [69](#), [74–76](#), [78](#), [80](#), [82](#), [84](#), [87](#), [90](#), [91](#)
[remove_duplicates](#), [74](#)
[remove_duplicates\(\)](#), [31](#), [32](#), [75](#)
[remove_unused_ids](#), [74](#)
[remove_unused_ids\(\)](#), [8](#), [31](#), [32](#), [81](#)
[set.seed\(\)](#), [33](#)
[set_dwell_time](#), [75](#)
[set_dwell_time\(\)](#), [40](#)
[set_max_speed](#), [78](#)
[set_max_speed\(\)](#), [31](#), [32](#)
[set_route_frequency](#), [80](#)
[set_route_speed](#), [82](#)
[set_route_speed\(\)](#), [45](#), [68](#), [85](#)
[set_trip_speed](#), [84](#)
[set_trip_speed\(\)](#), [45](#), [68](#), [70](#), [77](#), [79](#), [83](#)
[sf::st_equals_exact\(\)](#), [22](#)
[sf::st_intersects](#), [22](#)
[sf::st_is_within_distance\(\)](#), [22](#)
[stop_times_to_frequencies](#), [86](#)
[tempdir\(\)](#), [59](#)
[validate_gtfs](#), [88](#)
[validate_gtfs\(\)](#), [10](#), [58](#), [71](#)
[write_gtfs](#), [90](#)
[write_gtfs\(\)](#), [73](#), [85](#)