

Package: hrbrthemes (via r-universe)

January 16, 2025

Type Package

Title Additional Themes, Theme Components and Utilities for 'ggplot2'

Version 0.90

Date 2025-01-05

Maintainer Bob Rudis <bob@rud.is>

Description A compilation of extra 'ggplot2' themes, scales and utilities, including a spell check function for plot label fields and an overall emphasis on typography. A copy of the 'Google' font 'Roboto Condensed' is also included.

Copyright file inst/COPYRIGHTS

License MIT + file LICENSE

Encoding UTF-8

Suggests testthat, dplyr, gridExtra, hunspell, stringi, gcookbook, clipr, vdiff, svglite

Depends R (>= 4.0.0)

Imports ggplot2 (>= 3.4.0), grDevices, grid, scales, extrafont, tools, magrittr, gdttools, utils

RoxygenNote 7.3.2

Config/pak/sysreqs libcairo2-dev libfontconfig1-dev libfreetype6-dev

Repository <https://ar-puuk.r-universe.dev>

RemoteUrl <https://github.com/hrbrmstr/hrbrthemes>

RemoteRef HEAD

RemoteSha 19100d04fe0203d262f80d7b67ce4a98edc741c6

Contents

flexoki	3
flexoki_dark	4
flexoki_extended	4
flexoki_light	4

flush_ticks	5
font_an	5
font_es	6
font_gs	6
font_inter_thin	7
font_ps	8
font_pub	8
font_rc	9
ft_cols	10
ft_geom_defaults	10
ft_pal	11
gg_check	11
hrbrthemes-exports	12
import_econ_sans	12
import_goldman_sans	13
import_inter	13
import_plex_sans	14
import_public_sans	14
import_roboto_condensed	15
ipsum_pal	15
modern_geom_defaults	16
scale_color_flexoki_continuous	16
scale_color_flexoki_dark	17
scale_color_flexoki_light	17
scale_colour_ft	18
scale_colour_ipsum	19
scale_fill_flexoki_continuous	21
scale_fill_flexoki_dark	21
scale_fill_flexoki_light	22
scale_x_percent	23
theme_ft_rc	26
theme_ipsum	30
theme_ipsum_es	32
theme_ipsum_gs	35
theme_ipsum_inter	37
theme_ipsum_ps	40
theme_ipsum_pub	42
update_geom_font_defaults	44

Description

Color palettes and scales based on the Flexoki color scheme, a warm and soft color system designed by Steph Ango. Flexoki emphasizes readability and natural color harmony, making it particularly suitable for data visualization and long-form reading. The palette includes both light and dark variants, with each offering 8 distinct colors.

The name "Flexoki" combines "flexible" and "karaoke", reflecting its adaptable nature and harmonious color relationships.

Arguments

...	Additional arguments passed to <code>scale_color_manual()</code> or <code>scale_fill_manual()</code>
palette	For continuous scales, the name of the color palette to use (one of "red", "orange", "yellow", "green", "cyan", "blue", "purple", "magenta")

Details

The package provides several types of scales: * Discrete scales for both light and dark variants * Continuous scales with extended color ramps

The color palette includes: * Red: For emphasis and warnings * Orange: For secondary emphasis * Yellow: For highlighting * Green: For success states and nature-related data * Cyan: For information and water-related data * Blue: For primary elements and cool tones * Purple: For luxury and depth * Magenta: For creative and feminine contexts

Value

A `ggplot2` scale object

References

Flexoki Color System: <https://stephango.com/flexoki>

Examples

```
library(ggplot2)

# Discrete color scale (light variant)
ggplot(mpg, aes(class, fill = class)) +
  geom_bar() +
  scale_fill_flexoki_light()

# Continuous color scale
ggplot(faithfuld, aes(waiting, eruptions, fill = density)) +
  geom_tile() +
  scale_fill_flexoki_continuous(palette = "blue")
```

flexoki_dark	<i>Flexoki Dark Color Palette</i>
--------------	-----------------------------------

Description

A vector of 8 colors in the dark variant of the Flexoki color scheme

Usage

flexoki_dark

Format

A named character vector of hex color codes

flexoki_extended	<i>Extended Flexoki Color Palettes</i>
------------------	--

Description

A list of 8 color palettes, each containing 13 shades for continuous color interpolation

Usage

flexoki_extended

Format

A list of character vectors containing hex color codes

flexoki_light	<i>Flexoki Light Color Palette</i>
---------------	------------------------------------

Description

A vector of 8 colors in the light variant of the Flexoki color scheme

Usage

flexoki_light

Format

A named character vector of hex color codes

flush_ticks	<i>Makes axis text labels flush on the ends</i>
-------------	---

Description

A convenience function intended for basic, fixed-scale plots only (i.e. does not handle free scales in facets).

You need to pass in a ggplot2 object to this function. It can't be +'d in a chain of geoms, coords, scales, themes, etc. It also builds the plot (but does not display it) so if the plot takes a while (i.e. has lots of data or transforms) this will also take a while.

Usage

```
flush_ticks(gg, flush = "XY", plot = TRUE, cat = TRUE)
```

Arguments

gg	ggplot2 plot object
flush	either "X" or "Y" or "XY" to flush individual or both axes. Default: both.
plot	if FALSE then the ggplot object will be returned <i>invisibly</i>
cat	if TRUE then display theme() statements and copy them to the clipboard

Value

ggplot2 object with theme() elements added

Note

Intended for basic, fixed-scale plots only (i.e. does not handle free scales in facets).

font_an	<i>Arial Narrow font name R variable aliases</i>
---------	--

Description

```
font_an == "Arial Narrow"
```

Usage

```
font_an
```

Format

length 1 character vector

font_es	<i>Econ Sans Condensed font name R variable aliases</i>
---------	---

Description

```
font_es == "EconSansCndLig"  
font_es_bold == "EconSansCndBol"  
font_es_light == "EconSansCndLig"
```

Usage

```
font_es  
  
font_es_bold  
  
font_es_light
```

Format

```
length 1 character vector  
An object of class character of length 1.  
An object of class character of length 1.
```

Note

```
font_es_bold (a.k.a. "EconSansCndBol") is not available on Windows and will throw a warning  
if used in plots.  
font_es_light (a.k.a. "EconSansCndLig") is not available on Windows and will throw a warning  
if used in plots.
```

font_gs	<i>Goldman Sans font name R variable aliases</i>
---------	--

Description

```
font_gs == "Goldman Sans Condensed"
```

Usage

```
font_gs
```

Format

```
length 1 character vector
```

font_ps	<i>PlexSans font name R variable aliases</i>
---------	--

Description

```
font_ps == "IBMPlexSans"  
font_ps_light == "IBMPlexSans-Light"
```

Usage

```
font_ps  
  
font_ps_light
```

Format

length 1 character vector
An object of class character of length 1.

Note

font_ps_light (a.k.a. "IBMPlexSans-Light") is not available on Windows and will throw a warning if used in plots.

font_pub	<i>Public Sans font name R variable aliases</i>
----------	---

Description

```
font_pub == "Public Sans"  
font_pub_bold == "Public Sans Bold"  
font_pub_light == "Public Sans Light"  
font_pub_thin == "Public Sans Thin"
```

Usage

```
font_pub  
  
font_pub_bold  
  
font_pub_light  
  
font_pub_thin
```


Format

length 1 character vector

An object of class character of length 1.

An object of class character of length 1.

An object of class character of length 1.

Note

font_pub_bold (a.k.a. "Public Sans Bold") is not available on Windows and will throw a warning if used in plots.

font_rc

Roboto Condensed font name R variable aliases

Description

font_rc == "Roboto Condensed"

font_fc_light == "Roboto Condensed Light"

Usage

font_rc

font_rc_light

Format

length 1 character vector

An object of class character of length 1.

Note

font_rc_light (a.k.a. "Roboto Condensed Light") is not available on Windows and will throw a warning if used in plots.

ft_cols	<i>FT color palette</i>
---------	-------------------------

Description

FT color palette

Usage

ft_cols

ft_text_col

Format

An object of class list of length 9.

An object of class character of length 1.

Note

don't forget you can use `scales::alpha()` with these colors

ft_geom_defaults	<i>Change geom defaults from black to custom lights for the FT theme</i>
------------------	--

Description

Change geom defaults from black to custom lights for the FT theme

Usage

ft_geom_defaults()

ft_pal	<i>A bright qualitative color palette</i>
--------	---

Description

A bright qualitative color palette

Usage

```
ft_pal()
```

Examples

```
library(scales)
scales::show_col(ft_pal()(8))
```

gg_check	<i>Spell check ggplot2 plot labels</i>
----------	--

Description

Due to the way ggplot2 objects are created, this has to be used in a standalone context.

Usage

```
gg_check(gg, dict, ignore)
```

Arguments

gg	ggplot2 object
dict	a dictionary object or string which can be passed to hunspell::dictionary . Defaults to <code>hunspell::dictionary("en_US")</code>
ignore	character vector with additional approved words added to the dictionary. Defaults to <code>hunspell::en_stats</code>

Details

Current functionality only looks for misspelled words in the labels of ggplot2 objects. When misspelled words are found, a message is printed with the words and the label that they are in. No messages will be printed if there are no misspelled words.

Value

the object that was passed in

Examples

```
library(ggplot2)

df <- data.frame(x=c(20, 25, 30), y=c(4, 4, 4), txt=c("One", "Two", "Three"))

# not piping
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="This is some txt", y="This is more text",
       title="Thisy is a titlle",
       subtitle="This is a subitley",
       caption="This is a captien") -> gg

gg_check(gg)
```

hrbrthemes-exports	<i>hrbrthemes exported operators</i>
--------------------	--------------------------------------

Description

The following functions are imported and then re-exported from the hrbrthemes package to enable use of the magrittr pipe operator with no additional library calls

import_econ_sans	<i>Import Roboto Condensed font for use in charts</i>
------------------	---

Description

Roboto Condensed is a trademark of Google.

Usage

```
import_econ_sans()
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to `TRUE` – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

import_goldman_sans *Import Goldman Sans font for use in charts*

Description

Goldman Sans is a trademark of Goldman Sachs and distributed under the Goldman Sachs Restricted Font License

Usage

```
import_goldman_sans()
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

import_inter *Import Inter font for use in charts*

Description

Inter is Copyright (c) 2016-2024 The Inter Project Authors

Usage

```
import_inter()
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

import_plex_sans *Import IBM Plex Sans font for use in charts*

Description

IBM Plex Sans is a trademark of IBM and distributed under the SIL Open Font License, Version 1.1.

Usage

```
import_plex_sans()
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to `TRUE` – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

import_public_sans *Import Public Sans font for use in charts*

Description

Public Sans is Copyright 2015 Impallari Type and licensed under the SIL Open Font License, Version 1.1

Usage

```
import_public_sans()
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to `TRUE` – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

`import_roboto_condensed`*Import Roboto Condensed font for use in charts*

Description

Roboto Condensed is a trademark of Google.

Usage

```
import_roboto_condensed()
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to `TRUE` – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Note

This will take care of ensuring PDF/PostScript usage. The location of the font directory is displayed after the base import is complete. It is highly recommended that you install them on your system the same way you would any other font you wish to use in other programs.

`ipsum_pal`*A muted, qualitative color palette*

Description

A muted, qualitative color palette

Usage

```
ipsum_pal()
```

Examples

```
library(scales)
scales::show_col(ipsum_pal()(9))
```

modern_geom_defaults *Change geom defaults from black to white for the modern theme*

Description

Change geom defaults from black to white for the modern theme

Usage

```
modern_geom_defaults()
```

scale_color_flexoki_continuous
Continuous Color Scale Using Flexoki Colors

Description

Continuous Color Scale Using Flexoki Colors

Usage

```
scale_color_flexoki_continuous(palette = "red", ...)
```

Arguments

palette	Name of the color palette to use ("red", "orange", "yellow", "green", "cyan", "blue", "purple", "magenta")
...	Additional arguments passed to scale_color_gradientn()

Value

A continuous ggplot2 color scale

Examples

```
library(ggplot2)
ggplot(faithfuld, aes(waiting, eruptions, fill = density)) +
  geom_tile() +
  scale_color_flexoki_continuous(palette = "blue")
```

`scale_color_flexoki_dark`*Discrete Color Scale Using Flexoki Dark Colors*

Description

Discrete Color Scale Using Flexoki Dark Colors

Usage

```
scale_color_flexoki_dark(...)
```

Arguments

... Additional arguments passed to `scale_color_manual()`

Value

A discrete ggplot2 color scale

Examples

```
library(ggplot2)
ggplot(mtcars, aes(wt, mpg, color = factor(cyl))) +
  geom_point() +
  scale_color_flexoki_dark()
```

`scale_color_flexoki_light`*Discrete Color Scale Using Flexoki Light Colors*

Description

Discrete Color Scale Using Flexoki Light Colors

Usage

```
scale_color_flexoki_light(...)
```

Arguments

... Additional arguments passed to `scale_color_manual()`

Value

A discrete ggplot2 color scale

Examples

```
library(ggplot2)
ggplot(mtcars, aes(wt, mpg, color = factor(cyl))) +
  geom_point() +
  scale_color_flexoki_light()
```

 scale_colour_ft

Discrete color & fill scales based on the FT palette

Description

See [ft_pal\(\)](#).

Usage

```
scale_colour_ft(...)
```

```
scale_color_ft(...)
```

```
scale_fill_ft(...)
```

Arguments

... Arguments passed on to [ggplot2::discrete_scale](#)

aesthetics The names of the aesthetics that this scale works with.

scale_name **[Deprecated]** The name of the scale that should be used for error messages associated with this scale.

palette A palette function that when called with a single integer argument (the number of levels in the scale) returns the values that they should take (e.g., [scales::pal_hue\(\)](#)).

name The name of the scale. Used as the axis or legend title. If [waiver\(\)](#), the default, the name of the scale is taken from the first mapping used for that aesthetic. If NULL, the legend title will be omitted.

breaks One of:

- NULL for no breaks
- [waiver\(\)](#) for the default breaks (the scale limits)
- A character vector of breaks
- A function that takes the limits as input and returns breaks as output. Also accepts rlang [lambda](#) function notation.

labels One of:

- NULL for no labels
- [waiver\(\)](#) for the default labels computed by the transformation object
- A character vector giving labels (must be same length as breaks)
- An expression vector (must be the same length as breaks). See [?plot-math](#) for details.

- A function that takes the breaks as input and returns labels as output. Also accepts rlang `lambda` function notation.

limits One of:

- NULL to use the default scale values
- A character vector that defines possible values of the scale and their order
- A function that accepts the existing (automatic) values and returns new ones. Also accepts rlang `lambda` function notation.

na.translate Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify `na.translate = FALSE`.

na.value If `na.translate = TRUE`, what aesthetic value should the missing values be displayed as? Does not apply to position scales where NA is always placed at the far right.

drop Should unused factor levels be omitted from the scale? The default, TRUE, uses the levels that appear in the data; FALSE includes the levels in the factor. Please note that to display every level in a legend, the layer should use `show.legend = TRUE`.

guide A function used to create a guide or its name. See `guides()` for more information.

call The call used to construct the scale for reporting messages.

super The super class to use for the constructed scale

scale_colour_ipsum *Discrete color & fill scales based on the ipsum palette*

Description

See `ipsum_pal()`.

Usage

```
scale_colour_ipsum(...)
```

```
scale_color_ipsum(...)
```

```
scale_fill_ipsum(...)
```

Arguments

... Arguments passed on to `ggplot2::discrete_scale`

aesthetics The names of the aesthetics that this scale works with.

scale_name **[Deprecated]** The name of the scale that should be used for error messages associated with this scale.

palette A palette function that when called with a single integer argument (the number of levels in the scale) returns the values that they should take (e.g., `scales::pal_hue()`).

name The name of the scale. Used as the axis or legend title. If `waiver()`, the default, the name of the scale is taken from the first mapping used for that aesthetic. If `NULL`, the legend title will be omitted.

breaks One of:

- `NULL` for no breaks
- `waiver()` for the default breaks (the scale limits)
- A character vector of breaks
- A function that takes the limits as input and returns breaks as output. Also accepts rlang `lambda` function notation.

labels One of:

- `NULL` for no labels
- `waiver()` for the default labels computed by the transformation object
- A character vector giving labels (must be same length as breaks)
- An expression vector (must be the same length as breaks). See `?plot-math` for details.
- A function that takes the breaks as input and returns labels as output. Also accepts rlang `lambda` function notation.

limits One of:

- `NULL` to use the default scale values
- A character vector that defines possible values of the scale and their order
- A function that accepts the existing (automatic) values and returns new ones. Also accepts rlang `lambda` function notation.

na.translate Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify `na.translate = FALSE`.

na.value If `na.translate = TRUE`, what aesthetic value should the missing values be displayed as? Does not apply to position scales where `NA` is always placed at the far right.

drop Should unused factor levels be omitted from the scale? The default, `TRUE`, uses the levels that appear in the data; `FALSE` includes the levels in the factor. Please note that to display every level in a legend, the layer should use `show.legend = TRUE`.

guide A function used to create a guide or its name. See `guides()` for more information.

call The call used to construct the scale for reporting messages.

super The super class to use for the constructed scale

`scale_fill_flexoki_continuous`*Continuous Fill Scale Using Flexoki Colors*

Description

Continuous Fill Scale Using Flexoki Colors

Usage

```
scale_fill_flexoki_continuous(palette = "red", ...)
```

Arguments

<code>palette</code>	Name of the color palette to use ("red", "orange", "yellow", "green", "cyan", "blue", "purple", "magenta")
<code>...</code>	Additional arguments passed to <code>scale_fill_gradientn()</code>

Value

A continuous ggplot2 fill scale

Examples

```
library(ggplot2)
ggplot(faithfuld, aes(waiting, eruptions, fill = density)) +
  geom_tile() +
  scale_fill_flexoki_continuous(palette = "blue")
```

`scale_fill_flexoki_dark`*Discrete Fill Scale Using Flexoki Dark Colors*

Description

Discrete Fill Scale Using Flexoki Dark Colors

Usage

```
scale_fill_flexoki_dark(...)
```

Arguments

<code>...</code>	Additional arguments passed to <code>scale_fill_manual()</code>
------------------	---

Value

A discrete ggplot2 fill scale

Examples

```
library(ggplot2)
ggplot(mtcars, aes(factor(cyl), fill = factor(cyl))) +
  geom_bar() +
  scale_fill_flexoki_dark()
```

scale_fill_flexoki_light

Discrete Fill Scale Using Flexoki Light Colors

Description

Discrete Fill Scale Using Flexoki Light Colors

Usage

```
scale_fill_flexoki_light(...)
```

Arguments

... Additional arguments passed to scale_fill_manual()

Value

A discrete ggplot2 fill scale

Examples

```
library(ggplot2)
ggplot(mtcars, aes(factor(cyl), fill = factor(cyl))) +
  geom_bar() +
  scale_fill_flexoki_light()
```

scale_x_percent	<i>X & Y scales with opinionated pre-sets for percent & comma label formats</i>
-----------------	---

Description

The `_comma` ones set comma format for axis text and `expand=c(0,0)` (you need to set limits).

Usage

```
scale_x_percent(  
  name = waiver(),  
  breaks = waiver(),  
  minor_breaks = waiver(),  
  guide = waiver(),  
  n.breaks = NULL,  
  labels,  
  limits = NULL,  
  expand = c(0.01, 0),  
  oob = censor,  
  na.value = NA_real_,  
  trans = "identity",  
  transform = "identity",  
  position = "bottom",  
  sec.axis = waiver(),  
  accuracy = 1,  
  scale = 100,  
  prefix = "",  
  suffix = "%",  
  big.mark = " ",  
  decimal.mark = ".",  
  trim = TRUE,  
  ...  
)
```

```
scale_y_percent(  
  name = waiver(),  
  breaks = waiver(),  
  minor_breaks = waiver(),  
  guide = waiver(),  
  n.breaks = NULL,  
  labels,  
  limits = NULL,  
  expand = c(0.01, 0),  
  oob = censor,  
  na.value = NA_real_,  
  trans = "identity",
```

```
    transform = "identity",
    position = "left",
    sec.axis = waiver(),
    accuracy = 1,
    scale = 100,
    prefix = "",
    suffix = "%",
    big.mark = " ",
    decimal.mark = ".",
    trim = TRUE,
    ...
)

scale_x_comma(
  name = waiver(),
  breaks = waiver(),
  minor_breaks = waiver(),
  guide = waiver(),
  n.breaks = NULL,
  labels,
  limits = NULL,
  expand = c(0.01, 0),
  oob = censor,
  na.value = NA_real_,
  trans = "identity",
  transform = "identity",
  position = "bottom",
  sec.axis = waiver(),
  accuracy = 1,
  scale = 1,
  prefix = "",
  suffix = "",
  big.mark = ",",
  decimal.mark = ".",
  trim = TRUE,
  ...
)

scale_y_comma(
  name = waiver(),
  breaks = waiver(),
  minor_breaks = waiver(),
  guide = waiver(),
  n.breaks = NULL,
  labels,
  limits = NULL,
  expand = c(0.01, 0),
  oob = censor,
```



```

na.value = NA_real_,
trans = "identity",
transform = "identity",
position = "left",
sec.axis = waiver(),
accuracy = 1,
scale = 1,
prefix = "",
suffix = "",
big.mark = ",",
decimal.mark = ".",
trim = TRUE,
...
)

```

Arguments

name	The name of the scale. Used as axis or legend title. If <code>waiver()</code> , the default, the name of the scale is taken from the first mapping used for that aesthetic. If <code>NULL</code> , the legend title will be omitted.
breaks	One of: <ul style="list-style-type: none"> • <code>NULL</code> for no breaks • <code>waiver()</code> for the default breaks computed by the transformation object • A numeric vector of positions • A function that takes the limits as input and returns breaks as output
minor_breaks	One of: <ul style="list-style-type: none"> • <code>NULL</code> for no minor breaks • <code>waiver()</code> for the default breaks (one minor break between each major break) • A numeric vector of positions • A function that given the limits returns a vector of minor breaks.
guide	guide A function used to create a guide or its name. See guides() for more information.
n.breaks	An integer guiding the number of major breaks. The algorithm may choose a slightly different number to ensure nice break labels. Will only have an effect if <code>breaks = waiver()</code> . Use <code>NULL</code> to use the default number of breaks given by the transformation.
labels	Specifying overrides the default format (i.e. you really don't want to do that). <code>NULL</code> means no labels.
limits	A numeric vector of length two providing limits of the scale. Use <code>NA</code> to refer to the existing minimum or maximum.
expand	same as in <code>ggplot2</code>
oob	Function that handles limits outside of the scale limits (out of bounds). The default replaces out of bounds values with <code>NA</code> .

na.value	If na.translate = TRUE, what value aesthetic value should missing be displayed as? Does not apply to position scales where NA is always placed at the far right.
trans	(DEPRECATED) Either the name of a transformation object, or the object itself. Built-in transformations include "asn", "atanh", "boxcox", "exp", "identity", "log", "log10", "log1p", "log2", "logit", "probability", "probit", "reciprocal", "reverse" and "sqrt".
transform	Either the name of a transformation object, or the object itself. Built-in transformations include "asn", "atanh", "boxcox", "exp", "identity", "log", "log10", "log1p", "log2", "logit", "probability", "probit", "reciprocal", "reverse" and "sqrt".
position	The position of the axis. "left" or "right" for vertical scales, "top" or "bottom" for horizontal scales
sec.axis	specify a secondary axis
accuracy, scale, prefix, suffix, big.mark, decimal.mark, trim	See [scales::comma_format()] or [scales::percent_format()]
...	passed on to [scales::comma_format()] or [scales::percent_format()]

Details

The `_percent` ones set percent format for axis text and `expand=c(0, 0)` (you need to set limits).

theme_ft_rc	<i>A precise & pristine ggplot2 theme with opinionated defaults and an emphasis on typography</i>
-------------	---

Description

You should `import_roboto_condensed()` first and also install the fonts on your system before trying to use this theme.

Usage

```
theme_ft_rc(
  base_family = "Roboto Condensed",
  base_size = 11.5,
  plot_title_family = base_family,
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = if (.Platform$OS.type == "windows") "Roboto Condensed" else
    "Roboto Condensed Light",
  subtitle_size = 13,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = base_family,
```

```
strip_text_size = 12,
strip_text_face = "plain",
caption_family = if (.Platform$OS.type == "windows") "Roboto Condensed" else
  "Roboto Condensed Light",
caption_size = 9,
caption_face = "plain",
caption_margin = 10,
axis_text_size = base_size,
axis_title_family = base_family,
axis_title_size = 9,
axis_title_face = "plain",
axis_title_just = "rt",
plot_margin = margin(30, 30, 30, 30),
grid = TRUE,
axis = FALSE,
ticks = FALSE
)

theme_modern_rc(
  base_family = "Roboto Condensed",
  base_size = 11.5,
  plot_title_family = base_family,
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = if (.Platform$OS.type == "windows") "Roboto Condensed" else
    "Roboto Condensed Light",
  subtitle_size = 13,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = base_family,
  strip_text_size = 12,
  strip_text_face = "plain",
  caption_family = if (.Platform$OS.type == "windows") "Roboto Condensed" else
    "Roboto Condensed Light",
  caption_size = 9,
  caption_face = "plain",
  caption_margin = 10,
  axis_text_size = base_size,
  axis_title_family = base_family,
  axis_title_size = 9,
  axis_title_face = "plain",
  axis_title_just = "rt",
  plot_margin = margin(30, 30, 30, 30),
  grid = TRUE,
  axis = FALSE,
  ticks = FALSE
)
```

```

theme_ipsum_rc(
  base_family = "Roboto Condensed",
  base_size = 11.5,
  plot_title_family = base_family,
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = if (.Platform$OS.type == "windows") "Roboto Condensed" else
    "Roboto Condensed Light",
  subtitle_size = 13,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = base_family,
  strip_text_size = 12,
  strip_text_face = "plain",
  caption_family = if (.Platform$OS.type == "windows") "Roboto Condensed" else
    "Roboto Condensed Light",
  caption_size = 9,
  caption_face = "plain",
  caption_margin = 10,
  axis_text_size = base_size,
  axis_title_family = base_family,
  axis_title_size = 9,
  axis_title_face = "plain",
  axis_title_just = "rt",
  plot_margin = margin(30, 30, 30, 30),
  panel_spacing = grid::unit(2, "lines"),
  grid_col = "#cccccc",
  grid = TRUE,
  axis_col = "#cccccc",
  axis = FALSE,
  ticks = FALSE
)

```

Arguments

base_family, base_size
 base font family and size

plot_title_family, plot_title_face, plot_title_size,
 plot_title_margin
 plot title family, face, size and margin

subtitle_family, subtitle_face, subtitle_size
 plot subtitle family, face and size

subtitle_margin
 plot subtitle margin bottom (single numeric value)

strip_text_family, strip_text_face, strip_text_size
 facet label font family, face and size

```
caption_family, caption_face, caption_size, caption_margin
    plot caption family, face, size and margin
axis_text_size font size of axis text
axis_title_family, axis_title_face, axis_title_size
    axis title font family, face and size
axis_title_just
    axis title font justification one of [blmcr]
plot_margin plot margin (specify with ggplot2::margin)
grid panel grid (TRUE, FALSE, or a combination of X, x, Y, y)
axis add x or y axes? TRUE, FALSE, "xy"
ticks ticks if TRUE add ticks
panel_spacing panel spacing (use unit())
grid_col grid color
axis_col axis color
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Why Roboto Condensed?

It's free, has tolerable kerning pairs and multiple weights. It's also different than Arial Narrow and the fonts most folks use in `ggplot2` charts.

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 scatterplot example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_rc()

# seminal bar chart

# note: make this font_rc on Windows
update_geom_font_defaults(family=font_rc_light)

count(mpg, class) %>%
  ggplot(aes(class, n)) +
```

```

geom_col() +
geom_text(aes(label=n), nudge_y=3) +
labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
      title="Seminal ggplot2 bar chart example",
      subtitle="A plot that is only useful for demonstration purposes",
      caption="Brought to you by the letter 'g'") +
theme_ipsum_rc(grid="Y") +
theme(axis.text.y=element_blank())

## End(Not run)

```

theme_ipsum

A precise & pristine [ggplot2](#) theme with opinionated defaults and an emphasis on typography

Description

Also has a "dark" / "modern" version for the new RStudio theme

Usage

```

theme_ipsum(
  base_family = "Arial Narrow",
  base_size = 11.5,
  plot_title_family = base_family,
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = base_family,
  subtitle_size = 12,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = base_family,
  strip_text_size = 12,
  strip_text_face = "plain",
  caption_family = base_family,
  caption_size = 9,
  caption_face = "italic",
  caption_margin = 10,
  axis_text_size = base_size,
  axis_title_family = subtitle_family,
  axis_title_size = 9,
  axis_title_face = "plain",
  axis_title_just = "rt",
  plot_margin = margin(30, 30, 30, 30),
  grid_col = "#cccccc",
  grid = TRUE,
  axis_col = "#cccccc",

```

```

    axis = FALSE,
    ticks = FALSE
  )

```

Arguments

```

base_family, base_size
    base font family and size

plot_title_family,    plot_title_face,    plot_title_size,
plot_title_margin
    plot title family, face, size and margin

subtitle_family, subtitle_face, subtitle_size
    plot subtitle family, face and size

subtitle_margin
    plot subtitle margin bottom (single numeric value)

strip_text_family, strip_text_face, strip_text_size
    facet label font family, face and size

caption_family, caption_face, caption_size, caption_margin
    plot caption family, face, size and margin

axis_text_size  font size of axis text

axis_title_family, axis_title_face, axis_title_size
    axis title font family, face and size

axis_title_just
    axis title font justification, one of [blmcr]

plot_margin    plot margin (specify with ggplot2::margin())

grid_col, axis_col
    grid & axis colors; both default to #cccccc

grid
    panel grid (TRUE, FALSE, or a combination of X, x, Y, y)

axis
    add x or y axes? TRUE, FALSE, "xy"

ticks
    ticks if TRUE add ticks

```

Why Arial Narrow?

First and foremost, Arial Narrow is generally installed by default or readily available on any modern system, so it's "free"-ish; plus, it is a condensed font with solid default kerning pairs and geometric numbers.

Building upon theme_ipsum

The function is setup in such a way that you can customize your own one by just wrapping the call and changing the parameters. See source for examples.

Gotchas

There are distinctions between font names and various devices. Names that work for display graphics devices and bitmap ones such as png may not work well for PostScript or PDF ones. You may need two versions of a font-based theme function for them to work in a particular situation. This situation usually only arises when using a newer font with many weights but somewhat irregular internal font name patterns.

There is an option `hrbrthemes.loadfonts` which – if set to `TRUE` – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
        title="Seminal ggplot2 scatterplot example",
        subtitle="A plot that is only useful for demonstration purposes",
        caption="Brought to you by the letter 'g'") +
  theme_ipsum()

# seminal bar chart

update_geom_font_defaults()

count(mpg, class) %>%
  ggplot(aes(class, n)) +
  geom_col() +
  geom_text(aes(label=n), nudge_y=3) +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
        title="Seminal ggplot2 bar chart example",
        subtitle="A plot that is only useful for demonstration purposes",
        caption="Brought to you by the letter 'g'") +
  theme_ipsum(grid="Y") +
  theme(axis.text.y=element_blank())

## End(Not run)
```

theme_ipsum_es

A precise & pristine [ggplot2](#) theme with opinionated defaults and an emphasis on typography

Description

You should `import_econ_sans()` first and install the fonts on your system before trying to use this theme.

Usage

```

theme_ipsum_es(
  base_family = "EconSansCndReg",
  base_size = 11.5,
  plot_title_family = "EconSansCndBol",
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = if (.Platform$OS.type == "windows") "EconSansCndLig" else
    "EconSansCndLig",
  subtitle_size = 13,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = base_family,
  strip_text_size = 12,
  strip_text_face = "plain",
  caption_family = if (.Platform$OS.type == "windows") "EconSansCndLig" else
    "EconSansCndLig",
  caption_size = 9,
  caption_face = "plain",
  caption_margin = 10,
  axis_text_size = base_size,
  axis_title_family = base_family,
  axis_title_size = 9,
  axis_title_face = "plain",
  axis_title_just = "rt",
  plot_margin = margin(30, 30, 30, 30),
  panel_spacing = grid::unit(2, "lines"),
  grid_col = "#cccccc",
  grid = TRUE,
  axis_col = "#cccccc",
  axis = FALSE,
  ticks = FALSE
)

```

Arguments

base_family, base_size
 base font family and size

plot_title_family, plot_title_face, plot_title_size,
 plot_title_margin
 plot title family, face, size and margin

subtitle_family, subtitle_face, subtitle_size
 plot subtitle family, face and size

subtitle_margin
 plot subtitle margin bottom (single numeric value)

strip_text_family, strip_text_face, strip_text_size
 facet label font family, face and size

```
caption_family, caption_face, caption_size, caption_margin
    plot caption family, face, size and margin
axis_text_size font size of axis text
axis_title_family, axis_title_face, axis_title_size
    axis title font family, face and size
axis_title_just
    axis title font justification one of [blmcr]
plot_margin plot margin (specify with ggplot2::margin)
panel_spacing panel spacing (use unit())
grid_col grid color
grid panel grid (TRUE, FALSE, or a combination of X, x, Y, y)
axis_col axis color
axis add x or y axes? TRUE, FALSE, "xy"
ticks ticks if TRUE add ticks
```

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Why Econ Sans Condensed?

It's free, has tolerable kerning pairs and multiple weights. It's also different than Arial Narrow and the fonts most folks use in `ggplot2` charts.

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 scatterplot example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_es()

# seminal bar chart

# note: may need to make this font_es on Windows
update_geom_font_defaults(family=font_es_light)

count(mpg, class) %>%
  ggplot(aes(class, n)) +
```

```

geom_col() +
geom_text(aes(label=n), nudge_y=3) +
labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
      title="Seminal ggplot2 bar chart example",
      subtitle="A plot that is only useful for demonstration purposes",
      caption="Brought to you by the letter 'g'") +
theme_ipsum_es(grid="Y") +
theme(axis.text.y=element_blank())

## End(Not run)

```

theme_ipsum_gs	<i>A precise & pristine ggplot2 theme with opinionated defaults and an emphasis on typography</i>
----------------	---

Description

You should `import_goldman_sans()` first and install the fonts on your system before trying to use this theme.

Usage

```

theme_ipsum_gs(
  base_family = "Goldman Sans Condensed",
  base_size = 11.5,
  plot_title_family = "Goldman Sans Condensed",
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = if (.Platform$OS.type == "windows") "Goldman Sans Condensed" else
    "Goldman Sans Condensed",
  subtitle_size = 13,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = "Goldman Sans Condensed",
  strip_text_size = 12,
  strip_text_face = "bold",
  caption_family = if (.Platform$OS.type == "windows") "Goldman Sans Condensed" else
    "Goldman Sans Condensed",
  caption_size = 9,
  caption_face = "plain",
  caption_margin = 10,
  axis_text_size = 9,
  axis_title_family = base_family,
  axis_title_size = 9,
  axis_title_face = "plain",
  axis_title_just = "rt",
  plot_margin = margin(30, 30, 30, 30),

```

```

  grid_col = "#cccccc",
  grid = TRUE,
  axis_col = "#cccccc",
  axis = FALSE,
  ticks = FALSE
)

```

Arguments

base_family, base_size	base font family and size
plot_title_family, plot_title_face, plot_title_size, plot_title_margin	plot title family, face, size and margin
subtitle_family, subtitle_face, subtitle_size	plot subtitle family, face and size
subtitle_margin	plot subtitle margin bottom (single numeric value)
strip_text_family, strip_text_face, strip_text_size	facet label font family, face and size
caption_family, caption_face, caption_size, caption_margin	plot caption family, face, size and margin
axis_text_size	font size of axis text
axis_title_family, axis_title_face, axis_title_size	axis title font family, face and size
axis_title_just	axis title font justification one of [blmcr]t]
plot_margin	plot margin (specify with ggplot2::margin)
grid_col	grid color
grid	panel grid (TRUE, FALSE, or a combination of X, x, Y, y)
axis_col	axis color
axis	add x or y axes? TRUE, FALSE, "xy"
ticks	ticks if TRUE add ticks

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Why Goldman Sans?

Google "goldman sans design system"

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 scatterplot example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_gs()

# seminal bar chart

update_geom_font_defaults(family=font_gs_light)

count(mpg, class) %>%
  ggplot(aes(class, n)) +
  geom_col() +
  geom_text(aes(label=n), nudge_y=3) +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 bar chart example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_gs(grid="Y") +
  theme(axis.text.y=element_blank())

## End(Not run)
```

theme_ipsum_inter	<i>A precise & pristine ggplot2 theme with opinionated defaults and an emphasis on typography</i>
-------------------	---

Description

You should `import_inter()` first and install the fonts on your system before trying to use this theme.

Usage

```
theme_ipsum_inter(
  base_family = "Inter-Medium",
  base_size = 10,
  plot_title_family = "Inter-Bold",
  plot_title_size = 16,
  plot_title_face = "bold",
  plot_title_margin = 8,
```

```

    subtitle_family = "Inter-Light",
    subtitle_size = 12,
    subtitle_face = "plain",
    subtitle_margin = 13,
    strip_text_family = "Inter-SemiBold",
    strip_text_size = 12,
    strip_text_face = "bold",
    caption_family = "Inter-Thin",
    caption_size = 9,
    caption_face = "plain",
    caption_margin = 10,
    axis_text_family = "Inter-Light",
    axis_text_face = "plain",
    axis_text_size = 9,
    axis_title_family = base_family,
    axis_title_size = 9,
    axis_title_face = "plain",
    axis_title_just = "rt",
    plot_margin = margin(30, 30, 30, 30),
    grid_col = "#cccccc",
    grid = TRUE,
    axis_col = "#cccccc",
    axis = FALSE,
    ticks = FALSE
)

```

Arguments

```

base_family, base_size
    base font family and size

plot_title_family,      plot_title_face,      plot_title_size,
plot_title_margin
    plot title family, face, size and margin

subtitle_family, subtitle_face, subtitle_size
    plot subtitle family, face and size

subtitle_margin
    plot subtitle margin bottom (single numeric value)

strip_text_family, strip_text_face, strip_text_size
    facet label font family, face and size

caption_family, caption_face, caption_size, caption_margin
    plot caption family, face, size and margin

axis_text_family, axis_text_face
    axis text font family and face

axis_text_size
    font size of axis text

axis_title_family, axis_title_face, axis_title_size
    axis title font family, face and size

```

axis_title_just	axis title font justification one of [blmcr]t]
plot_margin	plot margin (specify with <code>ggplot2::margin</code>)
grid_col	grid color
grid	panel grid (TRUE, FALSE, or a combination of X, x, Y, y)
axis_col	axis color
axis	add x or y axes? TRUE, FALSE, "xy"
ticks	ticks if TRUE add ticks

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Why Inter?

Google "inter font".

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 scatterplot example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_inter()

# seminal bar chart

update_geom_font_defaults(family=font_inter_medium)

count(mpg, class) %>%
  ggplot(aes(class, n)) +
  geom_col() +
  geom_text(aes(label=n), nudge_y=3) +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 bar chart example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_inter(grid="Y") +
  theme(axis.text.y=element_blank())

## End(Not run)
```

theme_ipsum_ps	<i>A precise & pristine ggplot2 theme with opinionated defaults and an emphasis on typography</i>
----------------	---

Description

You should `import_plex_sans()` first and install the fonts on your system before trying to use this theme.

Usage

```
theme_ipsum_ps(  
  base_family = "IBMPlexSans",  
  base_size = 11.5,  
  plot_title_family = "IBMPlexSans-Bold",  
  plot_title_size = 18,  
  plot_title_face = "plain",  
  plot_title_margin = 10,  
  subtitle_family = if (.Platform$OS.type == "windows") "IBMPlexSans" else  
    "IBMPlexSans-Light",  
  subtitle_size = 13,  
  subtitle_face = "plain",  
  subtitle_margin = 15,  
  strip_text_family = "IBMPlexSans-Medium",  
  strip_text_size = 12,  
  strip_text_face = "plain",  
  caption_family = if (.Platform$OS.type == "windows") "IBMPlexSans" else  
    "IBMPlexSans-Thin",  
  caption_size = 9,  
  caption_face = "plain",  
  caption_margin = 10,  
  axis_text_size = 9,  
  axis_title_family = base_family,  
  axis_title_size = 9,  
  axis_title_face = "plain",  
  axis_title_just = "rt",  
  plot_margin = margin(30, 30, 30, 30),  
  grid_col = "#cccccc",  
  grid = TRUE,  
  axis_col = "#cccccc",  
  axis = FALSE,  
  ticks = FALSE  
)
```

Arguments

`base_family`, `base_size`
base font family and size

plot_title_family, plot_title_margin	plot_title_face,	plot_title_size,
	plot title family, face, size and margin	
subtitle_family, subtitle_margin	subtitle_face, subtitle_size	
	plot subtitle family, face and size	
	plot subtitle margin bottom (single numeric value)	
strip_text_family, caption_family, axis_text_size	strip_text_face, caption_face, axis_title_family, axis_title_size	strip_text_size, caption_size, axis_title_size
	facet label font family, face and size	
	plot caption family, face, size and margin	
	font size of axis text	
	axis title font family, face and size	
axis_title_just	axis title font justification one of [blmcr]	
plot_margin	plot margin (specify with <code>ggplot2::margin</code>)	
grid_col	grid color	
grid	panel grid (TRUE, FALSE, or a combination of X, x, Y, y)	
axis_col	axis color	
axis	add x or y axes? TRUE, FALSE, "xy"	
ticks	ticks if TRUE add ticks	

Details

There is an option `hrbrthemes.loadfonts` which – if set to TRUE – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Why IBM Plex Sans?

It's free, has tolerable kerning pairs and multiple weights. It's also different "not Helvetica".

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 scatterplot example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_rc()
```

```

# seminal bar chart

# note: make this font_rc on Windows
update_geom_font_defaults(family=font_rc_light)

count(mpg, class) %>%
  ggplot(aes(class, n)) +
  geom_col() +
  geom_text(aes(label=n, nudge_y=3)) +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 bar chart example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_ipsum_rc(grid="Y") +
  theme(axis.text.y=element_blank())

## End(Not run)

```

theme_ipsum_pub	<i>A precise & pristine ggplot2 theme with opinionated defaults and an emphasis on typography</i>
-----------------	---

Description

You should `import_public_sans()` first and install the fonts on your system before trying to use this theme.

Usage

```

theme_ipsum_pub(
  base_family = "Public Sans",
  base_size = 10.5,
  plot_title_family = if (.Platform$OS.type == "windows") "Public Sans" else
    "Public Sans Bold",
  plot_title_size = 18,
  plot_title_face = "bold",
  plot_title_margin = 10,
  subtitle_family = if (.Platform$OS.type == "windows") "Public Sans Thin" else
    "Public Sans Thin",
  subtitle_size = 13,
  subtitle_face = "plain",
  subtitle_margin = 15,
  strip_text_family = base_family,
  strip_text_size = 12,
  strip_text_face = "plain",
  caption_family = if (.Platform$OS.type == "windows") "Public Sans Thin" else
    "Public Sans Thin",

```

```

caption_size = 9,
caption_face = "plain",
caption_margin = 10,
axis_text_size = base_size,
axis_title_family = base_family,
axis_title_size = 9,
axis_title_face = "plain",
axis_title_just = "rt",
plot_margin = margin(30, 30, 30, 30),
grid_col = "#cccccc",
grid = TRUE,
axis_col = "#cccccc",
axis = FALSE,
ticks = FALSE
)

```

Arguments

base_family, base_size
base font family and size

plot_title_family, plot_title_face, plot_title_size,
plot_title_margin
plot title family, face, size and margin

subtitle_family, subtitle_face, subtitle_size
plot subtitle family, face and size

subtitle_margin
plot subtitle margin bottom (single numeric value)

strip_text_family, strip_text_face, strip_text_size
facet label font family, face and size

caption_family, caption_face, caption_size, caption_margin
plot caption family, face, size and margin

axis_text_size font size of axis text

axis_title_family, axis_title_face, axis_title_size
axis title font family, face and size

axis_title_just
axis title font justification one of [blmcr]t]

plot_margin plot margin (specify with [ggplot2::margin](#))

grid_col grid color

grid panel grid (TRUE, FALSE, or a combination of X, x, Y, y)

axis_col axis color

axis add x or y axes? TRUE, FALSE, "xy"

ticks ticks if TRUE add ticks

Details

There is an option `hrbrthemes.loadfonts` which – if set to `TRUE` – will call `extrafont::loadfonts()` to register non-core fonts with R PDF & PostScript devices. If you are running under Windows, the package calls the same function to register non-core fonts with the Windows graphics device.

Why Public Sans?

See [the design principles](#).

Examples

```
## Not run:
library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
        title="Seminal ggplot2 scatterplot example",
        subtitle="A plot that is only useful for demonstration purposes",
        caption="Brought to you by the letter 'g'") +
  theme_ipsum_pub()

# seminal bar chart

update_geom_font_defaults(family=font_pub)

count(mpg, class) %>%
  ggplot(aes(class, n)) +
  geom_col() +
  geom_text(aes(label=n), nudge_y=3) +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
        title="Seminal ggplot2 bar chart example",
        subtitle="A plot that is only useful for demonstration purposes",
        caption="Brought to you by the letter 'g'") +
  theme_ipsum_pub(grid="Y") +
  theme(axis.text.y=element_blank())

## End(Not run)
```

```
update_geom_font_defaults
```

Update matching font defaults for text geoms

Description

Updates `[ggplot2::geom_label]` and `[ggplot2::geom_text]` font defaults

Usage

```
update_geom_font_defaults(  
  family = "Arial Narrow",  
  face = "plain",  
  size = 3.5,  
  color = "#2b2b2b"  
)
```

Arguments

family, face, size, color
font family name, face, size and color

Index

* datasets

- flexoki_dark, 4
- flexoki_extended, 4
- flexoki_light, 4
- font_an, 5
- font_es, 6
- font_gs, 6
- font_inter_thin, 7
- font_ps, 8
- font_pub, 8
- font_rc, 9
- ft_cols, 10

%>% (hrbrthemes-exports), 12

- flexoki, 3
- flexoki_dark, 4
- flexoki_extended, 4
- flexoki_light, 4
- flush_ticks, 5
- font_an, 5
- font_es, 6
- font_es_bold (font_es), 6
- font_es_light (font_es), 6
- font_gs, 6
- font_inter_bold (font_inter_thin), 7
- font_inter_italic (font_inter_thin), 7
- font_inter_medium (font_inter_thin), 7
- font_inter_medium_italic (font_inter_thin), 7
- font_inter_semibold (font_inter_thin), 7
- font_inter_thin, 7
- font_inter_thin_italic (font_inter_thin), 7
- font_ps, 8
- font_ps_light (font_ps), 8
- font_pub, 8
- font_pub_bold (font_pub), 8
- font_pub_light (font_pub), 8
- font_pub_thin (font_pub), 8
- font_rc, 9
- font_rc_light (font_rc), 9
- ft_cols, 10
- ft_geom_defaults, 10
- ft_pal, 11
- ft_pal(), 18
- ft_text_col (ft_cols), 10

gg_check, 11

ggplot2, 26, 30, 32, 35, 37, 40, 42

ggplot2::discrete_scale, 18, 19

ggplot2::margin, 29, 34, 36, 39, 41, 43

guides(), 19, 20, 25

hrbrthemes-exports, 12

hunspell::dictionary, 11

- import_econ_sans, 12
- import_econ_sans(), 32
- import_goldman_sans, 13
- import_goldman_sans(), 35
- import_inter, 13
- import_inter(), 37
- import_plex_sans, 14
- import_plex_sans(), 40
- import_public_sans, 14
- import_public_sans(), 42
- import_roboto_condensed, 15
- import_roboto_condensed(), 26
- ipsum_pal, 15
- ipsum_pal(), 19

lambda, 18–20

modern_geom_defaults, 16

- scale_color_flexoki_continuous, 16
- scale_color_flexoki_dark, 17
- scale_color_flexoki_light, 17
- scale_color_ft (scale_colour_ft), 18
- scale_color_ipsum (scale_colour_ipsum), 19

scale_colour_ft, 18
scale_colour_ipsum, 19
scale_fill_flexoki_continuous, 21
scale_fill_flexoki_dark, 21
scale_fill_flexoki_light, 22
scale_fill_ft (scale_colour_ft), 18
scale_fill_ipsum (scale_colour_ipsum),
19
scale_x_comma (scale_x_percent), 23
scale_x_percent, 23
scale_y_comma (scale_x_percent), 23
scale_y_percent (scale_x_percent), 23
scales::alpha(), 10
scales::pal_hue(), 18, 20

theme_ft_rc, 26
theme_ipsum, 30
theme_ipsum_es, 32
theme_ipsum_gs, 35
theme_ipsum_inter, 37
theme_ipsum_ps, 40
theme_ipsum_pub, 42
theme_ipsum_rc (theme_ft_rc), 26
theme_modern_rc (theme_ft_rc), 26

update_geom_font_defaults, 44