

Package: paletteer (via r-universe)

January 1, 2025

Title Comprehensive Collection of Color Palettes

Version 1.6.0.9000

Author See AUTHORS file.

Maintainer Emil Hvitfeldt <emilhhvitfeldt@gmail.com>

Description The choices of color palettes in R can be quite overwhelming with palettes spread over many packages with many different APIs. This packages aims to collect all color palettes across the R ecosystem under the same package with a streamlined API.

License GPL-3

URL <https://emilhhvitfeldt.github.io/paletteer/>,
<https://github.com/EmilHvitfeldt/paletteer>

BugReports <https://github.com/EmilHvitfeldt/paletteer/issues>

Depends R (>= 2.10)

Imports prismatic, rematch2, rlang, rstudioapi

Suggests covr, ggplot2 (>= 3.3.0), ggthemes (>= 4.0.0), harrypotter (>= 2.1.0), knitr, oompaBase, palr, pals, rmarkdown, scico, testthat (>= 2.1.0), vdiff, viridisLite

Copyright See LICENSE.note file.

Config/testthat/edition 3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.0

Repository <https://ar-puuk.r-universe.dev>

RemoteUrl <https://github.com/EmilHvitfeldt/paletteer>

RemoteRef HEAD

RemoteSha d8db67b68309c0578c2fb7de3ce407254782dc52

Contents

ggplot2-scales-binned	2
ggplot2-scales-continuous	3
paletteer-c-wrapper	4
paletteer_c	4
paletteer_d	5
paletteer_dynamic	6
paletteer_packages	6
palettes_c_names	7
palettes_d	7
palettes_dynamic	8
palettes_dynamic_names	8
palettes_d_names	9
scale_colour_paletteer_d	10
Index	11

ggplot2-scales-binned *Binned scales to use for ggplot2*

Description

These functions provide the option to use binned palettes along with the ggplot2 package. It goes without saying that it requires ggplot2 to work.

Usage

```
scale_colour_paletteer_binned(palette, direction = 1, ...)
```

```
scale_color_paletteer_binned(palette, direction = 1, ...)
```

```
scale_fill_paletteer_binned(palette, direction = 1, ...)
```

Arguments

palette	Name of palette as a string. Must be on the form <code>packagename::palettename</code> .
direction	Either 1 or -1. If -1 the palette will be reversed.
...	Arguments to pass on to <code>ggplot2::scale_colour_stepsn()</code> or <code>ggplot2::scale_fill_stepsn()</code>

Details

Available package/palette combinations are available in the data.frame [palettes_c_names](#).

Value

A ScaleContinuous object that can be added to a ggplot object

Examples

```
library(ggplot2)
ggplot(iris, aes(x = Sepal.Length, y = Sepal.Width, colour = Petal.Length)) +
  geom_point() +
  scale_colour_paletteer_binned("scico::tokyo")
```

ggplot2-scales-continuous

Continuous scales to use for ggplot2

Description

These functions provide the option to use continuous palettes along with the ggplot2 package. It goes without saying that it requires ggplot2 to work.

Usage

```
scale_colour_paletteer_c(palette, direction = 1, ...)
```

```
scale_color_paletteer_c(palette, direction = 1, ...)
```

```
scale_fill_paletteer_c(palette, direction = 1, ...)
```

Arguments

palette Name of palette as a string. Must be on the form `packagename::palettename`.

direction Either 1 or -1. If -1 the palette will be reversed.

... Arguments to pass on to `ggplot2::scale_colour_gradientn()` or `ggplot2::scale_fill_gradientn()`.

Details

Available package/palette combinations are available in the data.frame [palettes_c_names](#).

Value

A `ScaleContinuous` object that can be added to a ggplot object

Examples

```
library(ggplot2)
ggplot(iris, aes(x = Sepal.Length, y = Sepal.Width, colour = Petal.Length)) +
  geom_point() +
  scale_colour_paletteer_c("scico::tokyo")
```

paletteer-c-wrapper *Wrappers around continuous palette functions by package*

Description

These functions provide a function wrapper for each package such that a palette can be generated using only the name of the desired palette and the length.

Usage

```
paletteer_c_ggthemes(name, n)
paletteer_c_grDevices(name, n)
paletteer_c_oompaBase(name, n)
paletteer_c_palr(name, n)
paletteer_c_pals(name, n)
paletteer_c_scico(name, n)
paletteer_c_viridis(name, n)
paletteer_c_harrypotter(name, n)
```

Arguments

name	Character, name of palette.
n	Integer, number of colors.

Value

Vector of color values from specified palette.

paletteer_c *Get continuous palette by package and name*

Description

Available package/palette combinations are available in the data.frame [palettes_c_names](#).

Usage

```
paletteer_c(palette, n, direction = 1)
```

Arguments

palette	Name of palette as a string. Must be on the form <code>packagename::palettename</code> .
n	Number of colors desired. Must be supplied.
direction	Either 1 or -1. If -1 the palette will be reversed.

Value

A vector of colors.

Examples

```
paletteer_c("scico::berlin", 100)
```

paletteer_d	<i>Get discrete palette by package and name</i>
-------------	---

Description

Available package/palette combinations are available in the data.frame [palettes_d_names](#).

Usage

```
paletteer_d(palette, n, direction = 1, type = c("discrete", "continuous"))
```

Arguments

palette	Name of palette as a string. Must be on the form <code>packagename::palettename</code> .
n	Number of colors desired. If omitted, returns complete palette.
direction	Either 1 or -1. If -1 the palette will be reversed.
type	Either "discrete" or "continuous". Colors are interpolated if "continuous" is picked. Defaults to "discrete".

Value

A vector of colors.

Examples

```
paletteer_d("nord::frost")
paletteer_d("wesanderson::Royal1", 3)
paletteer_d("Redmonder::dPBIPu0r", 14, type = "continuous")
```

paletteer_dynamic *Get dynamic palette by package and name*

Description

Available package/palette combinations are available in the data.frame [palettes_dynamic_names](#).

Usage

```
paletteer_dynamic(palette, n, direction = 1)
```

Arguments

palette	Name of palette as a string. Must be on the form <code>packagename::palettename</code> .
n	Number of colors desired. If omitted, returns complete palette.
direction	Either 1 or -1. If -1 the palette will be reversed.

Value

A vector of colors.

Examples

```
paletteer_dynamic("ggthemes_solarized::green", 8)
paletteer_dynamic("cartography::sand.pal", 20)
```

paletteer_packages *Names and version information for all packages included*

Description

Names and version information for all packages included

Usage

```
paletteer_packages
```

Format

A data.frame with 3 variables:

Names	character, name of package
Github	character, name of Github repository
github_ver	character, version number on Github
CRAN	logical, is package available on CRAN
CRAN_ver	character, version number on CRAN

palettes_c_names	<i>Names of all continuous palettes</i>
------------------	---

Description

A data.frame of the names and other characteristics of the continuous palettes included in this package.

Usage

```
palettes_c_names
```

Format

A data.frame of 319 observations with 3 variables:

package character, name of package

palette character, name of palette

type character, type of palette

Details

Contains palettes names from the following packages: ggthemes, grDevices, harrypotter, oompaBase, palr, pals, scico, viridis.

palettes_d	<i>Complete list of fixed discrete palettes</i>
------------	---

Description

A list of all the discrete palettes of fixed lengths included in this package. Structured as a list of lists with the first level being each package and the second level being the palettes available in that package.

Usage

```
palettes_d
```

Format

A list of 69 lists.

Details

Contains palettes from the following packages: ButterflyColors, DresdenColor, IslamicArt, LaCroix-Color, Manu, MapPalettes, MetBrewer, MexBrewer, MoMAColors, NatParksPalettes, NineteenEightyR, PNWColors, Polychrome, PrettyCols, RColorBrewer, RSkittleBrewer, Redmonder, awtools, basetheme, beyonce, calecopal, colRoz, colorBlindness, colorblindr, dichromat, dutchmasters, feathers, fishualize, futurevisions, ggpomological, ggprism, ggsci, ggthemes, ggthemr, ghibli, grDevices, impressionist.colors, jcolors, khroma, lisa, ltc, miscpalettes, musculusColors, nationalparkcolors, nba-palettes, nord, ochRe, palettesForR, palettetown, pals, peRReo, rcartocolor, rockthemes, rtist, severance, soilpalettes, suffrager, tayloRswift, tidyquant, trekcolors, tvthemes, unikn, vangogh, vapeplot, vapoRwave, waRhol, werpals, wesanderson, yarr.

data.frame of palette names can be found here [palettes_d_names](#).

palettes_dynamic	<i>Complete list of dynamic palettes</i>
------------------	--

Description

A list of all the dynamic palettes included in this package. Structured as a list of lists with the first level being each package and the second level being the palettes available in that package, and the third level being the palettes for various lengths.

Usage

```
palettes_dynamic
```

Format

A list of 3 lists.

Details

Contains palettes from the following packages: cartography and ggthemes.

Full list of palette names can be found here [palettes_dynamic_names](#).

palettes_dynamic_names	<i>Names of all fixed discrete palettes</i>
------------------------	---

Description

A data.frame of the names and other characteristics of the dynamic palettes included in this package.

Usage

```
palettes_dynamic_names
```


Format

A data.frame of 25 observations with 4 variables:

package character, name of package

palette character, name of palette

length integer, maximal number of colors in palette

type character, type of palette

Details

Contains palettes from the following packages: cartography and ggthemes.

Full list of palette can be found here [palettes_dynamic](#).

palettes_d_names	<i>Names of all fixed discrete palettes</i>
------------------	---

Description

A data.frame of the names and other characteristics of the discrete palettes of fixed lengths included in this package.

Usage

```
palettes_d_names
```

Format

A data.frame of 2415 observations with 4 variables:

package character, name of package

palette character, name of palette

length integer, number of colors in palette

type character, type of palette

Details

Contains palettes names from the following packages: ButterflyColors, DresdenColor, IslamicArt, LaCroixColor, Manu, MapPalettes, MetBrewer, MexBrewer, MoMAColors, NatParksPalettes, NineteenEightyR, PNWColors, Polychrome, PrettyCols, RColorBrewer, RSkittleBrewer, Redmonder, awtools, basetheme, beyonce, calecopal, colRoz, colorBlindness, colorblindr, dichromat, dutchmasters, feathers, fishualize, futurevisions, ggpomological, ggprism, ggsci, ggthemes, ggthemr, ghibli, grDevices, impressionist.colors, jcolors, khroma, lisa, ltc, miscpalettes, musculusColors, nationalparkcolors, nbapalettes, nord, ochRe, palettesForR, palettetown, pals, peRReo, rcartocolor, rockthemes, rtist, severance, soilpalettes, suffrager, taylorSwift, tidyquant, trekcolors, tvthemes, unkn, vangogh, vapeplot, vapoRwave, waRhol, werpals, wesanderson, yarr.

Full list of palette can be found here [palettes_d](#).

`scale_colour_paletteer_d`*Discrete scales to use for ggplot2*

Description

These functions provide the option to use the discrete and dynamic palettes along with the ggplot2 package. It goes without saying that it requires ggplot2 to work.

Usage

```
scale_colour_paletteer_d(palette, direction = 1, dynamic = FALSE, ...)
```

```
scale_color_paletteer_d(palette, direction = 1, dynamic = FALSE, ...)
```

```
scale_fill_paletteer_d(palette, direction = 1, dynamic = FALSE, ...)
```

Arguments

<code>palette</code>	Name of palette as a string. Must be on the form <code>packagename::palettename</code> .
<code>direction</code>	Either 1 or -1. If -1 the palette will be reversed.
<code>dynamic</code>	toggles between the discrete palettes and the dynamic palettes. Defaults to FALSE which indicates discrete palettes.
<code>...</code>	additional arguments to pass to <code>discrete_scale</code>

Details

Available package/palette combinations are available in the dataframe [palettes_d_names](#) and [palettes_dynamic_names](#).

Examples

```
library(ggplot2)
ggplot(iris, aes(x = Sepal.Length, y = Sepal.Width, colour = Species)) +
  geom_point() +
  scale_colour_paletteer_d("nord::frost")
```

Index

* datasets

- paletteer_packages, 6
- palettes_c_names, 7
- palettes_d, 7
- palettes_d_names, 9
- palettes_dynamic, 8
- palettes_dynamic_names, 8

- ggplot2-scales-binned, 2
- ggplot2-scales-continuous, 3

- paletteer-c-wrapper, 4
- paletteer_c, 4
- paletteer_c_ggthemes
 - (paletteer-c-wrapper), 4
- paletteer_c_grDevices
 - (paletteer-c-wrapper), 4
- paletteer_c_harrypotter
 - (paletteer-c-wrapper), 4
- paletteer_c_oompaBase
 - (paletteer-c-wrapper), 4
- paletteer_c_palr (paletteer-c-wrapper), 4
- paletteer_c_pals (paletteer-c-wrapper), 4
- paletteer_c_scico (paletteer-c-wrapper),
4
- paletteer_c_viridis
 - (paletteer-c-wrapper), 4
- paletteer_d, 5
- paletteer_dynamic, 6
- paletteer_packages, 6
- palettes_c_names, 2-4, 7
- palettes_d, 7, 9
- palettes_d_names, 5, 8, 9, 10
- palettes_dynamic, 8, 9
- palettes_dynamic_names, 6, 8, 8, 10

- scale_color_paletteer_binned
 - (ggplot2-scales-binned), 2
- scale_color_paletteer_c
 - (ggplot2-scales-continuous), 3
- scale_color_paletteer_d
 - (scale_colour_paletteer_d), 10
- scale_colour_paletteer_binned
 - (ggplot2-scales-binned), 2
- scale_colour_paletteer_c
 - (ggplot2-scales-continuous), 3
- scale_colour_paletteer_d, 10
- scale_fill_paletteer_binned
 - (ggplot2-scales-binned), 2
- scale_fill_paletteer_c
 - (ggplot2-scales-continuous), 3
- scale_fill_paletteer_d
 - (scale_colour_paletteer_d), 10