

Package: tidymodels (via r-universe)

October 16, 2024

Title Easily Install and Load the 'Tidymodels' Packages

Version 1.2.0.9000

Description The tidy modeling ``verse" is a collection of packages for modeling and statistical analysis that share the underlying design philosophy, grammar, and data structures of the tidyverse.

License MIT + file LICENSE

URL <https://tidymodels.tidymodels.org>,
<https://github.com/tidymodels/tidymodels>

BugReports <https://github.com/tidymodels/tidymodels/issues>

Depends R (>= 3.6)

Imports broom (>= 1.0.5), cli (>= 3.6.2), conflicted (>= 1.2.0), dials (>= 1.2.1), dplyr (>= 1.1.4), ggplot2 (>= 3.5.0), hardhat (>= 1.3.1), infer (>= 1.0.6), modeldata (>= 1.3.0), parsnip (>= 1.2.1), purrr (>= 1.0.2), recipes (>= 1.0.10), rlang (>= 1.1.3), rsample (>= 1.2.1), rstudioapi (>= 0.16.0), tibble (>= 3.2.1), tidyr (>= 1.3.1), tune (>= 1.2.0), workflows (>= 1.1.4), workflowsets (>= 1.1.0), yardstick (>= 1.3.1)

Suggests covr, glue, knitr, rmarkdown, testthat (>= 3.0.0), xml2

VignetteBuilder knitr

Config/Needs/website tidyverse/tidytemplate

Config/testthat/edition 3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Repository <https://ar-puuk.r-universe.dev>

RemoteUrl <https://github.com/tidymodels/tidymodels>

RemoteRef HEAD

RemoteSha a38566f4d8e3ed39e5d53d99ca5c7e76da46298f

Contents

pkg_deps	2
tag_show	2
tidymodels_conflicts	3
tidymodels_packages	4
tidymodels_prefer	4
tidymodels_update	5
Index	6

pkg_deps	<i>List all dependencies</i>
----------	------------------------------

Description

List all dependencies

Usage

```
pkg_deps(x = "tidymodels", recursive = FALSE)
```

Arguments

x	A character string for the packages being evaluated.
recursive	If TRUE, will also list all dependencies of tidymodels packages.

tag_show	<i>Facilities for loading and updating other packages</i>
----------	---

Description

The tidymodels metapackage contains a set of tags for specific topics in modeling and analysis. These can be used to load packages in groups.

Usage

```
tag_show()
tag_attach(tag)
tag_update(tag)
```

Arguments

`tag` A character string for the tag. Current options are: 'Bayesian analysis', 'deep learning', 'ensembles', 'extra models', 'extra recipes', 'feature engineering', 'interpretation', 'parallel processing', 'parameter tuning', 'resampling', 'text analysis', 'time series', and 'visualization'.

Examples

```
tag_show()
```

`tidymodels_conflicts` *Conflicts between the tidymodels and other packages*

Description

This function lists all the conflicts between packages in the tidymodels and other packages that you have loaded.

Usage

```
tidymodels_conflicts()
```

Details

There are four conflicts that are deliberately ignored: `intersect`, `union`, `setequal`, and `setdiff` from `dplyr`. These functions make the base equivalents generic, so shouldn't negatively affect any existing code.

To manage conflicts, you can use the `conflicted` package. To prefer tidymodels functions over other functions, use `tidymodels_prefer()`.

See Also

[tidymodels_prefer\(\)](#)

Examples

```
tidymodels_conflicts()
```

tidymodels_packages *List all packages in the tidymodels*

Description

List all packages in the tidymodels

Usage

```
tidymodels_packages(include_self = TRUE)
```

Arguments

include_self Include tidymodels in the list?

Examples

```
tidymodels_packages()
```

tidymodels_prefer *Resolve conflicts between tidymodels packages and others*

Description

tidymodels_prefer() uses the conflicted package to handle common conflicts with tidymodels and other packages.

Usage

```
tidymodels_prefer(quiet = TRUE)
```

Arguments

quiet If TRUE, all output will be suppressed

Details

The list of conflicts includes several dozen that are known issues with other packages.

Note that the **conflicted** package is used to manage which packages take precedence. Using tidymodels_prefer() will turn on general conflict resolution during the R session.

See Also

[tidymodels_conflicts\(\)](#)

Examples

```
tidymodels_prefer(quiet = FALSE)
```

tidymodels_update	<i>Update tidymodels packages</i>
-------------------	-----------------------------------

Description

This will check to see if all tidymodels packages (and optionally, their dependencies) are up-to-date, and will install after an interactive confirmation.

Usage

```
tidymodels_update(pkg = "tidymodels", recursive = FALSE, ...)
```

Arguments

pkg	A character string for the model being updated.
recursive	If TRUE, will also check all dependencies of tidymodels packages.
...	Extra arguments to pass to utils::install.packages()

Value

Nothing is returned but a message is printed to the console about which packages (if any) should be installed along with code to do so.

Examples

```
## Not run:  
tidymodels_update()  
  
## End(Not run)
```

Index

`pkg_deps`, 2

`tag_attach(tag_show)`, 2

`tag_show`, 2

`tag_update(tag_show)`, 2

`tags(tag_show)`, 2

`tidymodels_conflicts`, 3

`tidymodels_conflicts()`, 4

`tidymodels_packages`, 4

`tidymodels_prefer`, 4

`tidymodels_prefer()`, 3

`tidymodels_update`, 5

`utils::install.packages()`, 5